Lanberg DSP2-1005-12V network switch Unmanaged Gigabit Ethernet (10/100/1000) Black

Gamintojas: **LANBERG** · Modelis: **DSP2-1005-12V** · EAN: **5901969424164** · Prekės kodas: **1002639**



13,90 €

Kaina su PVM

Be PVM: **11,49 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5 x RJ-45 10/100/1000 Mbps ports with automatic connection negotiation
- ✓ Plug-and-play support – product does not require any additional configuration
- ✓ MDI / MDIX support, MAC-learning, MAC-aging
- ✓ Flow control function: Back Pressure @ Half-Duplex and IEEE 802.3x @ Full-Duplex
- ✓ Topology: Star
- ✓ Protocol: CSMA / CD
- ✓ MAC address table support: 2K
- ✓ Switching bandwidth: 10 Gbps
- ✓ Passive cooling for silent switch operation
- ✓ Mounting holes for wall installation





Aprašymas

Lanberg DSP2-1005 is a compact, unmanaged desktop switch equipped with 5 x Gigabit Ethernet RJ-45 ports. The device itself is small and handy with Plug & Play operation principles. Product provides switching functions for 5 x 10/100/1000 Mbps RJ-45 ports with automatic connection negotiation and MDI-MDIX support.

The distinctive feature of the DSP1 and DSP2 series switches is the use of universal 12V power supply, used in many other IP and CCTV surveillance,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

alarm, security, and IT devices. With this solution, the end-users, ISPs, or installers are not forced to use the default power supply, thus the greater freedom in regards to delivering the power to the switch using this voltage. The benefits of using 12V power include:

- Power and data can be routed via this Ethernet cable using PoE technology - in the passive version. One end of the cable is plugged into the 12V passive port, while the other end is separated by a passive adapter. This solution solves 2 issues: power and data. As a result of this, using the same cable, the switch is supplied with the appropriate voltage, and the RJ-45 end of the cable plugged into the switch, allows communication of both devices,

- 12V voltage is present in alarm systems and older CCTV solutions. In such cases, a collective power supply is used, which eliminates the need for any additional energy sources and allows for easy replacement of the main power adapter in case of failure,

- There are many manufacturers on the market offering 12V buffer power supplies offering a jack cable. Such small devices provide power to compact products such as routers and switches. 12V used in the DSP2 series allows you to connect all sorts of buffer power supplies to maintain the device's operation after a power outage,

- Increased stability of the equipment and better current efficiency of the device through the use of higher voltage.

Switch is an ideal solution for domestic use due to its modest size and silent passive cooling. On top of that, black color and elegant slim case fits to almost any interior. Moreover, device is suitable for office applications, including SOHO and SMB. Lanberg switch boasts adequate performance, meeting the requirements established by users in the switch segment.

Automatic recognition and adaptation to the type of connected network cable (solid or strand) feature eliminates the requirement to use only one type of Ethernet cabling, as well as a need for uplink ports, allowing simultaneous reduction of unnecessary costs. The switch supports Half-Duplex and Full-Duplex mode for inter-device connections. Flow control feature allows data flow management, thus avoiding any data transmission blocks on the port when one of the receiving devices is unable to receive enough data.

Lanberg desktop switch guarantees a combination of high-quality, automation and a range of features ensuring stable device operation without any excessive user intervention.

Techninė specifikacija

Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
10G support	No
Auto MDI/MDI-X	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes

Data transmission	
MAC address table	2000 entries
Switching capacity	1 Gbit/s
Design	
Rack mounting	No
Stackable	No
Product colour	Black
Housing material	Plastic
LED indicators	Yes
Power	
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
DC input voltage	12 V
Input current	0.5 A
Power consumption (max)	2.64 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 85%
Weight & dimensions	
Width	65.7 mm
Depth	93 mm
Height	22.3 mm
Weight	140 g
Certificates	
Certification	CE, RoHS
Matmenys ir svoris	
Matmenys (I × P × A)	9,00cm × 10,00cm × 8,00cm

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

› Atitikties deklaracija

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Gamintojo ir saugos informacija

GAMINTOJAS

Lanberg

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

› Atitikties deklaracija