Dahua Technology XVR5116H-4KL-I3/T digital video recorder (DVR) Black

Gamintojas: **DAHUA** · Modelis: **XVR5116H-4KL-I3/T** · EAN: **6937552419834** · Prekės kodas: **1005879**



754,89 €

Kaina su PVM

Be PVM: **623,88 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 16-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and recorder
- ✓ 8-channel AcuPick for analog channels which improves the efficiency of target retrieval
- ✓ 8-channel perimeter protection for analog channels which supports tripwire and intrusion detection powered by AI
- ✓ 4-channel face recognition for analog channels which supports face comparison
- ✓ 16-channel SMD Plus for analog channels or 32-channel SMD by camera which allows the device to trigger accurate alarms for humans and vehicles
- ✓ 16-channel AI Coding saves on storage and bandwidth while maintaining the details of targets in videos
- ✓ Supports HDCVI, AHD, TVI, CVBS and IP video input
- ✓ Supports up to 32-channel IP camera input and each channel can be up to 8 MP. The incoming bandwidth reaches 128 Mbps
- ✓ Supports accessing Wi-Fi cameras, making it suitable for a wide range of scenes
- ✓ Smart H.265+ and H.265 dual-stream video compression





Aprašymas

- 16-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and recorder

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

- 8-channel AcuPick for analog channels which improves the efficiency of target retrieval
- 8-channel perimeter protection for analog channels which supports tripwire and intrusion detection powered by AI
- 4-channel face recognition for analog channels which supports face comparison
- 16-channel SMD Plus for analog channels or 32-channel SMD by camera which allows the device to trigger accurate alarms for humans and vehicles
- 16-channel AI Coding saves on storage and bandwidth while maintaining the details of targets in videos
- Supports HDCVI, AHD, TVI, CVBS and IP video input
- Supports up to 32-channel IP camera input and each channel can be up to 8 MP. The incoming bandwidth reaches 128 Mbps
- Supports accessing Wi-Fi cameras, making it suitable for a wide range of scenes
- Smart H.265+ and H.265 dual-stream video compression

Summary: Dahua Technology XVR5116H-4KL-I3/T. Product colour: Black, Maximum video resolution: 3840 x 2160 pixels, Video compression formats: H.264, H.264+, H.265, H.265+. Video resolutions: 3840 x 2160,1920 x 1080,1280 x 720. Video input channels: 16 channels. Ethernet interface type: Fast Ethernet, Gigabit Ethernet, Supported network protocols: HTTP, HTTPS, TCP/IP, IPv4, IPv6, RTSP, UDP, NTP, DHCP, DNS, SMTP, UPnP, FTP, DDNS, SNMP, P2P, Ethernet LAN data rates: 10,100,1000 Mbit/s. Maximum HDD capacity: 16 TB | Vendor Homepage: https://www.dahuasecurity.com/products/All-Products/HDCVI-Recorders/4K-Value5MP-Series/XVR5116H-4KL-I3/T | Video input channels: 16 | BNC input ports: 16 | HDMI ports quantity: 1 | VGA (D-Sub) output ports: 1 | USB 2.0 ports quantity: 1 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Video RCA outputs: 1 | RS-485 ports: 1 | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet/Gigabit Ethernet | Ethernet LAN (RJ-45) ports: 1 | Ethernet LAN data rates: 10/100/1000 | Supported network protocols: HTTP, HTTPS, TCP/IP, IPv4, IPv6, RTSP, UDP, NTP, DHCP, DNS, SMTP, UPnP, FTP, DDNS, SNMP, P2P | Number of HDDs supported: 1 | Maximum HDD capacity: 16000 | Maximum video resolution: 3840 x 2160 | Audio formats supported: G.711 A-law/G.711u/PCM | Video compression formats: H.264/H.264+/H.265/H.265+ | Backup function: Yes | Video loss detection: Yes | Video motion detection: Yes | Audio input channels: 16 | Audio output channels: 1.0 | Dual stream support: Yes | Graphical user interface (GUI): Yes | Multi-display modes: 1/16/25/36/4/8/9 | Multi-display supported: Yes | Operating system installed: Embedded LINUX | Playback modes: Event/General/Instant/Smart/Tag | Product colour: Black | USB connectivity: Yes | Rack capacity: 1U | Video resolutions: 1280 x 720/1920 x 1080/3840 x 2160 | Power supply type: DC | DC voltage: 12 | Power consumption (typical): 15 | Width: 325 | Depth: 257.1 | Height: 55 | Weight: 1390 | Package width: 374 | Package depth: 119 | Package height: 311 | Package weight: 2060 | Quick start guide: Yes | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -10 - 55 | Storage temperature (T-T): -20 - 60 | Compliance certificates: CE | Unit Calculated Weight: 2.03 | Product Net Weight: 1.39 | Unit Calculated Volume: 0.01337 | Units per Shipping Box: 1 | Unit Width: 11.5 | Units per Pallet: 0 | Shipping Box Height: 31 | Unit Depth: 37.5 | Unit Height: 31 | Name: DVR 16CH HDCVI PENTABRID/XVR5116H-4KL-I3/T DAHUA

Techninė specifikacija

Performance	
Product colour	Black
Maximum video resolution	3840 x 2160 pixels
Video compression formats	H.264, H.264+, H.265, H.265+
Audio formats supported	G.711 A-law, G.711u, PCM
Backup function	Yes
Video loss detection	Yes
Video motion detection	Yes
Playback modes	Instant, General, Tag, Event, Smart
Graphical user interface (GUI)	Yes
Operating system installed	Embedded LINUX
Audio input channels	16 channels
Audio output channels	1.0 channels

USB connectivity	Yes
Multi-display supported	Yes
Multi-display modes	1, 4, 8, 9, 16, 25, 36
Dual stream support	Yes
Rack capacity	1U
Video	
Video resolutions	3840 x 2160,1920 x 1080,1280 x 720
Ports & interfaces	
Video input channels	16 channels
BNC input ports	16
HDMI ports quantity	1
VGA (D-Sub) output ports	1
USB 2.0 ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Video RCA outputs	1
RS-485 ports	1
Network	
Ethernet LAN	Yes
Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Ethernet LAN (RJ-45) ports	1
Supported network protocols	HTTP, HTTPS, TCP/IP, IPv4, IPv6, RTSP, UDP, NTP, DHCP, DNS, SMTP, UPnP, FTP, DDNS, SNMP, P2P
Ethernet LAN data rates	10,100,1000 Mbit/s
Hard drive	
Number of HDDs supported	1
Maximum HDD capacity	16 TB
Power	
Power supply type	DC
DC voltage	12 V
Power consumption (typical)	15 W
Weight & dimensions	
Width	325 mm
Depth	257.1 mm
Height	55 mm
Weight	1.39 kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Packaging data	
Package width	374 mm
Package depth	119 mm
Package height	311 mm
Package weight	2.06 kg
Packaging content	
Quick start guide	Yes
Operational conditions	
Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	10 - 90%
Storage temperature (T-T)	-20 - 60 °C
Technical details	
Compliance certificates	CE
Matmenys ir svoris	
Matmenys (I × P × A)	38,00cm × 12,00cm × 31,00cm

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Greitos pradžios vadovas
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Zhejiang Dahua Technology Co., Ltd
Bin'an Road, Binjiang District No.1187 & 1199, 310053 Hangzhou, CN
dahuasecurity.com

ATSAKINGAS ASMUO ES

Dahua Technology GmbH
Niederkasseler Lohweg 185, 40547 Düsseldorf, DE
dahuasecurity.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt