Dahua Technology HAC-HDW1500TRQ-A-0280B-S3-DIP security camera Turret CCTV security camera Indoor 2880 x 1620 pixels Ceiling/Wall/Pole

Gamintojas: **DAHUA** · Modelis: **HAC-HDW1500TRQ-A-0280B-S3-DIP** · EAN: **6937552413948** · Prekės kodas: **1005892**



46,90 €

Kaina su PVM

Be PVM: **38,76 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Max. 25 fps@5 MP (16:9 video output)
- ✓ Starlight, 3D NR
- ✓ 25 m illumination distance
- ✓ Quick-to-install eyeball saves installation time
- ✓ Built-in MIC
- ✓ 3.6 mm fixed lens (2.8 mm optional)
- ✓ CVI/CVBS/AHD/TVI switchable
- ✓ IP50, 12 VDC





Aprašymas

- Max. 25 fps@5 MP (16:9 video output)
- Starlight, 3D NR
- 25 m illumination distance
- Quick-to-install eyeball saves installation time
- Built-in MIC
- 3.6 mm fixed lens (2.8 mm optional)
- CVI/CVBS/AHD/TVI switchable

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

- IP50, 12 VDC

Summary: Dahua Technology HAC-HDW1500TRQ-A-0280B-S3-DIP. Type: CCTV security camera, Placement supported: Indoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Turret. Minimum illumination: 0.001 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 113.3°. Sensor type: CMOS. Detect distance: 59.8 m, Observe distance: 23.9 m, Recognize distance: 12 m | Vendor Homepage: https://www.dahuasecurity.com/products/All-Products/HDCVI-Cameras/Lite-Series/5MP/Starlight/HAC-HDW1500TRQ-A=S3 | Type: CCTV security camera | Connectivity technology: Wired | Placement supported: Indoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Form factor: Turret | Mounting type: Ceiling/Wall/Pole | Product colour: White | Housing material: Plastic | International Protection (IP) code: IP50 | Camera pan control: Yes | Camera tilt control: Yes | Minimum illumination: 0.001 | Angle of rotation: 360 | Lens viewing angle, horizontal: 113.3 | Lens viewing angle, vertical: 62.1 | Lens viewing angle, diagonal: 134.3 | Tilt angle range: 0 - 78 | Pan range: 0 - 360 | White balance: Area white balance/Auto | Camera shutter type: Electronic | Number of Privacy masking areas: 8 | Progressive scan: Yes | Sensor type: CMOS | Detect distance: 59.8 | Observe distance: 23.9 | Recognize distance: 12 | Identify distance: 6 | Maximum aperture number: 1.6 | Closest focusing distance: 0.8 | Fixed focal length: 2.8 | Night vision: Yes | Night vision distance: 25 | LED type: IR | Number of illumination LEDs: 2 | Maximum resolution: 2880 x 1620 | Total megapixels: 5 | Supported graphics resolutions: 1920 x 1080 (HD 1080)/2560 x 1440/2880 x 1620/960 x 480/960 x 576 | Frame rate: 30 | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Digital Wide Dynamic Range (DWDR): Yes | Highlight Compensation (HLC): Yes | Smart IR: Yes | Signal-to-Noise Ratio (SNR): 65 | Built-in microphone: Yes | Ethernet LAN: No | Wi-Fi: No | Bluetooth: No | Built-in HDD: No | BNC output ports: 1 | DC-in jack: Yes | Mirror: Yes | Power source type: DC | Power consumption (max): 2.9 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Height: 93 | Diameter: 97.1 | Weight: 170 | Compliance certificates: CE | Package weight: 230 | Number of cameras: 1 | Manual: Yes | Unit Calculated Weight: 0.27 | Product Net Weight: 0.17 | Unit Calculated Volume: 0.00165 | Units per Shipping Box: 1 | Unit Width: 12.5 | Units per Pallet: 0 | Shipping Box Height: 11 | Unit Depth: 12 | Unit Height: 11 | Name: CAMERA HDCVI 5MP EYEBALL/HDW1500TRQA0280BS3DIP DAHUA

Techninė specifikacija

Performance	
Type	CCTV security camera
Placement supported	Indoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Design	
Mounting type	Ceiling/Wall/Pole
Product colour	White
Form factor	Turret
Housing material	Plastic
International Protection (IP) code	IP50
Camera	
Camera pan control	Yes
Camera tilt control	Yes
Minimum illumination	0.001 lx
Angle of rotation	360°
Lens viewing angle, horizontal	113.3°

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Lens viewing angle, vertical	62.1°
Lens viewing angle, diagonal	134.3°
Tilt angle range	0 - 78°
Pan range	0 - 360°
White balance	Area white balance, Auto
Camera shutter type	Electronic
Number of Privacy masking areas	8
Image sensor	
Sensor type	CMOS
Progressive scan	Yes
Lens system	
Detect distance	59.8 m
Observe distance	23.9 m
Recognize distance	12 m
Maximum aperture number	1.6
Identify distance	6 m
Fixed focal length	2.8 mm
Closest focusing distance	0.8 m
Night vision	
Night vision	Yes
Night vision distance	25 m
LED type	IR
Number of illumination LEDs	2
Video	
Maximum resolution	2880 x 1620 pixels
Total megapixels	5 MP
Supported graphics resolutions	2880 x 1620, 2560 x 1440, 1920 x 1080 (HD 1080), 960 x 576, 960 x 480
Frame rate	30 fps
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Smart IR	Yes
Audio	
Signal-to-Noise Ratio (SNR)	65 dB
Built-in microphone	Yes
Network	
Ethernet LAN	No
Wi-Fi	No
Bluetooth	No
Storage	
Built-in HDD	No
Ports & interfaces	
BNC output ports	1
DC-in jack	Yes
Security	
Mirror	Yes
Power	
Power source type	DC
Power consumption (max)	2.9 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Weight & dimensions	
Height	93 mm
Diameter	9.71 cm
Weight	170 g
Packaging data	
Package weight	230 g
Sustainability	
Compliance certificates	CE
Packaging content	
Number of cameras	1
Manual	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Matmenys ir svoris	
Matmenys (I × P × A)	12,00cm × 13,00cm × 11,00cm

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Zhejiang Dahua Technology Co., Ltd
Bin'an Road, Binjiang District No.1187 & 1199, 310053 Hangzhou, CN
dahuasecurity.com

ATSAKINGAS ASMUO ES

Dahua Technology GmbH
Niederkasseler Lohweg 185, 40547 Düsseldorf, DE
dahuasecurity.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt