


APC Back-UPS Pro nepertraukiamo maitinimo resursai (UPS) „Line-Interactive“ 1,5 kVA 865 W 10 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **BR1500GI** · EAN: **731304268741** · Prekės kodas: **100785**



572,90 €

Kaina su PVM

Be PVM: **473,47 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ „Line-Interactive“
- ✓ 1,5 kVA 865 W
- ✓ Signalų forma: Sinusas
- ✓ 10 AC išvestis(ys / čių)
- ✓ Rūgštinis akumulatorius (VRLA)
- ✓ Juoda



Aprašymas

This APC Back-UPS Pro offers premium power protection for high performance computer systems, routers/modems, external storage devices, game consoles and other electronics in your home or business. The 1500VA tower UPS has 10 total outlets, 5 of which are battery back up and surge protection, and 5 that are surge protection only. It has a surge energy rating of 441 Joules. Its dimensions are 30.1 x 11.2 x 38 cm and 12.7 kg. The Back-UPS Pro family offers guaranteed power protection for high-performance computer systems, routers, external storage devices, game consoles, and other home and business electronics. This UPS has a 2-year warranty and CE product certification. It is compatible with a dedicated user-replaceable battery, and the APC replacement battery cartridge helps restore UPS performance to the original specifications.

Techninė specifikacija

Features

UPS topology	Line-Interactive
Output power capacity	1.5 kVA
Output power	865 W
Waveform	Sine
Input operation voltage (min)	156 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output frequency regulation	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Surge energy rating	441 J
Hold time (min)	10 ms
Hold time (max)	12 ms
Efficiency	98.9%
Crest factor	3:1
Noise level	45 dB
Surge protection	Yes
Surge protection features	Digital Subscriber Line (DSL), Fax, Modem, Network, Telephone
Audible alarm(s)	Yes
Audible alarm modes	Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	10 AC outlet(s)
Number of output IEC jumpers	2
USB port	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	187 VAh
Typical backup time at full load	3.7 min
Typical backup time at half load	12.4 min
Battery life (max)	5 year(s)
Battery recharge time	8 h
Hot-swap battery	Yes
Automatic battery test	Yes
Cold start	Yes

Replacement battery cartridge	APCRBC124
Design	
Product colour	Black
Display type	LCD
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 40 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 9000 m
Non-operating altitude	0 - 15000 m
Certificates	
Compliance certificates	RoHS
Certification	A-tick, C-tick, CE, GOST, GS Mark, Telepermit, TUV, REACH, PEP, EOLI, NEMKO-GS
Packaging content	
Cables included	Phone (RJ-11), USB cable
Manual	Yes
Sustainability	
Sustainability certificates	ENERGY STAR
Weight & dimensions	
Width	112 mm
Depth	380 mm
Height	301 mm
Weight	12.7 kg
Packaging data	
Warranty card	Yes
Software CD	Yes
Bundled software	PowerChute Personal Edition
Package width	238 mm
Package depth	488 mm
Package height	387 mm
Package weight	14.3 kg
Logistics data	
Products per pallet	20 pc(s)

Harmonized System (HS) code	85078000
Products per master (outer) case	1 pc(s)
Other features	
Nominal output voltage	230 V
Nominal input voltage	230 V
Packaging content	1x Detachable IEC Power Cord
Matmenys ir svoris	
Matmenys (I × P × A)	49,00cm × 40,00cm × 25,00cm
Svoris	13,90kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR
[se.com](https://www.se.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt