# APC Smart-UPS On-Line nepertraukiamo maitinimo resursai (UPS) Dviguba konversija (prisijungus) 6 kVA 6000 W 10 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **SRT6KXLI** · EAN: **731304301660** · Prekės kodas: **100806**




**7 669,90 €**

Kaina su PVM

Be PVM: **6 338,76 €**

**Sandėlyje**


**Prekė internetu**
Nuskenuokite kodą arba apsilankykite www.shopro.lt

## Pagrindinės savybės

- ✓ Dviguba konversija (prisijungus)
- ✓ 6 kVA 6000 W
- ✓ Signalų forma: Sinusas
- ✓ 10 AC išvestis(ys / čių)
- ✓ Rūgštinis akumuliatorius (VRLA)
- ✓ Stelažas / bokštas Juoda











## Aprašymas

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 6kVA on-line tower UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with hard wire 3-wire

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

(1P+N+E) input, 6x IEC 320 C13 and 4x IEC 320 C19 outlets, and 2x IEC jumper cables. The UPS has an embedded Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCI clusters. It has an additional SmartSlot for optional accessory card such as Dry Contact I/O card. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty. The UPS is compatible with SRTRK2 (4-post) and SRTRK3 (2-post) rail kits sold separately. Designed for IT professionals or network administrators providing wide input voltage window, tight output voltage regulation, frequency regulation, internal bypass, and input power factor correction.

## Techninė specifikacija

| | |
|---|---|
| **Features** | |
| UPS topology | Double-conversion (Online) |
| Output power capacity | 6 kVA |
| Output power | 6000 W |
| Waveform | Sine |
| Input operation voltage (min) | 100 V |
| Input operation voltage (max) | 275 V |
| Input frequency | 40 - 70 Hz |
| Output operation voltage (min) | 220 V |
| Output operation voltage (max) | 240 V |
| Output frequency regulation | 50/60 Hz |
| Surge energy rating | 480 J |
| Number of output phases | 1 |
| Efficiency | 94.4% |
| Crest factor | 3:1 |
| Emergency Power Off (EPO) | Yes |
| Output voltage Total Harmonic Distortion (THD) | 3% |
| Noise level | 55 dB |
| Surge protection | Yes |
| Audible alarm(s) | Yes |
| Auto-restart | Yes |
| **Ports & interfaces** | |
| AC outlet types | C13 coupler, C19 coupler |
| Power plug | Hardwire |
| AC outlets quantity | 10 AC outlet(s) |
| Number of output IEC jumpers | 2 |
| USB port | Yes |
| Serial interface | Yes |

| | |
|---|---|
| Serial interface type | RJ-45 |
| SmartSlot | Yes |
| SmartConnect port | No |

## Battery

| | |
|---|---|
| Battery technology | Sealed Lead Acid (VRLA) |
| Battery capacity | 902 VAh |
| Typical backup time at full load | 2.5 min |
| Typical backup time at half load | 8.7 min |
| Battery life (max) | 5 year(s) |
| Battery recharge time | 1.5 h |
| Hot-swap battery | Yes |
| Automatic battery test | Yes |
| Cold start | Yes |

## Design

| | |
|---|---|
| Form factor | Rackmount/Tower |
| Product colour | Black |
| Display type | LCD |
| LED indicators | Status |
| International Protection (IP) code | IP20 |

## Operational conditions

| | |
|---|---|
| Operating temperature (T-T) | 0 - 40 °C |
| Storage temperature (T-T) | -15 - 45 °C |
| Operating relative humidity (H-H) | 0 - 95% |
| Storage relative humidity (H-H) | 0 - 95% |
| Operating altitude | 0 - 3000 m |
| Non-operating altitude | 0 - 15000 m |

## Certificates

| | |
|---|---|
| Compliance certificates | RoHS |
| Certification | REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE |

## Packaging content

| | |
|---|---|
| Cables included | USB cable |
| Management card included | Yes |
| Quick installation guide | Yes |

## Sustainability

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

| | |
|---|---|
| Sustainability certificates | ENERGY STAR |
| **Weight & dimensions** | |
| Width | 174 mm |
| Depth | 719 mm |
| Height | 432 mm |
| Weight | 60 kg |
| **Packaging data** | |
| Temperature sensor | Yes |
| Warranty card | Yes |
| Software CD | Yes |
| Package width | 610 mm |
| Package depth | 960 mm |
| Package height | 370 mm |
| Package weight | 67 kg |
| **Logistics data** | |
| Products per pallet | 6 pc(s) |
| Harmonized System (HS) code | 85078000 |
| Total carbon footprint (kg of CO2e) | 13539.46 |
| **Other features** | |
| Packaging content | Removable support feet Web/SNMP Management Card |
| **Matmenys ir svoris** | |
| Matmenys (I × P × A) | 100,00cm × 65,00cm × 35,00cm |
| Svoris | 55,00kg |

## Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

## Gamintojo ir saugos informacija

GAMINTOJAS

**Schneider Electric SE**
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.