APC SMC1500IC nepertraukiamo maitinimo resursai (UPS) „Line-Interactive“ 1,5 kVA 900 W 8 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **SMC1500IC** · EAN: **731304332961** · Prekės kodas: **100834**



836,90 €

Kaina su PVM

Be PVM: **691,65 €**

Sandėlyje


Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ „Line-Interactive“
- ✓ 1,5 kVA 900 W
- ✓ Signalų forma: Sinusas
- ✓ 8 AC išvestis(ys / čių)
- ✓ Rūgštinis akumuliatorius (VRLA)
- ✓ „Mini Tower“ Juoda

























Aprašymas

Stay always online and prevent data loss

As soon as the power goes out, an APC Smart-UPS immediately provides emergency power to all connected equipment. Because an APC UPS does this automatically, you prevent unwanted failure of, for example, a PC, server or switch. With the free APC PowerChute software you can even have critical IT hardware shut down automatically and in a controlled manner when the battery of the UPS is almost empty. This way you prevent data loss, downtime and physical damage to hardware.

Safety

In addition, a Smart-UPS protects connected devices against peak voltage caused by lightning, among other things. This APC emergency power supply is therefore ideally suited for (small) business use.

SmartConnect

Out-of-box remote UPS monitoring, free for a 6-month trial period. Using the SmartConnect ethernet port, you can easily connect the Smart-UPS to your network and easily monitor it remotely via the secure APC SmartConnect cloud-based web portal*. In addition, the UPS can always be monitored via this port via EcoStruxure IT Expert (SFTWES1-DIGI).

* Extend access to SmartConnect through the following licenses:
1 year Standard Plan: ERWPMON1-1Y-DIGI
3 year Standard Plan: ERWPMON1-3Y-DIGI

1 year Advanced Plan: ERWPLUS1-1Y-DIGI
3 year Advanced Plan: ERWPLUS1-3Y-DIGI

PowerChute

By connecting the UPS to a maximum of one server via a USB cable, it can automatically provide it with a shutdown signal during a prolonged power outage and thus prevent a hard shutdown. This exact moment can be set via the free APC PowerChute Business Edition software.

Ease of use

By means of physical buttons and an LCD screen make it possible to set and read the basic functionalities.

Battery life

You can easily read the expected battery life in the runtime graph, which you can find between the product images. You can easily see how long the UPS supplies emergency power at a certain load.

Extend the lifespan

The internal battery cartridge (RBC6) can be replaced easily, safely and independently by the user. This without having to switch off the APC SMC1500IC or connected equipment. This way you can easily and cheaply extend the lifespan of the APC Smart-UPS and your equipment always remains online.

Warranty extension

The factory warranty of the SMC1500IC is 2 years and you can upgrade to 5 years with the APC service pack (WBEXTWAR3YR-SP-03).

Green Premium

This label represents Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises to comply with the latest regulations, transparency on environmental effects and circular and low CO2 emission products.

Green Premium:
- Stands for an energy-efficient product that helps our customers achieve their CO2 reduction goals and save energy costs at the same time. The energy efficiency of this product is at least 10% higher than the market average.

- Provides insight into the environmental effects of the product, this data is available 24/7 via the digital product environmental profile, see https://checkaproduct.se.com/

- Commits to minimal use of hazardous substances within and beyond regulatory compliance (RoHS-/REACh)

Peace of mind that comes with full equipment compatibility and reliability of a leader

Provides pure sine wave output which is recommended by server manufacturers using active power factor corrected (PFC) power supplies. Safety agency tested and approved means that you can deploy Smart-UPS with confidence that they meet or exceed the industry’s most rigorous standards.

Smarter productivity with ability to tailor to your specific application needs

Intuitive LCD interface provides clear information with the ability to configure the UPS locally with easy to use navigation keys. Over 15 different programmable settings including switched outlet group control allow for application specific settings, thresholds and notifications.

Avoids costly power problems by keeping your IT equipment and data safe and available

Network grade power conditioning protects from damaging surges and disruptive noise. Solid state automatic voltage regulation boosts low input voltage up to 30% and trims high voltage up to 12% without battery operation. Reliable battery back-up capacity to power through outages or gracefully shutdown systems

Low operating and maintenance costs with high efficiency, proven reliability and intelligent battery management

Patented green operating mode achieves efficiencies over 97%. Smart-ups was the first network UPS to be Energy Star certified. Intelligent battery management, pioneered by APC, maximizes battery performance and life through intelligent, precision temperature compensated charging. Dynamic battery replacement date indicator and automatic self tests insure battery reliability and warn in advance of needing replacement. Convenient, easy to connect, hot-swappable battery modules provide battery replacement without powering down. Designed and manufactured by APC for over 23 years, Smart-UPS is the world’s most trusted network UPS with over 25 million units sold.

Save time with easy and convenient remote accessibility

Network manageable via serial, USB or optional ethernet. Includes Powerchute Business Edition Software for convenient monitoring and control, safe operating system shutdown and innovative energy management capabilities.

Techninė specifikacija

Savybės	
UPS topologija	„Line-Interactive“
Išvesties galia (VA)	1,5 kVA
Išvesties galia	900 W
Signalų forma	Sinusas
Įvesties eksploatacinė įtampa (min.)	170 V

Įvesties eksploatacinė įtampa (maks.)	300 V
Įėjimo dažnis	50/60 Hz
Išvesties darbinė įtampa (min.)	220 V
Išvesties darbinė įtampa (maks.)	240 V
Išvesties dažnis	50/60 Hz
Automatinis įtampos reguliavimas (AVR)	Taip
Viršįtampio energijos įvertinimas	459 J
Išvesties įtampa THD	5%
Garso lygis	45 dB
Garsiniai perspėjimo signalai	Taip
Web pagrįstas valdymas	Taip
Garsinio pavojaus signalo režimai	Signalas veikiant su akumuliatoriumi, Senkančio akumuliatoriaus signalas, Perkrovos signalas
Automatinis paleidimas iš naujo	Taip
Temperatūros įtampos kompensavimas	Taip

Ryšys

AC išėjimo tipai	C13 šakotuvas
Maitinimo laido kištukas	C14 šakotuvas
Lizų kiekis	8 AC išvestis(ys / čių)
USB prievadas	Taip
USB 2.0 portų kiekis	1
Nuoseklioji sąsaja	Taip
Serijinių portų kiekis	1
„SmartSlot“	Ne
„SmartConnect“ prievadas	Taip

Baterija

Baterijos technologija	Rūgštinis akumuliatorius (VRLA)
Palaikomų baterijų skaičius	1
Baterijos veikimo trukmė (maks.)	5 metai
Baterijos įkrovimo laikas	3 h
Hot-Swap baterija	Taip
Automatinis baterijos bandymas	Taip
Aušinimo paleidimas	Taip

Konstrukcija

Forma	„Mini Tower“

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Produkto spalva	Juoda
Ekrano tipas	LCD
LED indikatoriai	Taip

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-15 - 45 °C
Darbo santykinės drėgmės diapazonas	0 - 95%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%
Darbinis aukštis	0 - 3000 m
Ne darbinis aukštis	0 - 15000 m

Sertifikatai

Sertifikavimas	C-tick, CE, CSA, GOST, UL 1778, VDE

Pakuotės turinys

Pridėti kabeliai	USB laidas
Pridedama valdymo kortelė	Ne

Tvarumas

Tvarumo sertifikatai	Green Premium

Svoris ir matmenys

Plotis	171 mm
Ilgis	439 mm
Aukštis	219 mm
Svoris	24,1 kg

Pakuotės duomenys

Šaltinis CD	Taip
Programinės įrangos CD	Taip
Pakuotės plotis	328 mm
Pakuotės gylis	595 mm
Pakuotės aukštis	376 mm
Pakuotės tūris	27230 cm³

Logistikos duomenys

Gaminių skaičius ant padėklo	18 vnt
Darniosios sistemos (DS) kodas	85078000
Bendrasis anglies pėdsakas (kg of CO2e)	1090,81

Matmenys ir svoris

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Matmenys (I × P × A)	60,00cm × 35,00cm × 33,00cm
Svoris	23,55kg

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.