APC BVS240XDPDR 24V DC UPS – 240Watt, 24V, 10A, DIN-Rail mounting, Power Module without battery

Gamintojas: **APC** · Modelis: **BVS240XDPDR** · EAN: **731304436942** · Prekės kodas: **1012279**



206,90 €

Kaina su PVM

Be PVM: **170,99 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt









Aprašymas

BVS240XDPDR 24V DC UPS – 240Watt, 24V, 10A, DIN-Rail mounting, Power Module without battery

Protect

your investment and prevent data loss with the new 240Watt 24V DC DIN-rail mounted industrial UPS from Schneider Electric, which provides reliable surge protection and battery backup during power failures in an industrial environment.

This Schneider Electric Industrial UPS enables machine builders and system integrators to:
efficiently manage their automation equipment in the event of a power failure.

Separate battery

The BVS240XDPDR power module is equipped with DC input/output terminals to support PLCs and HMIs, and must be equipped with a minimum of 1 and a maximum of 4 XB005XPDR runtime batteries. This allows for up to one hour of bridging time during power failures under full load. See runtime table for more details. The Industrial DC DIN Rail UPS comes with relay contactors that enable remote management of connected equipment and monitoring of the UPS.

Why consider Schneider Electric Industrial UPS?
-Minimize downtime and protect investments

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

-Helps reduce machine maintenance by enabling safe shutdown of equipment during a power failure and eliminating the need to reset automation machines.
-Gain better control over your industrial infrastructure with remote monitoring and management via relay contactors, external battery backup and LED indicators.

Key features
-24 DC input
Connect the right AC/DC or DC/DC power supply for your application.

-24 DC output

Designed to support industrial equipment such as PLCs, HMIs, industrial PCs that require a 24V DC power supply.

-Relay contactors

Shutdown and manage connected equipment via potential dry contacts.

-Expandable battery capacity

Extend runtime up to 4 batteries (XB005XPDR).

-On/Off button

Remotely turn the UPS on or off when needed.

-2-year warranty

Peace of mind with a 2-year warranty.

-LED indicators

Check the UPS status using LEDs that change from green to red when an event occurs.

Techninė specifikacija

Features	
Output power capacity	0.24 kVA
Output power	240 W
Input operation voltage (min)	21.6 V
Input operation voltage (max)	28.6 V
Output operation voltage (min)	24 V
Output operation voltage (max)	24 V
Design	
Product colour	Grey
Weight & dimensions	
Width	40 mm

Depth	129 mm
Height	119 mm
Weight	500 g
Logistics data	
Harmonized System (HS) code	85078000

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Vaizdo įrašas objects.icecat.biz/objects/97408834_21687023.mp4

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.