FSP H3-650 power supply unit 650 W 24-pin ATX Black

Gamintojas: **FSP GROUP** · Modelis: **9PA6507502** · EAN: **4713224525377** · Prekės kodas: **1012829**



108,90 €

Kaina su PVM

Be PVM: **90,00 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Complies with ATX12V V2.52 & EPS12 v2.92
- ✓ Efficiency ≥ 85% @ typical load
- ✓ Active PFC ≥ 0.9
- ✓ Hold up time > 17ms @80% load
- ✓ 450V, 105°C capacitors for a long product life cycle
- ✓ +12V single-rail design
- ✓ +5V &3.3V DC to DC module design
- ✓ 120mm silent and long life fan
- ✓ All black round cables
- ✓ Complete protection: OCP/OVP/OPP/SCP






Aprašymas

The new HYPER 80+ Pro PSUs comply fully ATX 12 v2.52 standard and latest safety 62368 regulation as well, and features with all black and high-grade ribbon cables, will give your PC a polished look. The HYPER 80+ Pro series is characterized by a powerful single +12V rail design that continually delivers maximum performance for the most demanding components, while FSP’s custom DC-DC design provides safety and power efficiency. With an 230V 80 Plus™ rating, both models deliver over 85% high efficiency and low noise levels thanks to its thermal control fan design, where a large 120mm fan takes care of cooling duties when required, making it excellent for situations that are sensitive to size and noise.

80 Plus® 230V EU White Certification

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

HYPER 80+ PRO series, 80 PLUS® 230V EU White certified, saves energy through its high efficiency up to 82% and excesses the standard through its high efficiency up to 85%.

DC-to-DC Module Design

With a 12V SR circuit and the DC to DC structure, HYPER 80+ PRO series ensure you outstanding conversion efficiency and provides stable output voltage.

450V 105C, Heavy-duty capacitor

The bulk capacitor inside serves to support working under an extremely harsh environment, such as with high temperatures, peak voltage fluctuations. It stabilizes the performance for high reliability that your system can count on.

Energy Related ErP/Eup 2013

Green Power! The total AC power consumption of the completed system is less than 5Vsb rail to support the new EU Regulation ErP 2013 for modern day systems.

Keep in Compliance IEC 62368

FSP Group provides a full kinds of additional safety approvals to keep designs ahead of the changing regulations. FSP has upgraded the majority of power supplies to the new IEC 62368 standard for your gaming rigs.

Intelligent Fan Speed Control

An advanced thermal control fan makes optimal cooling and reduces noise under maximum operation.

120mm fan and heat dissipation design to spin quietly and keep cooling under maximum operation.

All Black Round Cables

The all black coating round cables give your system a superior look rather so many entry-level power supplies.

Techninė specifikacija

Power	
Total power	650 W
AC input voltage	200 - 240 V
AC input frequency	50 - 60 Hz
Input current	5 A
Power factor	0.9
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	100 W
Combined power (+12V)	649.2 W
Combined power (+5V)	100 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	12.5 W

Max output current (+3.3V)	20 A
Max output current (+12V)	54.1 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	2.5 A
Hold time	17 ms
Efficiency	85%
Power protection features	Over current, Over power, Over voltage, Short circuit
Ports & interfaces	
Motherboard power connector	24-pin ATX
Peripheral (Molex) power connectors (4-pin)	2
Number of SATA power connectors	8
EPS power connector (8-pin)	Yes
EPS power connector (4+4 pin)	Yes
PCI Express power connectors (6+2 pin)	2
Floppy drive power connector	1
Floppy disk drive connector	Yes
Cabling type	Non-Modular
Performance	
80 PLUS certification	80 PLUS White
ATX version	2.52
EPS version	2.92
Design	
Product colour	Black
Cooling type	Active
Fan diameter	12 cm
Number of fans	1 fan(s)
Illumination	No
Certificates	
Certification	IEC 62368
Weight & dimensions	
Width	150 mm
Depth	140 mm
Height	86 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Weight	1.46 kg
Technical details	
Sustainability certificates	ErP
Sustainability compliance	Yes

Dokumentai ir vaizdo įrašai

› Vaizdo įrašas youtube.com/watch?v=qCrlou5Mjzo

Gamintojo ir saugos informacija

GAMINTOJAS

FSP Technology Inc.
Xinpu 6th St. No.101, 330 Taoyuan City, TW
fsplifestyle.com

ATSAKINGAS ASMUO ES

Fortron/Source (Europa) GmbH
Carl-Friedrich-Benz-Strasse 13, D-47877 Willich, DE
fsplifestyle.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt