GIGABYTE P550SS ICE power supply unit 550 W 20+4 pin ATX ATX White

Gamintojas: **GIGABYTE** · Modelis: **GP-P550SSICE** · Prekės kodas: **1012886**



76,90 €

Kaina su PVM

Be PVM: **63,55 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 80 PLUS Silver certified (230V EU)
- ✓ Support Intel ATX 3.0 standard
- ✓ 120mm Fluid Dynamic Bearing (FDB) Fan
- ✓ Flat cable design
- ✓ Powerful single +12V rail
- ✓ OVP/OPP/SCP/UVP/OCP/OTP protection








Aprašymas

80 PLUS

SILVER CERTIFIED

The 80 Plus Silver certification (230V EU) guarantees a 90% efficiency rate at a 50% load, resulting in reduced power wastage, diminished heat

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

generation, and minimized fan noise.

Support Intel
ATX 3.0 standard
The P550SS can sustain up to 2x total power excursion. It is fully compatible with Intel PSDG (Power Supply Design Guide) ATX 3.0 standard which supports up to 200% power excursion, reaches 70% low load efficiency and complies with required power supply timing standards.

120MM FLUID DYNAMIC
BEARING(FDB) FAN
High-performance Fluid Dynamic Bearing fan uses oil film shock absorption technology to effectively reduce noise, making it quieter than conventional sleeve fan and providing more than twice the lifespan. In addition, the fan will detect the current power usage and temperature, automatically adjust the fan speed to minimize the noise.

RELIABLE FLAT CABLE DESIGN

The utilization of flat cables minimizes clutter while enhancing the thermal performance of the chassis.

SINGLE +12V RAIL

The single +12V rail delivers optimal power output, stability, and hardware compatibility. This design not only simplifies power cable installation but also stands as the most effective choice for overclocking purposes.

PROTECTION

To guarantee the stable operation of your entire computer system under any circumstances, we have incorporated a range of protective features including OCP, OTP, OVP, OPP, UVP, and SCP. Moreover, we have obtained safety certifications from various countries to ensure the consistent and secure functioning of your system.

Techninė specifikacija

Power	
Total power	550 W
AC input frequency	50/60 Hz
Input current	6.3 A
Power factor	0.9
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	100 W
Combined power (+12V)	549.6 W
Combined power (+5V)	200 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	15 W
Max output current (+3.3V)	20 A
Max output current (+12V)	45.8 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A

Max output current (+5Vsb)	3 A
Hold time	16 ms
Efficiency	90%
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage

Ports & interfaces

Motherboard power connector	20+4 pin ATX
Peripheral (Molex) power connectors (4-pin)	3
Motherboard power cable length	60 cm
Number of SATA power connectors	5
SATA power cable length	500 mm
Peripheral (Molex) power cable length	500 mm
PCI Express power connectors (6+2 pin)	2
PCI Express power cable length	50 cm
CPU power connector (4+4 pin)	Yes
CPU power cable length	60 cm
ATX power connector (20+4 pin)	Yes
Floppy drive power connector	1
Floppy disk drive connector	Yes
PCI Express connector	Yes
Cabling type	Non-Modular

Performance

Purpose	PC
Power supply unit (PSU) form factor	ATX
80 PLUS certification	80 PLUS Bronze
ATX version	3
Bearing technology	HDB
Mean time between failures (MTBF)	100000 h

Design

Product colour	White
Cooling type	Active
Fan diameter	12 cm
Number of fans	1 fan(s)
Fan location	Top
On/off switch	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Weight & dimensions	
Width	150 mm
Depth	140 mm
Height	86 mm

Logistics data	
Harmonized System (HS) code	84733020

Gamintojo ir saugos informacija

GAMINTOJAS

GIGA-BYTE TECHNOLOGY CO., LTD.
Baoqiang Rd., Xindian Dist. No.6, 231 New Taipei City, TW
gigabyte.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.