TP-Link Omada TL-POE4818G PoE adapter Gigabit Ethernet 48 V

Gamintojas: **TP-LINK** · Modelis: **POE4818G** · EAN: **4895252501872** · Prekės kodas: **1013023**



38,90 €

Kaina su PVM

Be PVM: **32,15 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 48V passive PoE supported
- ✓ Auto-determine the necessary power requirements
- ✓ Convenient wall-mounting design
- ✓ Gigabit speed support
- ✓ Plug-and-Play, requires no configuration





Aprašymas

Passive PoE Adapter
Powers TP-Link products that support 48V passive PoE

Power Your Devices

Use the passive PoE adapter POE4818G to simultaneously supply power and transmit data to a passive PoE device.

Convenient Wall-Mounting Design

POE4818G offers a convenient wall-mounting brackets to be easily installed on a wall.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Compatible Devices

POE4818G is recommended to offer power supply to TP-Link’s passive PoE products which as follows.

Techninė specifikacija

Network	
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Cabling technology	10/100/1000
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Passive PoE
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6
Features	
Product colour	White
Wall mountable	Yes
Easy to install	Yes
Plug and Play	Yes
Maximum operating distance	100 m
LED indicators	Power, Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
RJ-45 input ports	1
RJ-45 output ports	1
Power	
Power over Ethernet (PoE) voltage	48 V
Output power	18 W
AC adapter input voltage	100-240 V
AC adapter frequency	50-60 Hz
Input voltage	100 - 240 V
Input frequency	50/60 Hz
Total Power over Ethernet (PoE) budget	18 W
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Operational conditions	
Operating temperature (T-T)	0 - 40 °C

Operating temperature (T-T)	32 - 104 °F
Operating relative humidity (H-H)	10 - 90%
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	85.8 mm
Depth	43.9 mm
Height	35 mm
Packaging content	
Number of products included	1 pc(s)
Power cord included	Yes
Packaging data	
Package type	Box

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH
Niederkasseler Lohweg 175, 40547 Düsseldorf, DE
tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt