MSI MAG A850GN PCIE5 maitinimo blokas 850 W 20+4 pin ATX ATX Juoda

Gamintojas: **MSI** · Modelis: **MAG A850GN PCIE5** · EAN: **4711377244275** · Prekės kodas: **1013653**



172,90 €

Kaina su PVM

Be PVM: **142,89 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 850 W 100 - 240 V 47 - 63 Hz
- ✓ Motininės plokštės maitinimo jungtis: 20+4 pin ATX
- ✓ PC ATX 80 PLUS Gold
- ✓ Aktyvus 12 cm
- ✓ Juoda







Aprašymas

The MAG series fights alongside gamers in pursuit of honor.
With added military-inspired elements in these gaming products, they were reborn as the symbol of sturdiness and durability.

80 PLUS GOLD CERTIFIED

The efficiency of your power supply directly influences your system’s performance and your power consumption. The 80 PLUS Gold certification promises lower energy consumption and higher efficiency.

ATX 3.1 Ready

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

It has an output port that is compliant with PCIe CEM 5.1 and Intel PSDG (Power Supply Design Guide)ATX 3.1, also this power supply can hold up to 2x total power excursion and 3x GPU power excursion.

Offer the CPU sufficient power

This power supply features dual 4+4-pin PCIe power connectors, providing ample 12V power to support high-performance CPUs.

POWER AT YOUR SIDE

The power supply is built with DC-to-DC construction, ensuring top-tier efficiency and unwavering voltage stability for your system.

SET FREE FOR THE +12V POWER OUTPUT

The latest CPUs and graphics cards demand more power, and a single +12V rail PSU provides an ideal combination of simplicity, robust power delivery.

FAN

The fan curve is designed to prioritize low noise output while maintaining effective cooling. When the power supply operates at 70% load, the resulting noise level is kept below 20 dBA.

Capacitors You Can Trust

The 105°C main capacitor is designed to perform reliably in handling high temperatures and peak voltage fluctuations. It ensures stable performance, providing your system with dependable reliability.

CERTIFIED CABLE

This power supply comes equipped with certified cables and connector made of copper alloy terminals. This provides greater safety than typical phosphor bronze connectors, especially during high current surges.

PROTECTION MECHANISMS

operate safely and stably at all times, this power supply comes with a number of protection mechanisms to give you the best peace of mind.

connectors

This power supply equipped with black, flat cables that are soft, and easy to bend, making cable management a breeze.

Techninė specifikacija

Power	
Total power	850 W
AC input voltage	100 - 240 V
AC input frequency	47 - 63 Hz
Power Factor Correction (PFC) type	Active
Number of +12V rail(s)	1
Combined power (+3.3V)	110 W

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Combined power (+12V)	846 W
Combined power (+5V)	110 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	15 W
Max output current (+3.3V)	20 A
Max output current (+12V)	70.5 A
Max output current (+5V)	20 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	3 A
Efficiency	90%
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit
Ports & interfaces	
Motherboard power connector	20+4 pin ATX
Peripheral (Molex) power connectors (4-pin)	2
Motherboard power cable length	60 cm
Number of SATA power connectors	4
EPS power connector (8-pin)	No
EPS power connector (4+4 pin)	Yes
PCI Express power connectors (6-pin)	0
PCI Express power connectors (6+2 pin)	2
PCI Express power connectors (8-pin)	0
PCI Express power connectors (16-pin)	1
PCI Express power connectors (12+4 pin)	0
PCI Express power connectors (12-pin)	0
CPU power connector (4+4 pin)	Yes
ATX Power connector (24-pin)	No
ATX power connector (20+4 pin)	No
Cabling type	Non-Modular
Performance	
Purpose	PC
Power supply unit (PSU) form factor	ATX
80 PLUS certification	80 PLUS Gold
Design	
Product colour	Black
Cooling type	Active

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Fan diameter	12 cm
Number of fans	1 fan(s)
Illumination	No
On/off switch	Yes
Weight & dimensions	
Width	150 mm
Depth	140 mm
Height	86 mm
Packaging data	
Package type	Box
Logistics data	
Harmonized System (HS) code	84733020
Matmenys ir svoris	
Matmenys (I × P × A)	29,00cm × 12,00cm × 20,00cm

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas
- Vaizdo įrašas objects.icecat.biz/objects/128401672_63292598.mp4

Gamintojo ir saugos informacija

GAMINTOJAS

Micro-Star Int'l Co.
Lide St., Zhonghe Dist. No. 69, 235 New Taipei City, TW
msi.com

ATSAKINGAS ASMUO ES

Mystar Computer B.V.
Science Park Eindhoven 5706, 5692 ER Son, NL
msi.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt