APC Easy Rack PDU, Basic, Horizontal, 1 Phase, 3.7kW, 230V, 16A, 8 x C13 outlets, IEC60320 C20 inlet

Gamintojas: **APC** · Modelis: **SEP6116G** · EAN: **731304804543** · Prekės kodas: **1015669**



134,90 €

Kaina su PVM

Be PVM: **111,49 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ World class power distribution at an accessible price point.
- ✓ The uncomplicated rPDU that simply provides power for the customer's solutions.
- ✓ Perfect offering for smaller organizations that are without dedicated IT staff.
- ✓ An eco friendly design ensures business contintuity and environmental friendliness.
- ✓ It offers a sustainability the reduces energy waste with a green premium.



Aprašymas

The SEP6 Extension for the Basic APC Easy rPDU provides the power for a rack full of devices while being easy to install and inexpensive. It's an integral piece of a plan to deliver a network infrastructure that is standardized and reliable. The SEP6 Extension for the Basic APC Easy rPDU slots perfectly into any data center and supports current solutions with ones to be deployed in the future. It’s nominal power runs between 2.3-22kW and can operate at a maximum temperature of 60C, which is the highest of any Easy rPDU. The SEP6116G is horizontal with 3.7kW, 230V and 16A with 8xC13 outlets. In addition to the operating high temperature the SEP6 Extension for the Basic APC Easy rPDU has 42 outlets, also more than any other Easy rPDU offering. It's a key part of any enivromental friendly policies and reduces energy waste with a Green Premium. The offerings of Single and Three Phase and the rPDU comes equipped with standardized one single platform with TUV certified safety and EMC report. Thanks to its budget friendly pricepoint, the rPDU is perfect when it comes to current and future AI technologies allowing for business growth and margin improvement. Customer satifaction is guaranteed as the rPDU comes with a standard two year warranty for any field replacement units.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Techninė specifikacija

Design	
PDU types	Basic
Rack capacity	1U
Type	Single-phase
Mounting	Horizontal
Product colour	Black
Ports & interfaces	
AC outlets quantity	8 AC outlet(s)
AC outlet types	C13 coupler
Power plug	C20 coupler
Power	
Nominal input voltage	200 - 240 V
Maximum current	16 A
AC input frequency	50/60 Hz
Output voltage	230 V
Maximum power	3700 W
Certificates	
Certification	CE
Operational conditions	
Operating temperature (T-T)	-5 - 60 °C
Storage temperature (T-T)	-25 - 60 °C
Operating relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	44.5 mm
Depth	482 mm
Height	44.5 mm
Weight	550 g
Packaging data	
Package weight	1.35 kg
Package width	170 mm
Package depth	570 mm
Package height	73 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Matmenys ir svoris	
Svoris	1,41kg

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.