Manhattan USB-C Dock/Hub, Ports (x4): HDMI, USB-A, USB-C and VGA, with Power Delivery (PD) 87W- requires external USB-C charger (not included). USB powered (no external power supply required) when PD is not in use, Aluminium

Gamintojas: **MANHATTAN** · Modelis: **130691** · EAN: **766623130691** · Prekės kodas: **1017631**



26,90 €

Kaina su PVM

Be PVM: **22,23 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Creates a dual-display setup, charges your devices and connects a peripheral
- ✓ Up to 4K@30Hz UHD (3840×2160) resolution on HDMI connection
- ✓ Up to 1080p@60Hz Full HD (1920×1080) resolution on VGA connection
- ✓ Dual-video output with resolutions up to 1080p@60Hz on both displays
- ✓ Supports display modes Mirror and Extended Mirror
- ✓ One USB 3.2 Gen 1 Type-A port (formerly USB 3.0) with SuperSpeed transfer rates up to 5 Gbps and charging up to 5 W (5 V / 1 A)
- ✓ USB-A port to connect mice, keyboards or portable memory devices (and more) or to charge and sync a portable electronic device
- ✓ Supports USB Power Delivery (PD) function up to 87 W; requires an external PD charger - available from Manhattan
- ✓ Compliant with DisplayPort 1.2 Alternate Mode (DP Alt Mode)
- ✓ Compatible with all USB-C DP-Alt-Mode-supported desktops, notebooks and tablets including Apple® MacBook®, Chromebook™, Pixel™ and more









Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.





Aprašymas

USB-C to HDMI and VGA Adapter to connect a laptop, MacBook® or PC to a dual-display setup - including USB-A peripheral and PD charging port The USB-C to HDMI & VGA 4-in-1 Docking Converter with Power Delivery establishes a fast, simple and convenient link between newer USB Type-C equipped media source (laptop, PC, MacBook®, Chromebook™, computer, tablet, etc.) and existing HDMI and VGA displays (monitors, TVs and projectors). You'll enjoy resolutions up to 4K@30Hz on the HDMI connection, up to 1080p@60Hz on the VGA connection, or up to 1080p@60Hz on each display of a dual-display setup. Create a mini-workstation by adding any USB 3.2 Gen 1 (formerly USB 3.0) peripheral such as a mouse, keyboard, hub, external memory device and more with the integrated USB-A port. This multiport Docking Converter is easy and quick to install. No complicated configuration or setup is required to enhance the functionality of your USB-C device. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly.

Up to 87 W charging power with USB-C Power Delivery (PD)

The included USB-C PD port lets you charge your notebook with power up to 87 W while simultaneously charging your other mobile devices, such as smartphones or tablets, through the USB-A port. The Power Delivery function also provides faster charging than standard chargers since it determines the power needs of compatible devices and supplies it at the quickest and safest rate.

Take your phone to the big screen

Connect any Android 9 and later smartphone that supports video output over USB-C DP Alt Mode to enjoy your apps and media even more. Watch a video on your monitor or flip through the slides of your presentation - all from your phone.

A Multiport Adapter that's made to go where you go

The very compact aluminum housing makes this USB-C to HDMI & VGA Docking Converter the perfect travel companion. With a footprint of only 62 x 40 x 15 mm (2.44 x 1.73 x 0.59 in.), it's small enough to fit in an outer notebook bag pocket, so you can create a mini-workstation for your laptop wherever you're going.

Techninė specifikacija

Ports & interfaces	
Connectivity technology	Wired
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
HDMI ports quantity	1
Microphone in	No
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
HDMI version	1.4
VGA (D-Sub) ports quantity	1
DisplayPort version	1.2

HDCP	Yes
HDCP version	1.4
Network	
Ethernet LAN	No
Performance	
Product colour	Grey
Card reader integrated	No
Data transfer rate	5 Gbit/s
Maximum digital resolution	3840 x 2160 pixels
Maximum refresh rate	60 Hz
Plug and Play	Yes
Housing material	Aluminium
Certification	CE FCC RoHS REACH UKCA
Power	
USB cable length	0.15 m
Software	
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8.1
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Other operating systems supported	Android, ChromeOS
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	40 mm
Depth	62 mm
Height	15 mm
Weight	42 g
Packaging data	
Quantity per pack	1 pc(s)
Package weight	63 g
Packaging content	
Manual	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Technical details	
Compliance certificates	CE, REACH, RoHS, UKCA, Federal Communications Commission (FCC)

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Manhattan

ATSAKINGAS ASMUO ES

IC Intracom Vertriebs GmbH
Löhbacher Str. 7, D-58553 Halver, DE
intellinetnetwork.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt