ATEN CL6700MW rack console 43.9 cm (17.3") 1920 x 1080 pixels Metal Black 1U

Gamintojas: **ATEN** · Modelis: **CL6700MW-ATA-2XK06FG** · EAN: **672792005930** · Prekės kodas: **1018054**



1 566,90 €

Kaina su PVM

Be PVM: **1 294,96 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Exclusive LED illumination light - designed by ATEN to illuminate the keyboard and touchpad to allow visibility in low-light conditions
- ✓ Integrated KVM console with a 17.3” LED-backlit widescreen Full HD LCD monitor in a single rail housing with top and bottom clearance for smooth operation with a 1U high system rack (CL6700MW)
- ✓ Supports an external console with USB / DVI / VGA / HDMI connectors
- ✓ Superior video quality – up to 1920 x 1080 @ 60Hz; DDC, DDC2, DDC2B





Aprašymas

The CL6700 features an integrated 17.3" (CL6700MW) or 19” (CL6700N) LED-backlit LCD panel, a full keyboard, and a touchpad in a 1U rack-mountable sliding housing with audio support. The CL6700 LCD KVM console provides front end access to compatible KVM switches utilizing space with a module that closes flat and slides into the rack.

The CL6700MW supports three types of video input – HDMI, DVI, and VGA – and provides the ultimate in installation flexibility by allowing users to connect the console and the computer via any of the three types of video source. For added convenience, the 17.3" full HD console features a port for an external USB mouse on the unit’s front panel, while ports for the second KVM console (USB keyboard, USB mouse and HDMI, DVI, or VGA monitor) are provided on the rear panel.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

While the CL6700MW supports multiple video interfaces, the CL6700N is a dedicated front end sliding console for compatible DVI KVM switches. The CL6700N supports DVI video input and provides ports for the second KVM console (USB keyboard, USB mouse and DVI or VGA monitor) on the rear panel. Both of the CL6700MW and CL6700N include two mini stereo ports for connecting audio speakers.

Users who already have a switch can take advantage of the space saving and efficiency benefits of the CL6700 LCD KVM console without the unnecessary expense of having to purchase a KVM switch. This model provides convenient ‘at the rack’ console access to KVM switches already installed at your site.

Note: Optional rack mount kits are available. For more information, refer to Compatible Accessories below.

Techninė specifikacija

Display	
Display diagonal	43.9 cm (17.3")
Display resolution	1920 x 1080 pixels
Display	LCD
Display brightness	250 cd/m²
Contrast ratio (typical)	800:1
Viewing angle, horizontal	170°
Viewing angle, vertical	170°
Pixel pitch	0.1989 x 0.1989 mm
Aspect ratio	16:9
Display type	TFT
Response time	16 ms
Supported resolutions	up to 1920 x 1200 @ 60 Hz (all resolution @ 60 Hz only); 1920 x 1080 @ 60 Hz, DDC2B
Technical details	
Rack capacity	1U
Material	Metal
Product colour	Black
Hot-Plug support	Yes
Operating relative humidity (H-H)	0 - 80%
Built-in KVM switch	Yes
Maximum resolution	1920 x 1200 pixels
Rack mounting	Yes
Console port	HDMI/VGA/DVI/USB/3.5mm
Number of computers controlled	1
On/off switch	Yes
LED indicators	Yes

Push button	Yes
Compliance certificates	RoHS
Ports & interfaces	
3.5 mm (1/8-inch) out	Yes
3.5 mm (1/8-inch) in	Yes
VGA (D-Sub) ports quantity	2
DVI connector type	DVI-D
DVI input ports	1
DVI output ports	1
Keyboard port type	USB
Mouse port type	USB
USB 2.0 Type-A ports quantity	3
USB 2.0 Type-B ports quantity	1
I/O ports	2x HDMI 1x RJ-11
Keyboard	
Keyboard number of keys	105
Built-in touchpad	Yes
Keyboard language	French
Keyboard layout	AZERTY
Hot keys	Yes
Power	
Power consumption (typical)	19.4 W
AC adapter input voltage	100 - 240 V
AC adapter frequency	50/60 Hz
Input current	1 A
AC (power) in	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Weight & dimensions	

Width	589.2 mm
Height	44 mm
Depth	480 mm
Weight	11.4 kg
Packaging content	
Cables included	AC, KVM
Quick installation guide	Yes
Manual	Yes
Rack mount kit	Yes

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Greitos pradžios vadovas
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.
Datung Road No.125, Sec. 2, 221 New Taipei City, TW
aten.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.