Dahua Technology Lite HAC-HDW1500TQ-IL-T Dome IP security camera Indoor & outdoor 2880 x 1620 pixels Ceiling/wall

Gamintojas: **DAHUA** · Modelis: **HAC-HDW1500TQ-IL-T-0280B-DIP** · Prekės kodas: **1018083**



60,90 €

Kaina su PVM

Be PVM: **50,33 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ The parameters and datasheets below can only be applied to1500-IL-T series
- ✓ Max. 25 fps@5MP
- ✓ Two-way Talk
- ✓ Smart Light+
- ✓ Smart Dual Light
- ✓ 40 m illumination distance
- ✓ 3DNR
- ✓ 3.6 mm fixed lens (2.8 mm optional)
- ✓ CVI/CVBS/AHD/TVI switchable
- ✓ IP67, 12 VDC



Aprašymas

The Lite Series is a great choice for consumers looking for high-quality monitoring products at a reasonable price. Its low cost and high performance make it ideal for residential areas and SMB solutions. This series is equipped with a wide range of technologies, such as full color and starlight, providing various solutions for different scenarios.

Two-way Talk

With its built-in high-sensitivity microphone and high-power speaker, the camera enables two-way communication through a mobile app.

Smart Dual Light

With its smart dual-light mechanism, the camera automatically turns on white light when the Perimeter Protection or SMD Plus function of an AI XVR detects a target in the rule area, capturing clear and vivid images. When the target leaves the area, the camera switches from white light to IR light to significantly reduce light pollution.

Smart Light+

Equipped with advanced LEDs and beam-processing technology, the camera effectively reduces interference from stray light, ensuring concentrated illumination within the lens’s field of view. This allows it to produce clear images that reveal fine details of targets even in low-light conditions.

Advanced 3DNR

Dahua’s advanced 3DNR technology reduces image noise with little to no impact on image sharpness, especially in poor lighting conditions. It detects noise and compares sequential frames to effectively reduce it while also saving bandwidth and storage space.

Protection

IP67: The camera passed rigorous dust and immersion tests. Its enclosure is dust-proof and waterproof and can function normally while immersed in water up to 1 m deep for 30 minutes.

4 Signals over 1 Coaxial Cable

HDCVI technology supports four signals (video, audio*, data, and power) transmitted simultaneously over a coaxial cable. Dual-way data transmission allows the HDCVI camera to interact with the XVR to perform actions such as sending control signals and triggering alarms. HDCVI also supports PoC, making installation quick and easy.
*Audio input is available for select HDCVI camera models.

Smart Area Lighting

Automatically adjusts brightness intensity and exposure for the left and right areas of the video based on the proportion and position of targets, revealing more details in the image.

Super Adapt

With its intelligent algorithm, the camera automatically adjusts its parameters to provide optimal performance and vivid images.

Techninė specifikacija

Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Alarm input/output	Yes

Remote viewing	Yes
Built-in light	Yes
Certification	CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035;

Design

Mounting type	Ceiling/wall
Product colour	White
Form factor	Dome
Housing material	Plastic, Metal
Protection features	Waterproof
International Protection (IP) code	IP67

Camera

Minimum illumination	0.01 lx
Angle of rotation	360°
Lens viewing angle, horizontal	113.3°
Lens viewing angle, vertical	62.1°
Lens viewing angle, diagonal	134.3°
Tilt angle range	0 - 75°
Pan range	0 - 360°
White balance	Auto, Area white balance
Camera shutter type	Electronic
Camera shutter speed	1/100000 s
Number of Privacy masking areas	8

Image sensor

Sensor type	CMOS
Number of sensors	1
Progressive scan	Yes

Lens system

Number of lenses	1
Detect distance	59.8 m
Observe distance	23.9 m
Recognize distance	12 m
Fixed focus	Yes
Focus	Motorized/Manual
Maximum aperture number	1.6

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Identify distance	6 m
Fixed focal length	2.8 mm
Night vision	
Night vision	Yes
Night vision distance	40 m
Number of illumination LEDs	4
Video	
Maximum resolution	2880 x 1620 pixels
Total megapixels	5 MP
Supported graphics resolutions	2880 x 1620, 2560 x 1440, 1920 x 1080 (HD 1080), 1280 x 720 (HD 720)
Frame rate	30 fps
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Digital Wide Dynamic Range (DWDR)	Yes
Smart IR	Yes
Audio	
Built-in speaker(s)	Yes
Audio system	2-way
Signal-to-Noise Ratio (SNR)	65 dB
Built-in microphone	Yes
Storage	
Built-in HDD	No
Security	
Video motion detection	Yes
Mirror	Yes
Power	
Power source type	DC
Power consumption (max)	9.5 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Weight & dimensions	
Height	109.9 mm
Diameter	10.6 cm
Weight	500 g
Packaging data	
Package weight	640 g
Packaging content	
Number of cameras	1
Manual	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	13,00cm × 13,00cm × 12,00cm
Svoris	0,45kg

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Zhejiang Dahua Technology Co., Ltd
Bin'an Road, Binjiang District No.1187 & 1199, 310053 Hangzhou, CN
dahuasecurity.com

ATSAKINGAS ASMUO ES

Dahua Technology GmbH
Niederkasseler Lohweg 185, 40547 Düsseldorf, DE
dahuasecurity.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt