TP-Link 10/100 Mbps WDM Media Converter

Gamintojas: **TP-LINK** · Modelis: **TL-FC111A-20** · EAN: **6935364010980** · Prekės kodas: **1019015**



56,89 €

Kaina su PVM

Be PVM: **47,02 €**

Sandėlyje


Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Complies with 802.3u 10/100Base-TX, 100Base-FX standards
- ✓ Auto-negotiation of Half-Duplex/Full-Duplex transfer mode
- ✓ Adopts WDM technology, transmitting and receiving data on one single fiber
- ✓ Extends fiber distance up to 20km











Aprašymas

What This Product Does

TL-FC111A-20 is a 100M media converter, providing a 100M RJ-45 port and a 100M SC fiber port, which can convert between electrical and optical signals. And long-distance data transmission through optical fiber can be applied to commercial scenarios such as park security monitoring and

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

wireless networking.

How This Product Works

TL-FC111A-20 adopts WDM (wavelength division multiplexing) technology, helping send and receive data at a distance of up to 20km (12.4 miles) over only one fiber, which saves half of the cable deployment cost for customers. TL-FC111A-20 transmits data at 1550nm wavelength and receives data at 1310nm wavelength on optical fiber. The TL-FC111A-20 works in the other end as a pair by receiving data at wavelength 1550nm and sending data at wavelength 1310nm.

Other Features

Besides, this media converter can be used as a standalone device (no rack required) or used with TP-Link’s TL-FC1420 rack for auto MDI/MDI-X in TX port in which duplex mode is automatically negotiated.

Techninė specifikacija

Network	
Maximum data transfer rate	100 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3i, IEEE 802.3u
Ethernet LAN data rates	10,100 Mbit/s
Copper ethernet cabling technology	10BASE-T, 100BASE-T
Fiber ethernet cabling technology	100BASE-FX
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Duplex system	Full, Half
Cable types supported	Cat3, Cat4, Cat5, Cat5e
Performance	
Maximum transfer distance	20000 m
Fiber mode structure	Single-mode
Fiber cable diameters supported (core/cladding)	9/125 µm
Features	
Internal	No
LED indicators	Activity, Link, Power
Product colour	Black
Ports & interfaces	
Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Fiber ports quantity	1
Power	
Output voltage	5 V
Output current	0.6 A
Weight & dimensions	
Width	94.5 mm
Depth	73 mm
Height	27 mm
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Packaging data	
Package width	165 mm
Package depth	204 mm
Package height	65 mm
Package weight	360 g
Certificates	
Compliance certificates	RoHS
Certification	FCC, CE
Logistics data	
Harmonized System (HS) code	85176990

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH
Niederkasseler Lohweg 175, 40547 Düsseldorf, DE
tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.