APC Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 16A, 230V, (21) C13 & (3) C19

Gamintojas: **APC** · Modelis: **AP8659EU3** · EAN: **731304299516** · Prekės kodas: **1021371**



1 976,90 €

Kaina su PVM

Be PVM: **1 633,80 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Metered, Metered-by-outlet, Switched 0U Black
- ✓ 24 AC outlet(s) C13 coupler, C19 coupler
- ✓ 3680 W





Aprašymas

APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets Power sequencing delays allow users to define the order in which to power up or down attached equipment Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding Current metering provides real-time remote monitoring of connected loads Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles User-defined alarms warn of potential circuit overloads before critical IT failures occur Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Techninė specifikacija

Design	
PDU types	Metered, Metered-by-outlet, Switched
Rack capacity	0U
Mounting	Vertical
Product colour	Black
Ports & interfaces	
AC outlets quantity	24 AC outlet(s)
AC outlet types	C13 coupler, C19 coupler
Power plug	IEC309
Features	
Cable length	3 m
Management features	
Monitoring	Current, Power, Voltage
Outlet control	Lock-out, Recycle, Turn off, Turn on
Power	
Nominal input voltage	200-230 V
AC input frequency	50 - 60 Hz
Nominal output voltage	230 V
Load capacity	3680 VA
Maximum input current per phase	16 A
Maximum total current draw per phase	16 A
Maximum power	3680 W
Certificates	
Compliance certificates	RoHS
Certification	EN 55022 A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC 15 A, ICES-003, PSE, UL, VCCI Class A, VDE
Operational conditions	
Operating temperature (T-T)	-5 - 45 °C
Storage temperature (T-T)	-25 - 65 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Weight & dimensions	
Width	56 mm
Depth	51 mm
Height	1829 mm
Weight	6.77 kg
Packaging data	
Package weight	9.05 kg
Package width	162 mm
Package depth	117 mm
Package height	2038 mm
Logistics data	
Total carbon footprint (kg of CO2e)	7441.92
Matmenys ir svoris	
Matmenys (I × P × A)	204,00cm × 17,00cm × 12,00cm
Svoris	8,74kg

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt