APC KVM1116R KVM switch Rack mounting Black

Gamintojas: **APC** · Modelis: **KVM1116R** · EAN: **731304340195** · Prekės kodas: **1021372**



1 729,90 €

Kaina su PVM

Be PVM: **1 429,67 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Manage multiple servers with just one keyboard, monitor and mouse



Aprašymas

The APC KVM 2G Digital/IP Switch supports one remote and one local user, with sixteen ports and virtual media. It is a 1U rack-mountable device. It supports various input voltages and frequencies, and includes a CD with software, installation guide and rack-mount brackets.

Occupies 1U of rack space

Conserve valuable rack space in the data center.

Hot Pluggable Operation

Add or remove servers without having to power off the switch.

Multi-platform Support

Windows, Sun, Unix and Linux compatible.

Scalable Architecture

Cascade multiple KVM switches for a modular solution that supports multiple platforms, improving flexibility and simplifying future expansion. Please see the user's manual for specific cascading capabilities.

Out-of-band management

Troubleshoot servers and diagnose problems in lieu of a working operating system with POST and BIOS-level access to servers.

Multi-platform Support

Windows, Sun, Unix and Linux compatible.

Scalable Architecture

Cascade multiple KVM switches for a modular solution that supports multiple platforms, improving flexibility and simplifying future expansion. Please see the user's manual for specific cascading capabilities.

Techninė specifikacija

Ports & interfaces	
Number of computers controlled	16
Keyboard port type	PS/2
Mouse port type	PS/2
Video port type	VGA
VGA (D-Sub) ports quantity	1
Network	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Design	
Rack mounting	Yes
Product colour	Black
Rack capacity	1U
Certification	C-tick, CE, EAC, FCC Part 15 Class A, ICES-003, TAA compliance, UL-AR, UL 60950-1, VCCI Class A, VDE
Display	
Built-in display	No
Power	
AC input frequency	50 - 60 Hz

Sustainability	
Compliance certificates	RoHS
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	424 mm
Depth	188 mm
Height	43 mm
Weight	2.59 kg
Packaging data	
Package width	619 mm
Package depth	330 mm
Package height	146 mm
Package weight	3.99 kg
Logistics data	
Harmonized System (HS) code	85176200
Matmenys ir svoris	
Matmenys (I × P × A)	62,00cm × 35,00cm × 16,00cm
Svoris	4,02kg

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.