APC Smart-UPS 750VA nepertraukiamo maitinimo resursai (UPS) „Line-Interactive“ 0,75 kVA 500 W 4 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **SMT750RMI2UNC** · EAN: **731304327721** · Prekės kodas: **1021767**



1 059,90 €

Kaina su PVM

Be PVM: **875,95 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ „Line-Interactive“
- ✓ 0,75 kVA 500 W
- ✓ Signalų forma: Sinusas
- ✓ 4 AC išvestis(ys / čių)
- ✓ Rūgštinis akumuliatorius (VRLA) 168 Ah
- ✓ Stelažas Juoda















Aprašymas

Stay always online and prevent data loss

As soon as the power fails, an APC Smart-UPS immediately supplies emergency power to all connected equipment. Because an APC UPS does this automatically, you prevent unwanted failure of, for example, a PC, server or switch. With the APC PowerChute Network Shutdown software, you can even have critical IT hardware shut down automatically and in a controlled manner when the UPS battery is almost empty. This prevents data loss, downtime and physical damage to hardware.

Safety

In addition, a Smart-UPS protects connected devices against peak voltage caused by lightning, among other things. This APC emergency power supply is ideally suited for (small) business use.

Battery life

You can easily read the expected battery life in the runtime graph, which you can find between the product images. This makes it easy to see how long the UPS will supply emergency power at a certain load.

Manage your Smart-UPS

Thanks to the pre-installed network card (ap9641), you can easily connect the APC UPS to the network. This allows you to monitor and manage the UPS remotely (SNMP) and the UPS can send a shutdown signal to multiple physical and/or virtual servers using PowerChute Network Shutdown software.

PowerChute Network Shutdown

PowerChute Network Shutdown is UPS management software that works with the UPS Network Management Card to protect Windows, Linux and Host ESXi, but also hyperconverged and virtual infrastructure*. In the event of a power failure, PowerChute can shut down your virtual machines correctly and the pre-configured boot sequence ensures that they are turned back on.

*For HCI and virtual machine support an additional license is required:
1 year: SWPCNS1Y-DIGI
3 years: SWPCNS3Y-DIGI
5 years: SWPCNS5Y-DIGI

Remote management and monitoring of your network

The network card can be managed remotely via the user-friendly web browser interface, remote management software EcoStruxure™ IT (SFTWES1-DIGI) or another SNMP-compatible system. Tip EcoStruxure™ IT also includes the functionalities of the support contract below.

Support contract

The optional network card support contract license* ensures that you are always up-to-date and secure and includes additional benefits such as frequent updates with:
• New and improved functions
• Security updates
• Advanced support
(The functionality of the support contract is included free of charge in the first year of the UPS)

*The above license and available in the variants:
1 year: SWNMC3SU-**1**Y-DIGI
Up to (Replace the bold number in the article number with the desired variant)
6 years: SWNMC3SU-**6**Y-DIGI

Ease of use

The basic functionalities can be set and read using physical buttons and an LCD screen. Thanks to the included 4-post rail kit, you can easily mount the UPS in a rack.

Extend the lifespan

The internal battery cartridge (APCRBC123) can be replaced easily, safely and independently by the user. This without having to switch off the APC SMT750RMI2UNC or connected equipment. This way you can easily and cheaply extend the lifespan of the APC Smart-UPS and your equipment always stays online.

Warranty extension

The factory warranty of the SMT750RMI2UNC is 3 years, with the exception of the battery cartridge, which has a factory warranty of 2 years. Both are extended by 3 years to 6 and 5 years respectively with the APC service pack (WBEXTWAR3YR-SP-02).

Switched Outlet Groups: Remote reboot and phased start-up

Thanks to the Switched Outlet Groups it is possible to configure a phased/delayed power-on per UPS outlet group. This reduces the peak load on the UPS and brings it closer to the constant load, which can limit oversizing of the UPS.

It is also possible to reset a group of multiple UPS outputs and the equipment connected to them. If SmartConnect Advanced (ERWPLUS1-1Y-DIGI), a UPS with SmartConnect port + Ecostruxure IT Expert (SFTWES1-DIGI) or a network card (ap9640) in combination with Ecostruxure IT Expert (SFTWES1-DIGI) are used, this can even be done remotely.

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. The 750VA line interactive 2U rackmount UPS provides pure sine wave power to support critical electronics during power disruptions. It comes with IEC 320 C14 input, 4x IEC 320 C13 outlets, and 2x IEC jumper cables. It has a preinstalled Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCI clusters. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. It provides surge protection against lightning strikes, power sags, brownouts and surges. The SMT UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty. It is compatible with a dedicated user-replaceable battery, and the APC replacement battery cartridge helps restore UPS performance to the original specifications.

Techninė specifikacija

Savybės	
UPS topologija	„Line-Interactive“
Išvesties galia (VA)	0,75 kVA
Išvesties galia	500 W
Signalų forma	Sinusas
Įvesties eksploatacinė įtampa (min.)	151 V
Įvesties eksploatacinė įtampa (maks.)	302 V
Įėjimo dažnis	50/60 Hz
Išvesties darbinė įtampa (min.)	220 V
Išvesties darbinė įtampa (maks.)	240 V
Išvesties dažnis	50/60 Hz
Išvesties dažnių reguliavimas	+/- 3 Hz

Išvesties įtampos reguliavimas	5%
Viršįtampio energijos įvertinimas	459 J
Reakcijos laikas	2 ms
Avarinis elektros išjungimas (EPO)	O
Garso lygis	46 dB
Apsauga nuo viršįtampių	Taip
Garsiniai perspėjimo signalai	Taip
Web pagrįstas valdymas	Taip
Garsinio pavojaus signalo režimai	Baterijos keitimas
Automatinis paleidimas iš naujo	Taip
Ryšys	
AC išėjimo tipai	C13 šakotuvas, C14 šakotuvas
Maitinimo laido kištukas	C14 šakotuvas
Lizų kiekis	4 AC išvestis(ys / čių)
USB 2.0 portų kiekis	1
Ethernet LAN (RJ-45) portų kiekis	1
„SmartSlot“	Taip
„SmartConnect“ prievadas	Ne
Baterija	
Baterijos technologija	Rūgštinis akumuliatorius (VRLA)
Baterijos talpa	168 Ah
Baterijos įkrovimo laikas	3 h
Hot-Swap baterija	Taip
Automatinis baterijos bandymas	Taip
Aušinimo paleidimas	Taip
Konstrukcija	
Forma	Stelažas
Produkto spalva	Juoda
Rėmo pajėgumas	2U
Ekrano tipas	LCD
LED indikatoriai	Taip
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-15 - 45 °C

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Darbo santykinės drėgmės diapazonas	0 - 95%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%
Darbinis aukštis	0 - 3000 m
Ne darbinis aukštis	0 - 15000 m
Sertifikatai	
Atitikties sertifikatai	RoHS
Sertifikavimas	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Pakuotės turinys	
Stovo montavimo rinkinys	Taip
Pridėti kabeliai	Įvesties maitinimo laidas, USB laidas
Pridedama valdymo kortelė	Taip
Greito diegimo vadovas	Taip
Tvarumas	
Tvarumo sertifikatai	Green Premium
Svoris ir matmenys	
Plotis	432 mm
Ilgis	406 mm
Aukštis	89 mm
Svoris	17,2 kg
Pakuotės duomenys	
Šaltinis CD	Taip
Pakuotės plotis	546 mm
Pakuotės gylis	584 mm
Pakuotės aukštis	241 mm
Paketo svoris	21,2 kg
Logistikos duomenys	
Gaminių skaičius ant padėklo	16 vnt
Darniosios sistemos (DS) kodas	85078000
Bendrasis anglies pėdsakas (kg of CO2e)	497,38
Kitos savybės	
Išėjimo įtampa	230 V
Matmenys ir svoris	
Matmenys (I × P × A)	58,00cm × 54,00cm × 25,00cm
Svoris	21,18kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.