

iiyama ProLite TF2738MSC-B2 kompiuterio monitorius 68,6 cm (27") 1920 x 1080 pikseliai „Full HD“ LED Lietimui jautrus ekranas Daugybė naudotojų Juoda

Gamintojas: **IIYAMA CONSIGNMENT** · Modelis: **TF2738MSC-B2** · EAN: **4948570118199** · Prekės kodas: **102333**



693,90 €

Kaina su PVM

Be PVM: **573,47 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 68,6 cm (27") Juoda
- ✓ Įmontuoti garsiakalbiai
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekranas: Plokščias
- ✓ Reakcijos laikas: 5 ms Atsako trukmės matavimo tipas: GTG (Gray to Gray)
- ✓ 1920 x 1080 pikseliai „Full HD“ Skydo tipas: IPS
- ✓ Energijos vartojimo efektyvumo klasė (SDR): E ErP CE, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE





Aprašymas

With 1920x1080 Full HD resolution and Projective Capacitive 10 point touch technology, the ProLite TF2738MSC-B2 delivers seamless and accurate touch response. Featuring IPS LED LCD Screen technology, it offers exceptional colour performance and wide viewing angles. Its rugged bezel with edge-to-edge glass makes it very suitable for applications like table top integration. In addition, the screen comes with an IPX1 rating, making it water resistant from the front. Equipped with speakers and triple digital input (DVI, HDMI and DisplayPort). The ProLite TF2738MSC-B2 is an ideal screen for kiosk integrators and a perfect solution for Interactive Digital Signage, Instore Retail, Gaming and Interactive Presentations.

Techninė specifikacija


Display	
Display diagonal	68.6 cm (27")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	IPS
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Display number of colours	16.7 million colours
Touchscreen type	Multi-user
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	500 cd/m²
Display brightness	425 cd/m²
Response time measurement type	GTG (Gray to Gray)
Contrast ratio (dynamic)	12000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.311 x 0.311 mm

Horizontal scan range	30 - 80 kHz
Viewable size, horizontal	59.8 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.6 cm
Surface hardness	6H
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Low Blue Light technology	Yes
Operating hours (hours/days)	16/7
Multimedia	
Built-in speaker(s)	Yes
Number of speakers	2
RMS rated power	6 W
Design	
Product colour	Black
Front bezel colour	Black
Glass thickness	3.6 mm
Ports & interfaces	
HDMI	Yes
USB Touch port	Yes
DVI port	Yes
HDMI ports quantity	1
DisplayPorts quantity	1
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100,200 x 100 mm
Wall mountable	Yes
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, German, English, French, Japanese, Dutch, Polish, Russian
Number of OSD languages	8
Power	
Energy efficiency class (SDR)	F

Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	24 kWh
Power consumption (typical)	25 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	648.5 mm
Depth (with stand)	52 mm
Height (with stand)	386.5 mm
Weight (with stand)	8.3 kg
Width (without stand)	648.5 mm
Depth (without stand)	52 mm
Height (without stand)	386.5 mm
Weight (without stand)	8.3 kg
Bezel width (side)	2.45 cm
Bezel width (top)	2.4 cm
Bezel width (bottom)	2.4 cm
Packaging data	
Package width	746 mm
Package depth	123 mm
Package height	500 mm
Package weight	9.4 kg
Packaging content	
Cables included	AC, USB, HDMI, DisplayPort
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP
Other features	
International Protection (IP) code	IP1X

Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Display viewable area (HxV)	597.6 x 336.2 mm
Placement supported	Horizontal/Vertical
Brightness	425 cd/m²
Active display area (W x H)	597.6 x 336.2 mm
Bezel width	2.4 cm
Weight	8.3 kg
Height	386.5 mm
Width	648.5 mm
Depth	52 mm
Compliance certificates	CE, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE
Certification	CE, TÜV-Bauart, EAC, RoHS, ErP, WEEE, REACH, UKCA
User controls	picture adjust (contrast, brightness, adv. contrast, ECO mode, OD) input select, audio adjust (volume, mute, audio input) colour adjust (cool, normal, warm, user colour, i-Style colour), information, manual image adjust (sharpness, video mode adjust, blue light reducer, X-res technology), setup menu (language select, OSD position, OSD time out, OSD background, opening logo, LED) memory recall
Touch method	stylus, finger, glove
Control panel	Menu, Scroll up/ Audio, Scroll down/ i-Style colour, Select/ Input select, Power
Logistics data	
Products per pallet	36 pc(s)
Pallet net width	74.7 cm
Pallet net length	2 m
Pallet net height	110.7 cm
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Matmenys (I × P × A)	75,00cm × 49,00cm × 13,00cm
Svoris	10,34kg

Energijos efektyvumas ir ekologinis projektavimas



21 kWh/1000h



2019/10/13

Energijos efektyvumo klasė

F A-G

- > [Energijos etiketė](#)
- > [Gaminio informacijos lapas](#)
- > [EPREL duomenų bazė](#)

Dokumentai ir vaizdo įrašai

- > [Vaizdo įrašas](#) youtube.com/watch?v=AuPCFL8oUyU

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeesterstraat 8, 2131 HA Hoofddorp, NL

iiyama.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt