ATEN 2-Port USB 3.0 8K DisplayPort KVMP™ Switch (Cables included)

Gamintojas: **ATEN** · Modelis: **CS1922A-AT-G** · EAN: **4711581520721** · Prekės kodas: **1023334**



253,89 €

Kaina su PVM

Be PVM: **209,83 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt


Pagrindinės savybės

- ✓ Up to 7680 × 4320 @ 60 Hz, 5120 × 2880 @ 60 Hz and 4096 × 2160 @ 120 Hz
- ✓ Supports daisy-chaining for dual-display setups by connecting two CS1922A units, enabling dual-screen control through a single connection
- ✓ All DisplayPort/USB cables and power adapter included for hassle-free installation
- ✓ Computer selection via pushbuttons, remote port selector, hotkeys, mouse, and RS-232 commands









Aprašymas

Control two computers with a single USB keyboard and mouse while sharing USB peripherals and enjoying ultra-high-resolution video.

Built on ATEN’s enterprise-grade design heritage, the CS1922A belongs to ATEN’s first KVM switch series with 8K support, delivering professional-grade performance and reliable multi-computer control from a single console.

Ultra-High Resolution for Versatile Professional Applications

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

The CS1922A delivers up to 8K@60 Hz and 4K@120 Hz, providing precise, clear visuals for demanding tasks. It enables users to control multiple computers from a single console, supporting efficient multitasking and high-resolution workflows while keeping the workspace clean and organized.

Multi-Display Expansion and Broad Display Compatibility

Daisy-chaining further allows multi-display setups using a single keyboard and mouse, streamlining multi-screen workflows and enhancing productivity for complex tasks. With DisplayPort Dual-Mode (DP++) support, the switch can connect to HDMI or DVI displays via compatible adapters, expanding compatibility with a wide range of monitors.

Flexible and Intuitive Switching for Efficient Workflows

Multiple switching methods, including front panel pushbuttons, a remote port selector, hotkeys, mouse switching, and RS-232 commands, allow users to control connected computers seamlessly. This flexibility enables fast, efficient workflow management tailored to individual preferences, ensuring smooth transitions between multiple systems.

Efficient Peripheral Sharing and Easy Installation

The integrated USB 3.1 Gen 1 hub provides 5 Gbps data transfer speeds, enabling fast sharing of peripherals between connected computers. All required DisplayPort and USB cables, along with a power adapter, are included for quick, plug-and-play setup, helping users maintain a clean, organized, and fully functional workspace from the start.

Techninė specifikacija

Ports & interfaces	
Number of computers controlled	2
Keyboard port type	USB
Mouse port type	USB
Video port type	DisplayPort
Console ports	USB A, DisplayPort, 3.5mm headphone
DisplayPorts quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	2
Console USB ports quantity	2
Console DisplayPorts ports quantity	1
Console RJ-45 ports quantity	1
USB hub	Yes
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	2
USB connector type	USB Type-A, USB Type-B
Headphone outputs	4
Number of microphone inputs	4
DC-in jack	Yes
Performance	
HD type	8K Ultra HD

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Maximum resolution	7680 x 4320 pixels
Video bandwidth	60 Hz
Scan interval	1,99 s
Maximum refresh rate	240 Hz
Design	
Rack mounting	No
Product colour	Black
LED indicators	Yes
Push button	Yes
Display	
Built-in display	No
Power	
Power source	DC
Input voltage	12 V
Power consumption (typical)	2.26 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	73 mm
Depth	200 mm
Height	43 mm
Weight	470 g
Packaging content	
Quick installation guide	Yes
Logistics data	
Harmonized System (HS) code	84718000
Country of origin	Taiwan

Dokumentai ir vaizdo įrašai

- Greitos pradžios vadovas
- Gaminio lankstinukas

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.

Datung Road No.125, Sec. 2, 221 New Taipei City, TW

aten.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt