D-Link 52-Port Gigabit Stackable POE Smart Managed Switch including 4 x 10G SFP+

Gamintojas: **D-LINK** · Modelis: **DGS-1510-52XMP** · EAN: **790069434303** · Prekės kodas: **1028472**



1 896,90 €

Kaina su PVM

Be PVM: **1 567,69 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L3 Web-based management
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 48
- ✓ Cat5, Cat5e 10G support
- ✓ MAC address table: 16000 entries Switching capacity: 128 Gbit/s
- ✓ Rack mounting Stackable
- ✓ Power supply included Power over Ethernet (PoE)







Aprašymas

The D-Link DGS-1510 Series is the latest generation of Smart Managed switches with 10G capability, available with 16, 24, or 48 10/100/1000 Mbps ports plus additional fibre ports for physical stacking or uplinks. The PoE-capable DGS-1510-28P, DGS-1510-28XMP and DGS-1510-52XMP switches provide additional flexibility for businesses looking to power IP phones, wireless access points, or IP cameras using existing network infrastructure. The combination of high bandwidth connections and PoE support make the DGS-1510 Series ideal for Small-Medium Enterprise (SME) and Small-Medium Business (SMB) environments.

10G SFP+ Stacking/Uplink Ports

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

The last two SFP+ ports of the DGS-1510 Series switches allow users to create a physical stack of up to 6 units in a fault-tolerant ring or linear topology using Direct Attach Cables (DACs) or any compatible SFP+ transceiver1. This creates a total of 288 Gigabit ports, ensuring high bandwidth while staying cost-efficient. Meanwhile, the remaining uplink ports can be used for other functions, such as connecting to a larger network. Users can also easily configure and manage any of the DGS-1510 Series Smart Managed switches in a single stack. With 20 Gbps full-duplex capabilities, the DGS-1510 Series offers 10G connectivity to core networks and servers while still maintaining fast data transfer rates.

Layer 3 Traffic Management

The DGS-1510 Series provides static routing, allowing you to segment your network into workgroups that communicate between VLANs and increase application performance. With these capabilities, you can reduce the load on your core devices, allowing you to create a scalable and efficient network.

Extensive Layer 2 Features

The DGS-1510 Series switches are equipped with a complete line-up of Layer 2 features, including IGMP Snooping, Port Mirroring, Spanning Tree, and Link Layer Discovery Protocol (LLDP). The IEEE 802.3x Flow Control function allows servers to directly connect to the switch for fast, reliable data transfer. Network maintenance features include Loopback Detection and Cable Diagnostics. Loopback Detection automatically detects and shuts down loops created by a specific port or VLAN. The Cable Diagnostics feature, designed primarily for administrators and customer service representatives, can determine cable quality and can quickly discover sections of cabling that need to be replaced.

Traffic Classification & QoS

The DGS-1510 Series supports Auto Surveillance VLAN (ASV) and Auto Voice VLAN, which are best suited for VoIP and video surveillance deployments. Auto Surveillance VLAN is a new, industry-leading technology built into D-Link Smart switches. This technology consolidates data and surveillance video transmissions through a single DGS-1510 Series Smart Managed switch, saving businesses the costs of maintaining expensive dedicated hardware and infrastructure. ASV also ensures the quality of real-time video for monitoring and control without compromising the transmission of conventional network data by giving ASV traffic priority over other packets.

Keep Your Network Secure

D-Link’s innovative Safeguard Engine protects the DGS-1510 Series against traffic flooding caused by malicious attacks. The DGS-1510 Series supports both MAC and web-based access control. This gives network administrators multiple authentication options, reducing deployment times and removing the need for client software. The DGS-1510 Series supports IEEE 802.1X port-based authentication, allowing network users to be authenticated through external RADIUS servers. The Address Resolution Protocol (ARP) Spoofing Prevention feature helps to prevent attacks that may allow an intruder to intercept users’ traffic while the DHCP Server Screening feature screens rogue DHCP server packets from user ports to prevent unauthorised IP assignment.

IPv6 Ready

The DGS-1510 Series is IPv6 ready and supports various IPv6 functions such as MLD Snooping, IPv6 security features, and IPv6 Quality of Service (QoS), ensuring seamless integration with next generation networks. The DGS-1510 Series also supports IPv4/v6 dual stack functionality, which allows the switches to act as a bridge between IPv4 and IPv6 networks.

1 When stacking in a linear typology, the remaining unused SFP+ ports in the stacking port pair of the top and bottom switches will also be considered occupied by the switch and cannot be used for any other purpose.

Techninė specifikacija

Management features	
Switch type	Managed
Switch layer	L3

Quality of Service (QoS) support	Yes
Web-based management	Yes
Traffic classification	Yes
ARP inspection	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	48
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	4
Network	
Networking standards	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x
10G support	Yes
Cable types supported	Cat5, Cat5e
Full duplex	Yes
Auto MDI/MDI-X	Yes
Data transmission	
MAC address table	16000 entries
Switching capacity	128 Gbit/s
Throughput	95.24 Mpps
Number of IP interfaces	16
Jumbo frames support	Yes
Jumbo frames	9216
Multicast features	
Multicast support	Yes
Multicast MAC address table	512 entries
Design	
Rack mounting	Yes
Stackable	Yes
Product colour	Black
Reset button	Yes
LED indicators	Activity, Link, PoE, Speed
Number of fans	3 fan(s)
Performance	
Noise level	56.9 dB
Power	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	486.9 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	-5 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Heat dissipation	138.787 BTU/h
Weight & dimensions	
Width	440 mm
Depth	308 mm
Height	44 mm
Weight	5.41 kg
Packaging data	
Package width	475 mm
Package depth	520 mm
Package height	110 mm
Package weight	7.26 kg
Technical details	
Shipping (inner) case height	50.7 cm
Shipping (inner) case width	27.3 cm
Shipping (inner) case length	55.5 cm
Shipping (inner) case net weight	14.5 kg
Products per shipping (inner) case	2 pc(s)
Pallet gross weight (air)	400.7 kg
Master (outer) cases per pallet (air)	24 pc(s)
Products per pallet (air)	48 pc(s)
Pallet gross length	110 cm
Pallet gross width	120 cm
Pallet height (air)	166 cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Pallet gross weight (sea)	400.7 kg
Master (outer) cases per pallet (sea)	24 pc(s)
Products per pallet (sea)	48 pc(s)
Pallet height (sea)	166 cm
Shipping (inner) case gross weight	16.1 kg
Certificates	
Certification	CE FCC C-Tick VCCI BSMI cUL CB
Logistics data	
Harmonized System (HS) code	85176990

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux
Postbus 48, 5480 AA Schijndel, NL
dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.