APC AR3350B2 lentyna 42U Atskiras stovas Juoda

Gamintojas: **APC** · Modelis: **AR3350B2** · EAN: **731304642213** · Prekės kodas: **1029895**



4 014,90 €

Kaina su PVM

Be PVM: **3 318,10 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Ideal for AI, high density server and networking applications
- ✓ 2nd Gen model with higher load capacity and better airflow
- ✓ Lower CO2 emissions with 3.3% decarbonization rate
- ✓ Ample space, organization, security and convenience features














Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Aprašymas

Product Description

APC NetShelter SX enclosures are built with the power, space and organizational features needed for versatile and demanding IT environments. This 19-inch rack is optimized for high-density servers and networking applications. At 42U high, the enclosure fits easily through doorways and can support a static load of 4000 lbs.

Integrated with APC Products

APC cooling, power distribution and cable management products seamlessly integrate into the enclosures to create a complete IT infrastructure support system.

Optimized for High Capacity Cable Management Systems

NetShelter SX enclosures are specifically designed for use with high-capacity cable management systems that are mounted on mounting rails and are designed to fit the u-spaces for mounting equipment. The enclosures feature channels for routing and managing cables.

Cable access openings with pre-installed brushes

Large cable slots in the roof allow for overhead cable access. The bottom is specially designed for trouble-free cable passage via a raised floor. The roof is equipped with openings with brush strips pre-installed at locations that run diagonally towards the front of the cabinet for the passage of data cables and air management facilities.

Perforated front door with curved profile

The perforated front and rear doors (80%) ensure adequate ventilation of servers and network equipment. The perforated area of the front door has been improved with a curved profile for a larger surface area, greater perforation coverage and a higher perforation percentage (80%). The front and rear doors open 270° (180° tracked) and thus keep aisles clear. The front doors are also equipped with three-point locking.

Quick Release Doors

The door can be placed on the opposite side or interchanged with the rear doors. Doors are easy to remove with a simple "lift-off" design.

Half-Height Side Panels and Optional Pass-Through Brush Strips

The half-height, easy-to-remove side panels are more compact and lighter, and provide quicker access to equipment. The side panels can be locked with a single key for the doors. Side panels with openings and brush strips are now available to route cables to adjacent racks in a row, while maintaining adequate airflow.

Easy-Removal Roof for Cable Access

The roof can be easily removed via pin hinges for access during equipment installation and even after cables have been routed and routed through the cable openings. The roof can be reversed after removal to adjust the larger cable openings for power distribution plugs and connections.

Eyebolt support integrated into the cabinet frame

The integrated eyebolt openings on the cabinet frame allow the cabinet to be lifted and moved using lifting equipment. See the cabinet owner's manual for more information on eyebolts and maximum cabinet weight.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Cabinet adjustment tools and hardware included

All cabinets come standard with a bag of hardware for mounting IT equipment and tools for basic adjustments inside the cabinet.

Integrated electrical grounding

The roof and side panels and the front and rear doors are grounded to the enclosure frame. Eight additional electrical grounding connections for external grounding are located on the external frame.

Includes: Baying hardware, Doors, Keys, Keyed alike doors and side panels, Leveling feet, Mounting hardware, Pre-installed casters, Roof, Side panels, Unpacking instructions

Introducing the redesigned APC NetShelter SX rack enclosure - trusted, versatile, and built for demanding IT environments. With larger load capacities and more space for equipment, it enables higher-density computing. Choose from standard, wide, extra wide, and large-depth options. The modern look is perfect for colocation and customer-facing businesses. Simplify workflows with easy access to cabling and equipment, and optimize airflow and cable management with our wide range of APC accessories. The 270° (180° bayed) opening doors keep aisles clear, while 80% door perforation improves airflow for high-powered servers. Built sustainably with all-steel construction, it lasts for years and can be used for various applications. It also boasts a 3.3% decarbonization rate and ships in sturdy, recyclable packaging.

Techninė specifikacija

Savybės	
Rėmo pajėgumas	42U
Tipas	Atskiras stovas
Produkto spalva	Juoda
Šoninės panelės įskaitytos	Taip
Klavišų užrakinimas	Taip
Šoninės dėžės spyna	Taip
Reguliuojamas padas	Taip
Durų atidarymo kampas	270°
Svoris ir matmenys	
Dydis	48,3 cm (19")
Plotis	750 mm
Ilgis	1200 mm
Aukštis	1991 mm
Svoris	157,5 kg
Montavimo gylis (min.)	28,6 cm
Montavimo gylis (maks.)	104,8 cm
Pakuotės duomenys	
Pakuotės plotis	853 mm
Pakuotės gylis	1323 mm
Pakuotės aukštis	2128 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Paketo svoris	183,2 kg
Techninė informacija	
Sudėtyje nėra	SVHC
Atitikties sertifikatai	REACH, RoHS
Garantinis laikotarpis	5 metai
Logistikos duomenys	
Kilmės šalis	Kinija

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.