Zyxel GS1200-5HP v2 Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey

Gamintojas: **ZYXEL** · Modelis: **GS1200-5HPV2-EU0101F** · EAN: **4718937598717** · Prekės kodas: **1030090**



64,90 €

Kaina su PVM

Be PVM: **53,64 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed Web-based management
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 5
- ✓ MAC address table: 2000 entries Switching capacity: 10 Gbit/s
- ✓ Power over Ethernet (PoE)





Aprašymas

Web-managed PoE+ switches are now within reach for SMBs seeking more network control

The GS1200 series of PoE+ switches features true web management, QoS and support for 802.3af and 802.3at PoE+ plus a user-friendly set-up interface. With essential power and value features built-in, it’s the right choice for small or remote offices deploying IP cameras, VoIP phone systems or wireless access points.

Smart PoE+ 802.3af/802.3at support

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

The GS1200 series supports the IEEE 802.3at standard, providing a maximum of 30 watts per port (with a max total power budget of 60 watts) to supply power to PoE network devices like wireless APs, IP cameras and VoIP phones. Web GUI management enables you to monitor the power status on each port and/or reboot the network devices, as needed.

IGMP Snooping for optimized traffic delivery

Based on the IGMP (Internet Group Management Protocol) query and report messages, the switch forwards traffic only to the ports that request the multicast traffic rather than to all ports. It helps to optimize multicast performance and is especially useful for bandwidth-intensive IP multicast applications such as online media streaming and gaming.

VLAN segregation for enhanced network security

VLAN (virtual local area network) can be used to separate traffic within a business such as isolating resources between network administrators and general users or between employees and public guest users.

Enhanced port-based QoS for better traffic control

QoS (Quality of service) is the ability to provide different priority to different applications, users, or video/voice/data flows, or to guarantee a certain level of performance to a data flow.

Link Aggregation increase throughput

GS1200-5HP v2/GS1200-8HP v2 combines 2 physical ports together to make a single high-bandwidth data path, for faster file transfers and to enhance connection reliability.

Easy web management

This switch comes with a user-friendly web-based set-up interface that walks you through setup, configuration and management—including configuration backups and firmware upgrades—quickly and easily. With a few simple clicks, your network will be humming along, so you can get back to business.

Advanced Energy-Savings at Work

This switch’s built-in IEEE 802.3az Energy Efficient Ethernet (EEE) function automatically detects network traffic and adjusts power consumption dynamically to reduce power usage during times of low traffic.

Fanless, noiseless design

Extend your network control and visibility without disrupting your quiet business environment. This business switch features a fanless design that ensures noiseless operation and greater reliability over time with fewer parts to fail.

More comprehensive smart features included

Featuring Gigabit performance that’s 10 times faster than Fast Ethernet. Deliver up to 2,000 Mbps of dedicated, non-blocking bandwidth per port and more advanced features like port mirroring, Jumbo Frame, broadcast storm control, loop detection/prevention. It’s a great choice for SMBs who want to enjoy high-speed business network applications!

Techninė specifikacija

Management features	
Switch type	Managed

Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Network	
Networking standards	IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Port mirroring	Yes
Full duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes
VLAN support	Yes
Virtual LAN features	Port-based VLAN
Data transmission	
MAC address table	2000 entries
Switching capacity	10 Gbit/s
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	0.1 MB
Security	
DHCP features	DHCP client
IGMP snooping	Yes
Multicast features	
Multicast support	Yes
Number of multicast groups filtered	20
Design	
Rack mounting	No
Stackable	No
Product colour	Grey
Reset button	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

LED indicators	Link, PoE, Power
On/off switch	Yes
Safety	LVD EN60950-1
Performance	
Firmware upgradeable	Yes
Power	
Output current	1.3 A
Power consumption (max)	72 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	5
Power over Ethernet plus (PoE+) ports quantity	4
Total Power over Ethernet (PoE) budget	60 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	193 mm
Depth	84 mm
Height	26 mm
Weight	392 g
Packaging data	
Package type	Box
Package width	210 mm
Package depth	132 mm
Package height	78 mm
Package weight	950 g
Certificates	
Certification	CE, FCC, C-Tick, Class A
Logistics data	
Harmonized System (HS) code	85176990

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

GAMINTOJAS

Zyxel Networks Corporation
Industry East RD. IX, Hsinchu Science Park 2,
30076 Hsinchu, TW
zyxel.com

ATSAKINGAS ASMUO ES

Zyxel Networks A/S
Adenauerstraße 20/A3, 52146 Würselen, DE
zyxel.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt