TP-Link VIGI 32 Channel Network Video Recorder

Gamintojas: **TP-LINK** · Modelis: **VIGI NVR4032H** · EAN: **4895252500752** · Prekės kodas: **1031583**



722,90 €

Kaina su PVM

Be PVM: **597,44 €**

Sandėlyje


Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt


Pagrindinės savybės

- ✓ 16-ch@2MP/ 8-ch@4MP Decoding Capacity†: Allows you to enjoy more channels, live view, and playback at the same time
- ✓ 1 HDMI and 1 VGA Interface: Supports independent video output
- ✓ H.265+: Without using any extra bandwidth, your camera transmits compressed crystal-clear video to save disk space, ease network loads, and reduce monitoring costs without sacrificing image quality
- ✓ 320 Mbps Incoming and Outgoing Bandwidth: Ensures your NVR manages more cameras with high resolutions
- ✓ Mass Storage: Supports 4× SATA, up to 10 TB each
- ✓ 16-Channel Simultaneous Playback: Replay the feed from up to 16 cameras at the same time, increase replay speed, and find events in the video schedule to easily review footage
- ✓ Dual Ethernet Ports Design: Supports three network modes, including muti-address mode, network fault-tolerance and load balance
- ✓ Plug & Play: Allows new and unused VIGI IP Cameras to be added automatically to the new NVR and activated instantly, making installation faster than ever before
- ✓ Remote Monitoring: The dedicated VIGI app, web UI, and VIGI Security Manager enable remote monitoring, providing ease and convenience
- ✓ Rack Mounting: Space-saving and easy installation









Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903



Aprašymas

Security Never Shuts Down
32 Channel Network Video Recorder

Every angle all on one screen.
4K HDMI Video Output & 32MP Decoding Capacity
Sharp image definition up to 8MP ensures you capture every detail. 16-ch@2MP/ 8-ch@4MP decoding capacity allows you to enjoy more-channels live view and playback at the same time

Independent Video Output

Greatly reduces the time spent on switching between screens.

Connect the HDMI and VGA ports to the two different screens and freely choose what live views each screen shows. That way, you will enjoy multi-channels live views simultaneously.

The VGA and HDMI ports display live views and configuration & playback interface, respectively. It will allow users to play back the videos or configure the devices while watching live views at the same time.

Rich Ports for Diversified Functions.
Equipped with a variety of ports, VIGI NVR4032H integrates 16× alarm in, 4× alarm out, two-way audio, video input, independent video output, and more, suitable for SMB surveillance scenarios.

Dual Ethernet Ports Design

Supports a variety of network modes to meet your different needs.

Higher bandwidth for high-definition cameras.
320 Mbps Video Access Bandwidth
High video access bandwidth ensures your NVR manages more cameras with high resolutions.Based on laboratory testing using VIGI cameras, VIGI NVR can manage up to 32 HD cameras.

Smart Video Coding by H.265+

Compresses the video size without sacrificing video quality, easing the network load and saving disk space.

Security for every hour and every day.
4 SATA (1 up to 10TB)
Automatically and continuously stores up to 40 TB of footage from connected cameras to secure your data for quick, convenient access.

Space-saving and easy installation.
Rack Mounting
Just simply plug your NVR into the rack and connect it to the appropriate power and communication cables. Then, it is ready to go. This will give more convenience for many industrial and commercial applications.

No need to check long compatibility lists.
ONVIF Ensures Compatibility
Easily add IPCs from VIGI and other brands to establish a powerful and varied network thanks to barrier-free compatibility

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

One system. Full security.

Run your business with peace of mind.

The VIGI professional surveillance system by TP-Link is dedicated to protecting the business you've worked hard to build — whenever, wherever. Our outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.

Techninė specifikacija

Performance	
Video input channels	32 channels
Maximum resolution	3840 x 2160 pixels
Alarm input channels	16
Alarm output channels	4
Number of simultaneously playbacked channels	16 channels
Video recording modes	720p, 1080p
Supported resolutions	3840 x 2160, 1920 x 1080, 1680 x 1050, 1440 x 900, 1280 x 1024, 1280 x 720, 1024 x 768
Video motion detection	Yes
Video loss detection	Yes
Video formats supported	H.264, H.264+, H.265, H.265+
Backup function	Yes
Playback modes	Digital zoom, Fast play, Forward, Full screen, Pause, Play, Stop
Input bandwidth	320 Mbit/s
Output bandwidth	320 Mbit/s
Recording modes	Manual, Schedule
Audio system	2-way
Hard drive	
Number of HDDs installed	0
HDD capacity	0 GB
Maximum storage capacity	10 TB
HDD interface	SATA
Number of HDDs supported	4
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
Ethernet LAN data rates	10,100,1000 Mbit/s
HDMI ports quantity	1
VGA (D-Sub) output ports	1
USB 2.0 ports quantity	2

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Line-in	Yes
Audio output	1
RS-232 ports	1
Supported network protocols	UPnP, NTP, ONVIF, CGI

Features

Rack mounting	Yes
Buzzer off	Yes
Product colour	Black

Power

Power consumption (max)	48 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz

System requirements

Mobile operating systems supported	Android, iOS
Browser supported	Chrome (57+), Firefox (52+), Edge (91+)

Operational conditions

Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	440 mm
Depth	330 mm
Height	44 mm
Weight	4 kg
Package width	440 mm
Package depth	528 mm
Package height	100 mm
Package weight	5.22 kg

Packaging content

Cables included	AC, Power
Quick installation guide	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH
Niederkasseler Lohweg 175, 40547 Düsseldorf, DE
tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.