Dahua Technology WizMind NVR5216-XI Black

Gamintojas: **DAHUA** · Modelis: **NVR5216-XI** · EAN: **6923172510143** · Prekės kodas: **1031588**



1 293,90 €

Kaina su PVM

Be PVM: **1 069,34 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats
- ✓ Max. decoding capability: 32 × 1080p@30 fps
- ✓ Max. 512/512/512 Mbps incoming/recording/outgoing bandwidth
- ✓ Supports IP cameras with a resolution up to 32 MP
- ✓ Supports AcuPick with up to 16 channels
- ✓ AI by Recorder supports 8-channel face detection and recognition, up to 20 face databases and 200,000 face images; 8-channel metadata; 16-channel perimeter protection; 16-channel SMD Plus
- ✓ AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting
- ✓ Supports N+M cluster, ISCSI
- ✓ Supports EPTZ, and one-click arming and disarming







Techninė specifikacija

Performance	
Video input channels	16 channels
Maximum resolution	3840 x 2160 pixels
Alarm input channels	4
Alarm output channels	2

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Video recording modes	720p, 1080p, 2160p
Supported resolutions	3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768
Video motion detection	Yes
Audio formats supported	G.711 A-law, G.711 µ-law, G.726, PCM
Video formats supported	H.264, H.264+, H.265, H.265+, M-JPEG
Operating system installed	Embedded LINUX
Face detection	Yes
Hard drive	
Maximum storage capacity	20 TB
HDD interface	SATA
Number of HDDs supported	2
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Power over Ethernet (PoE)	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Power over Ethernet (PoE) ports quantity	8
HDMI ports quantity	1
VGA (D-Sub) output ports	1
USB 2.0 ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
RS-485 ports	1
RS-232 interface	Yes
Features	
Rack mounting	Yes
On/off switch	Yes
Product colour	Black
Compatible products	Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec
Certification	FCC: 47 CFR FCC Part15, SubpartB, Class A CE-EMC: EN 55032: 2015+A1: 2020; EN IEC 61000-3-2: 2019+A1: 2021; EN 61000-3-3: 2013+A1: 2019+A2: 2021; EN 55035: 2017+A11: 2020; EN 50130-4: 2011+A1: 2014 CE-LVD: EN 62368-1: 2014
Processor	
Built-in processor	Yes
Power	
Power consumption (typical)	10 W

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

AC input voltage	100 - 240 V
AC input frequency	47 - 63 Hz
Power over Ethernet (PoE) power per port	25.5 W
System requirements	
Mobile operating systems supported	Android, iOS
Operational conditions	
Operating temperature (T-T)	-10 - 65 °C
Operating relative humidity (H-H)	10 - 93%
Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Width	375 mm
Depth	283 mm
Height	56 mm
Weight	1.56 kg
Package width	433 mm
Package depth	366 mm
Package height	141 mm
Package weight	2.86 kg

Gamintojo ir saugos informacija

GAMINTOJAS

Zhejiang Dahua Technology Co., Ltd
Bin'an Road, Binjiang District No.1187 & 1199, 310053 Hangzhou, CN
dahuasecurity.com

ATSAKINGAS ASMUO ES

Dahua Technology GmbH
Niederkasseler Lohweg 185, 40547 Düsseldorf, DE
dahuasecurity.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt