TP-Link DeltaStream 8-port Pizza-box GPON Optical Line Terminal

Gamintojas: **TP-LINK** · Modelis: **DS-P7001-08** · EAN: **4897098683170** · Prekės kodas: **1031836**



1 993,90 €

Kaina su PVM

Be PVM: **1 647,85 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8 GPON Ports: Supports 1:128 splitting ratio for every port—up to 1024 ONTs by one device
- ✓ High-Speed Uplink Ports: Provides 2× 10GE SFP+ ports and 1× gigabit uplink port
- ✓ Redundant Dual Power Supplies: Carrier-class reliability with dual hot-swapping AC+DC power supplies
- ✓ Complete L2 & Advanced L3 Functions: Satisfies the need for numerous commercial requirements
- ✓ Centralized Management: Via DeltaStream PON Management System (DPMS), SNMP, CLI, and WEB UI
- ✓ Advanced L2/L2+ Functions: Static Routing, IGMP Snooping, and more meet the requirement for different applications





Aprašymas

8-Port GPON Optical Line Terminal

8 GPON Ports,
Supports 1024 ONUs
Supports 1:128 splitting ratio for every port—up to 1024 ONTs by one device.

Free Centralized Management
Via DeltaStream PON Management System (DPMS)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Easy maintenance and centralized management makes your life a breeze. Configure and update all your devices at once via DeltaStream PON Management System (DPMS), SNMP, CLI and Web UI.

- No Additional Expense
- Improve Management Efficiency And Reduce Maintenance Costs
- The Easy-to-Use Dashboard Ensures Hassle-Free Configuration

Compact Size, Flexible Deployment

Mount in a rack for flexible deployment with all your other products.

Constant Reliability Through Dual Redundant Power Supplies

Dual redundant power supplies ensures carrier-class reliability. AC, DC and mixed power input supported.

Techninė specifikacija

Features	
Static route	Yes
DHCP server	Yes
DHCP relay	Yes
IGMP snooping	Yes
Multicast Listener Discovery (MLD) snooping	Y
Quality of Service (QoS) support	Yes
GPON split ratio (max)	1:128
Maximum operating distance (GPON)	20000 m
Access Control List (ACL)	Yes
Ports & interfaces	
Upstream ports	Gigabit Ethernet
Ethernet LAN (RJ-45) ports	2
GPON ports quantity	8
SFP/SFP+ slots quantity	2
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
DC voltage range	38.4 - 72 V
Power consumption (max)	70 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	440 mm
Depth	260 mm
Height	44 mm

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH
Niederkasseler Lohweg 175, 40547 Düsseldorf, DE
tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.