ATEN CS1942ATC KVM switch Black

Gamintojas: **ATEN** · Modelis: **CS1942ATC** · EAN: **4710469343162** · Prekės kodas: **1031888**



1 562,90 €

Kaina su PVM

Be PVM: **1 291,65 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ One USB / DisplayPort console controls 2 DisplayPort computers and shares 2 USB peripherals
- ✓ Supports 2048 x 2048 @ 60 Hz screen resolutions dedicated for radar monitoring; maximum resolution up to 4096 x 2160 @ 60 Hz
- ✓ Zero-Second Switch – provides continuous video stream and real-time switching
- ✓ Supports power failover – 2 DC jacks for power redundancy to ensure constant availability for mission-critical applications
- ✓ Computer Selection via front panel pushbuttons, hotkeys, mouse, RS-232 commands, and remote port selector
- ✓ Video DynaSync – exclusive ATEN technology eliminates boot-up display problems and optimizes resolutions when switching between ports
- ✓ EDID Expert – smooth power- up, high-quality display and use of the best video resolution across different screens
- ✓ Supports serial port switching for legacy devices
- ✓ Built-in 2-port USB 3.1 Gen 1 hub with SuperSpeed 5 Gbps data transfer rates
- ✓ DisplayPort 1.2, and HDCP compliant







Aprašymas

The ATEN CS1942ATC 2-Port USB 3.0 4K DisplayPort Dual Display KVMP Switch for ATC is tailor-made for Air Traffic Control scenarios. It supports 2Kx2K resolution, making it perfect for radar monitoring, and also enables constant monitoring of flight information and mission-critical processes. Incorporating dual display capability, users can enjoy a wider screen and easy switch between the two DisplayPort systems.

The Zero-Second Switch function ensures nearly real-time switching without any black screens, providing air traffic controllers instant access to two

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

USB / DisplayPort-interfaced dual display ATC computers for crucial operations. Port switching is flexible via pushbuttons, hotkeys, mouse, RS-232 commands, or an optional accessory the remote port selector.

With two lockable DC jacks for power redundancy, the CS1942ATC ensures uninterrupted operation and constant availability for mission-critical applications. It aims to greatly minimize or eliminate the risk of downtime. Patented ATEN technology – Video DynaSync™, and EDID expert™, combined with DisplayPort 1.2 and video resolutions up to 4K @ 60 Hz, it delivers optimized display resolution with exceptional detail and clarity in all conditions.

The CS1942ATC creates a safer environment and enhanced operational efficiency for Air traffic Control Towers, Approach Control Rooms, and Area Control Centers, specifically tailored the air traffic control industry.

Techninė specifikacija

Ports & interfaces	
Number of computers controlled	2
Keyboard port type	USB
Mouse port type	USB
Video port type	DisplayPort
Console ports	3.5mm headphone, 3.5mm mic, DisplayPort, USB A, VGA (D-Sub)
VGA (D-Sub) ports quantity	3
DisplayPorts quantity	4
Console USB ports quantity	2
Console DisplayPorts ports quantity	2
USB hub	Yes
USB 3.2 Gen 1 (3.1 Gen 1) Type-A hub ports quantity	2
USB connector type	Micro-USB, USB Type-A
Audio connections	Yes
Headphone outputs	2
Number of microphone inputs	2
RJ-11 ports quantity	1
DC-in jack	Yes
Performance	
HD type	4K Ultra HD
Maximum resolution	4096 x 2160 pixels
Video bandwidth	60 Hz
Firmware upgradeable	Yes
Design	
Product colour	Black
Housing material	Metal

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

LED indicators	Yes
Push button	Yes
Hot keys	No
Display	
Built-in display	Yes
Power	
Power source	DC
Input voltage	12 V
Power consumption (typical)	17.8 W
Operational conditions	
Operating temperature (T-T)	0 - 20 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	161 mm
Depth	335 mm
Height	65.5 mm
Weight	1.88 kg
Packaging data	
Package width	133 mm
Package depth	499 mm
Package height	324 mm
Package weight	4.21 kg
Logistics data	
Harmonized System (HS) code	84718000
Master (outer) case width	427 mm
Master (outer) case length	519 mm
Master (outer) case height	348 mm
Master (outer) case gross weight	13.7 kg
Country of origin	Taiwan

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Greitos pradžios vadovas
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.
Datung Road No.125, Sec. 2, 221 New Taipei City, TW
aten.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.