Axagon ADE-AR USB-A 3.2 Gen 1 - Gigabit Ethernet 10/100/1000 Adapter - Adapter - Digital/Daten Eternetas 1000 Mbit/ai

Gamintojas: **AXAGON** · Modelis: **ADE-AR** · EAN: **8595247907929** · Prekės kodas: **1031959**



14,90 €

Kaina su PVM

Be PVM: **12,31 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ USB 2.0/3.2 Gen 1 (3.1 Gen 1) Eternetas
- ✓ Greitas eternetas, Gigabitinis eternetas 1000 Mbit/ai
- ✓ Taikoma: Kompiuteris / knyginis kompiuteris Lustų rinkinys: Realtek RTL8153













Aprašymas

The external network card AXAGON ADE-AR easily converts USB-A 3.2 Gen 1 port to Gigabit Ethernet port. USB network adapter compatible with 10/100/1000 Mbit/s expands the computer with a fast and stable network connection, adds the missing RJ-45 network connector, adds another network card, or replaces the original non-functional network connection.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

In addition to gigabit throughput, the LAN adapter offers a wide range of features such as. IPv4/IPv6 checksum to reduce CPU load by checksums, the crossover detection and auto-correction, TCP large send offload, support for various modes of the Wake-on-LAN feature, the work with VLAN and advanced Power Management features.

Thanks to its compact dimensions and minimal weight, it is an ideal accessory for laptops. Support for current versions of Windows, macOS, Linux and Chrome OS operating systems allows it to be used for any desktop computer, laptop or ultrabook. In Windows from version 8.1 and above, the adapter enables easy automatic installation without the need for an Internet connection.

Input:
• USB 5Gbps (USB 3.2 Gen 1 / USB 3.0).
• Backward compatible with USB 480Mbps (USB 2.0) and USB 1.1.
• Connection to computer via USB type A male connector.

Output:
• Gigabit Ethernet interface with RJ-45 connector for UTP or STP cable connection.
• Supported transmission rates for the Ethernet interface 10/100/1000 Mb/s.
• Supported IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T specifications.
• 10/100/1000 Mb/s auto-detection.
• Supports IPv4 / IPv6 packet Checksum Offload Engine (COE) to reduce processor load, including IPv4 IP/TCP/UDP/ICMP/ IGMP & IPv6 TCP/UDP/ICMPv6 checksum control and generation.
• Supports TCP Large Send Offload V1 and V2.
• Supports IEEE 802.1P Layer 2 priority encoding & decoding.
• Supports IEEE 802.1Q VLAN tagging.
• Supports IEEE 802.3az EEE (Energy Efficient Ethernet) - reduce power consumption at rest.
• Supports Jumbo frame.
• Supports full-duplex transmissions with IEEE 802.3x flow control and half-duplex transmissions with back-pressure flow control.
• Supports Auto MDI/MDIX - crossover detection and auto-correction eliminates the need for crossover cables.
• Supports hardware Cyclic Redundancy Check (CRC) to detect transmission errors.
• Supports Pair Swap/Polarity/Skew Correction.

Other features:
• Full Plug and Play and Hot Plug support.
• Supports CDC-ECM – for automatic installation of drivers across different OSs.
• Adapter power supply via USB (bus power) - no auxiliary power supply required.
Two LEDs to indicate network activity and the adapter's connection to the network.
• Dimensions 58 x 24 x 16 mm.
• Weight 22 g (incl. cable).
• USB cable length 15 cm.
• The Realtek RTL8153 chipset is used.

Wake-on-LAN feature support in different modes:
• Supports sleep mode and remote Wake Up via Magic Packet, Microsoft Wakeup Frame, Microsoft Wake Packet Detection and Link Change Wake-up.
• Supports ECMA-393 proxZzzy® standard for sleeping hosts to manage the network connection of sleeping guests using proxy servers.
• RealWoW! technology support allows remote wake up over the Internet.

Advanced Power Management features:
The adapter supports advanced power management to reduce losses during standby or light traffic on the network. It further supports advanced power saving when the Ethernet cable has been disconnected.
• Supports Advanced Configuration Power Management Interface (ACPI).
• Supports Power Management offload (ARP & NS).

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

• Supports Microsoft Always On Always Connected (AOAC).
• Supports Intel Converged Platform Power Management (CPPM).
• Supports Link Power Management (LPM).
• Supports Operating System-directed Power Management (OSPM).
• Supports IEEE 802.3az EEE (Energy Efficient Ethernet).

Supported operating systems:
• Windows, macOS, Linux and Chrome OS.

Package contains:
• USB - Gigabit Ethernet adapter with fixed 15 cm long USB-A cable,
• multilingual manual CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / TR / BG / CN / ARA,
• packed in a cardboard box with a hanging hole.

Techninė specifikacija

Ryšys	
Ryšio technologija	Vielinis
Priimančioji sąsaja	USB
Sąsaja	Eternetas
Ethernet LAN (RJ-45) portų kiekis	1
USB versija	2.0/3.2 Gen 1 (3.1 Gen 1)
Tinklas	
Didžiausias duomenų perdavimo greitis	1000 Mbit/ai
Tinklo standartai	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az
Ethernet LAN jungtis	Taip
Eterneto sąsajos tipas	Greitas eternetas, Gigabitinis eternetas
Eterneto LAN duomenų perdavimo norma	10,100,1000 Mbit/ai
„Wi-Fi“	Ne
Wake-on-LAN pasirengimas	Taip
Pilnai abipusis (duplex)	Taip
Jumbo Frames palaikymas	Taip
VLAN palaikymas	Taip
LAN kontroleris	Realtek RTL8153
Konstrukcija	
Vidinis	Ne
Taikoma	Kompiuteris / knyginis kompiuteris
Produkto spalva	Juoda
Lustų rinkinys	Realtek RTL8153
„Plug and Play“ funkcija	Taip

LED indikatoriai	Taip
Kilmės šalis	Kinija
Sertifikavimas	CE
Energijos valdymas	
USB maitinimas	Taip
Sistemos reikalavimai	
Palaikomos „Windows“ operacinės sistemos	Taip
Palaikomos MAC operacinės sistemos	Taip
Palaikoma operacinė sistema „Linux“	Taip
Palaikomos serverio valdymo sistemos	Taip
Svoris ir matmenys	
Plotis	58 mm
Ilgis	24 mm
Aukštis	16 mm
Svoris	22 g
Pakuotės duomenys	
Pakuotės plotis	203 mm
Pakuotės gylis	99 mm
Pakuotės aukštis	28 mm
Paketo svoris	68 g
Pakuotės turinys	
Pridėti kabeliai	USB
Instrukcija	Taip
Techninė informacija	
Atitikties sertifikatai	RoHS
Garantinis laikotarpis	3 metai
Matmenys ir svoris	
Matmenys (I × P × A)	3,00cm × 10,00cm × 20,00cm

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

GAMINTOJAS

RealQ, s.r.o.
Železná 663/5, 619 00 Brno-jih, CZ
axagon.eu

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt