Zyxel XGS1930-28HP Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **ZYXEL** · Modelis: **XGS1930-28HP-EU0101F** · EAN: **4718937595006** · Prekės kodas: **1032019**



641,91 €

Kaina su PVM

Be PVM: **530,50 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ NebulaFlex™ gives you the flexibility to switch between standalone and our license-free Nebula cloud management
- ✓ Nebula cloud management allows easy deployment, real-time configurations and effortless access to all your cloud devices anytime
- ✓ Handles the increasing highbandwidth applications in your office affordably with four built-in 10G SFP+ uplinks
- ✓ Easy management and setup with web-based interface and user-friendly wizard
- ✓ Smart fan design offers silent operations in your office
- ✓ Check real-time status intuitively by cloud and PoE LED indicators



Aprašymas

Flexible and easy way to manage your switch

The XGS1930 can be used in two modes by utilizing Zyxel's NebulaFlex. You are able to easily change between standalone and our license free Nebula cloud management platform, anytime, with a few simple clicks. You can easily access advanced features such as VLAN, Quality of Service (QoS), IGMP Snooping, Link Aggregation (LAG) wether you choose intuitive web-based GUI or cloud-based Nebula management platform.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

The XGS1930 enables cloud manageability with Zyxel's NebulaFlex to protect your investment by having the flexibility to benefit from the cloud in your own time, without the need to worry about additional ongoing licensing costs. You can grasp your network device status and perform remote configuraitons anytime, anywhere.

A new and flexible approach to 10G!

Under the new stylish carbon-like cover comes new hardware and software to widen the user experience for our new series of 10G switches. The XGS1930's flexible approach includes the introduction of NebulaFlex, giving you the ability to configure the switch without unboxing. The XGS1930 also includes intuitive new features like the One-touch 'Restore' button on the front panel.

What to benefit from Central management?

The XGS1930 series of switches are able to join our License Free Cloud management platform, Nebula. Simply register your switch via the portal (Nebula Control Center) and the device will automatically join, auto provision and begin to give you real-time control and information, anywhere, anytime.

Not ready for the cloud… Just yet?

Not ready for the cloud? No problem the XGS1930 series offers traditional standalone (Smart Managed) configuration via it's intuitive local web based setup, whilst always giving you the flexibility to centrally control via Nebula when you are ready without any additional fees.

An affordable approach to 10G, the backbone of any network.

The XGS1930 series has been designed to suite a wide range of scenarios that SMBs are often faced with. Feature rich, flexible management options and 10G uplinks, all make the XGS1930 series the first choice for SMBs looking for an upgrade path from 1G, future proofing or have requirements for higher bandwidths across their backbone.

More available power with intelligent PoE support.

The XGS1930 series offers 30-watt (802.2at) PoE+ to each port and gives a large PoE+ budget of 375w on all PoE models. The PoE is further enhanced with intelligent PoE (Smart Power), allowing the switch to deliver the actual power required to devices connected without wasting power often lost in the PoE allocation process. This approach can see the switch support more PoE devices on a single switch compared to traditional smart managed switches, even power-hungry devices like CCTV and Wireless Access Points.

Experience whisper-silent operation.

The XGS1930 series has been designed with smart fan technology to automatically adjust speeds round the temperature of the device. This allows the switch to minimize the acoustic noise and create a whisper-silent operation in typical deployments.

Techninė specifikacija

Management features	
Switch type	Managed
Switch layer	L3
Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP+ module slots quantity	4

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Fiber optic connector	SFP+
Network	
Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	Yes
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Port mirroring	Yes
IP routing	Yes
Routing entries	32
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Spanning tree protocol	Yes
VLAN support	Yes
Virtual LAN features	Voice VLAN, Port-based VLAN
Number of VLANs	4000
Data transmission	
MAC address table	16000 entries
Switching capacity	128 Gbit/s
Forwarding rate	95.2 Mpps
Static route	Yes
Path MTU discovery	Yes
Packet buffer memory	1.5 MB
Security	
DHCP features	DHCP relay, DHCPv6 relay, DHCP client
Access Control List (ACL)	Yes
IGMP snooping	Yes
Security algorithms	802.1x RADIUS, HTTPS, SHA-2, SNMPv3, SSL/TLS
SSH/SSL support	Yes
Loop protection	Yes
Authentication	Guest VLAN, MAC-based authentication, Port-based authentication
Password protection	Yes
CPU defense	Yes
Multicast features	

Multicast support	Yes
Protocols	
GARP VLAN Registration Protocol (GVRP)	Yes
Design	
Rack mounting	Yes
Product colour	Black
Safety	LVD, BSMI
Electromagnetic compatibility	FCC 15 A, CE A, BSMI EMC
Performance	
Internal memory	512 MB
Flash memory	32 MB
Noise level	28.5 dB
Mean time between failures (MTBF)	1369432 h
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	471 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	24
Total Power over Ethernet (PoE) budget	375 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 95%
Storage relative humidity (H-H)	10 - 95%
Heat dissipation	1606.11 BTU/h
Weight & dimensions	
Width	441 mm
Depth	330 mm
Height	44 mm
Weight	4.6 kg
Packaging content	
Cables included	AC

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Rack mount kit	Yes
Packaging data	
Package width	585 mm
Package depth	503 mm
Package height	95 mm
Package weight	5.82 kg
Certificates	
Certification	RoHS
Logistics data	
Harmonized System (HS) code	85176990

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Zyxel Networks Corporation
Industry East RD. IX, Hsinchu Science Park 2,
30076 Hsinchu, TW
zyxel.com

ATSAKINGAS ASMUO ES

Zyxel Networks A/S
Adenauerstraße 20/A3, 52146 Würselen, DE
zyxel.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt