


AG Neovo HMQ-4301 vaizdo stebėjimo monitorius CCTV monitorius 109,2 cm (43") 3840 x 2160 pikseliai

Gamintojas: **AG NEOVO TECHNOLOGY** · Modelis: **HM431011M0000** · EAN: **4710739597493** · Prekės kodas: **103285**



1 314,89 €

Kaina su PVM

Be PVM: **1 086,69 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4K UHD 3840 x 2160 resolution
- ✓ Versatile connectivity: VGA, DVI, HDMI, SDI (BNC), Composite (BNC) inputs
- ✓ Supports multiple SDI formats: 3G / HD / SD-SDI
- ✓ SDI (BNC) and Composite (BNC) loop-through output ports
- ✓ Anti-Burn-in technology prevents image ghosting
- ✓ RS232 / LAN connection for easy control and management



Aprašymas

The HMQ-4301 is a 43-inch 4K surveillance display with SDI that supports live video streaming over long distances in surveillance and monitoring applications. The display technology is future-proof and compatible with analogue and digital surveillance systems. The HMQ-4301 supports up to 8MP image quality through an HDMI connection to present crisp video footage. With SDI loop-through design, the display can receive real-time 1080p images from HD-SDI or 3G-SDI cameras and transmit the uncompressed videos to multiple SDI displays with ultra-low latency. It fulfils the need for high-quality image details to live video monitoring in broadcasting and video surveillance solutions.

See Intricate Details in 4K

The HMQ-4301 features 3840 x 2160 pixels, offering finer video footage. The high resolution enables zoom-in with clear detail as CCTV evidence. As a result, the operator can zoom in on a license plate number or the lines on a face. Furthermore, the panel enables the operator to view smooth 4K video and graphics with a new level of detail and clarity.

Support 3G-SDI 1080p High-definition Video Streaming

Support for 3G-SDI and HD-SDI at 1080p resolution enables the HMQ-4301 to display live video signals from SDI cameras. The SDI loop-through output terminal allows displaying the same image to a local SDI monitor or other SDI device.

Uncompressed and Ultra-low Latency Transmission via Long Distance

The HMQ-4301 supports multiple SDI video standards, including SD, HD and 3G-SDI formats. These standards support ultra-low latency and uncompressed transmission of HDTV signals up to 300 meters for live video monitoring.

The maximum distances for 3G-SDI, HD-SDI and SD-SDI signal transmission via RG6 coaxial cables:

3G-SDI: 100M

HD-SDI: 150M

SD-SDI: 300M

Fine-tune CCTV IMAGES for Maximum Clarity and Detail

A special pre-configured CCTV Mode maximizes image clarity in low-light footage. You can make granular adjustments and quickly fine-tune your video footage with sharpness, saturation, contrast, brightness, and more. As a result, you don't need to waste time constantly testing and re-adjusting because the HMQ-4301 already has it all figured out!

Enhanced Gamma Selection

Offering an enhanced gamma selection makes for excellent visual optimization. As a result, you can easily improve the light, shadow, and colour balance quality of your videos.

Tailor-Made for Reliability

The HMQ-4301 security display adopts a commercial-grade panel and incorporates high-quality components to ensure 24/7 continuous operations. Furthermore, the patented Anti-burn-in™ Technology adds another protection level in mission-critical environments.

Metal Casing Ensures Reliable Monitoring

The outer metal case provides enhanced heat dissipation, offering a high level of strength and durability. In turn, this improves the cooling performance to ensure 24/7 proper operation.

Easy Control and Integration

The built-in RS232 / LAN connections and AG Neovo PID command & Ctrl software allow you to easily control, configure and maintain multiple-display installations in a simple and intuitive way. The software provides intuitive web and mobile interfaces for remote management and OSD-related settings.

Versatile Connectivity and Video Loop Through

The HMQ-4301 can easily connect to various surveillance equipment with HDMI, DVI, VGA, SDI and Composite (BNC) ports. Its BNC inputs and outputs enable security camera footage to be directly displayed on the screen and loop through to the second device for instant monitoring.

Techninė specifikacija

Konstrukcija

Gaminio tipas	CCTV monitorius
Montavimo tipas	Montuojama ant sienos
Produkto spalva	Juoda

Ekranas

Ekrano įstrižainė	109,2 cm (43")
Ekrano rezoliucija	3840 x 2160 pikseliai
Ekrano tipas	LCD
Skydo tipas	IPS
Ekrano ryškumas	350 cd/m²
Matymo kampas, horizontalus	178°
Matymo kampas, vertikalus	178°
Ekrano spalvų skaičius	1,07 milijardo spalvų
Pikselių žingsnis	0,245 x 0,245 mm
Kontrasto santykis (tipinis)	1200:1
Reakcijos laikas	5 ms
Miglotumo koeficientas	1%
RGB spalvų erdvė	NTSC
NTSC aprėptis (tipinė)	72%
Neblizgantis ekranas	Taip
Paviršiaus kietumas	3H
Horizontalus skaitmeninis dažnis	15 - 135 kHz
Vertikalus skaitmeninis dažnis	24 - 86 Hz

Veikimo charakteristikos

Įmontuoti garsiakalbiai	Taip
Įmontuotų garsakalbių skaičius	2
Garsiakalbio galingumas	5 W
VESA tvirtinimo pagrindas	Taip
Suderinama su VESA sienos tvirtinimo sistema	400 x 200 mm

Ryšys

HDMI portų kiekis	1
HDMI versija	2.0
DVI-D prievadų skaičius	1
VGA (D-Sub) portų kiekis	1

Ethernet LAN jungtis	Taip
RJ-45 prievadų skaičius	1
USB prievadas	Taip
USB 2.0 portų kiekis	1
Kompozuoti video in	1
Kompozicinio video išėjimas	1
3,5 mm įvestis	Taip
3,5 mm išvestis	Taip
RS-232 portai	1
SDI įėjimai	1
SDI išėjimai	1
Skaitmeninis garso optinis išėjimas	1
Energijos valdymas	
Maitinimo šaltinio tipas	AC
Maitinimo tipas	Vidinis
Energijos suvartojimas	75 W
Energijos suvartojimas (laukimo režimu)	0,5 W
Energijos suvartojimas (off)	0,3 W
AC įėjimo įtampa	100 - 240 V
AC įėjimo dažnis	50 - 60 Hz
AC adapterio išėjimo įtampa	100 - 240 V
Energijos vartojimo efektyvumo klasė (SDR)	G
Energijos efektyvumo skalė	Nuo A iki G
Energijos sąnaudos (SDR) per 1000 valandų	75 kWh
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	10 - 60 °C
Darbo santykinės drėgmės diapazonas	20 - 85%
Sandėliavimo santykinis drėgmės diapazonas	10 - 95%
Techninė informacija	
Atitikties sertifikatai	CE, Žemos įtampos direktyva (LVD), REACH, RoHS, UKCA, WEEE
Tvarumo reikalavimų laikymasis	Taip
Svoris ir matmenys	
Svoris	9,2 kg

Aukštis	558,3 mm
Ilgis	84,6 mm
Plotis	969,9 mm
Pakuotės plotis	1070 mm
Pakuotės gylis	153 mm
Pakuotės aukštis	663 mm
Paketo svoris	11,9 kg
Pakuotės turinys	
Pridėti kabeliai	AC, HDMI
Pridedamas nuotolinio valdymo pultelis	Taip
Greitos pradžios vadovas	Taip
Pridėtos baterijos	Taip
Matmenys ir svoris	
Matmenys (I × P × A)	107,00cm × 66,00cm × 19,00cm
Svoris	12,04kg