

Philips 275S9JML/00 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LCD Black

Gamintojas: **PHILIPS** · Modelis: **275S9JML/00** · EAN: **8712581801168** · Prekės kodas: **103827**



204,90 €

Kaina su PVM

Be PVM: **169,34 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 68.6 cm (27") Black
- ✓ Height adjustment 13 cm Built-in speaker(s)
- ✓ USB upstream port type: USB Type-B
- ✓ Screen shape: Flat
- ✓ Maximum refresh rate: 75 Hz Response time: 4 ms
- ✓ 2560 x 1440 pixels Quad HD Panel type: VA
- ✓ Energy efficiency class (SDR): F



Aprašymas

Our S Line monitor delivers business efficiency. Features like Flicker-free and LowBlue mode make work easy on the eyes and increase your productivity.

Techninė specifikacija

Specifications

Sandėlio grupė

Displays > Lcd Monitor [+331][-416]

Display	
Display diagonal	68.6 cm (27")
Display resolution	2560 x 1440 pixels
Native aspect ratio	16:9
Display technology	LCD
HD type	Quad HD
Panel type	VA
Response time	4 ms
Screen shape	Flat
Contrast ratio (typical)	4000:1
Maximum refresh rate	75 Hz
Display number of colours	16.7 million colours
LED backlight	Yes
Backlight type	W-LED
Display brightness (typical)	300 cd/m²
Anti-glare screen	Yes
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.2331 x 0.2331 mm
Pixel density	108.79 ppi
Horizontal scan range	30 - 114 kHz
Vertical scan range	48 - 75 Hz
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.5 cm
DDC/CI	Yes
Haze rate	25%
Surface hardness	3H
Colour depth	8 bit
Colour gamut standard	sRGB, NTSC
Colour gamut	97%
sRGB coverage (typical)	119%
NTSC coverage (typical)	97%
Display sRGB	Yes
Display panel size	27 inch/68.5 cm

Performance

VESA Adaptive Sync support	Yes
Component video sync	Separate Sync
Flicker-free technology	Yes

Multimedia

Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	4 W

Design

Market positioning	Business
Product colour	Black
Front bezel colour	Black
Feet colour	Black

Ports & interfaces

Built-in USB hub	Yes
USB upstream port type	USB Type-B
Audio output	Yes
HDCP	Yes
HDCP version	1.4
Charging port type	USB Type-A

Ergonomics

VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington
Adjustable height (max)	13 cm
Pivot	Yes
Pivot angle	-90 - 90°
Swivelling	Yes
Swivel angle range	-180 - 180°
Tilt adjustment	Yes
Tilt angle range	-5 - 25°

On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
Plug and Play	Yes
LED indicators	Operation, Stand-by
Power	
Energy efficiency class (SDR)	F
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	26 kWh
Power consumption (typical)	19.6 W
Power consumption (standby)	0.3 W
Power consumption (off)	0.3 W
Power consumption (PowerSave)	15 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	0 - 12192 m
Weight & dimensions	
Width (with stand)	613 mm
Depth (with stand)	205 mm
Height (with stand)	525 mm
Weight (with stand)	5.6 kg
Width (without stand)	613 mm
Depth (without stand)	56 mm
Height (without stand)	367 mm
Weight (without stand)	3.84 kg
Packaging data	
Package width	780 mm

Package depth	161 mm
Package height	445 mm
Package weight	8.2 kg
Packaging content	
Stand included	Yes
Manual	Yes
Bundled software	SmartControl
Sustainability	
Doesn't contain	Mercury, PVC/BFR
Other features	
Compatible operating systems	Mac OS X; Windows 11/10/8.1/8
Exterior finish type	Textured
Monitor sync input signal	Separate Sync
EasyRead mode	Yes
LowBlue mode	Yes
Mean time between failures (MTBF)	70000 h
User controls	SmartImage/Back; Brightness/UP; Input/Down; Menu/OK; Power On/Off
Picture enhancement	SmartImage
Regulatory Approvals	CB; CE Mark; CU-EAC; EAEU RoHS; FCC Class B; ICES-003; TUV Ergo; TUV/GS
Recycling data	
Packaging recyclability rate	100%
Product post-consumer recycled plastic	85%
Matmenys ir svoris	
Matmenys (I × P × A)	79,00cm × 45,00cm × 16,00cm
Svoris	8,20kg