CATALYST 1200 24-PORT GE 4X10G - SFP+

Gamintojas: **CISCO** · Modelis: **C1200-24T-4X** · EAN: **889728521734** · Prekės kodas: **104049**



327.90€

Kaina su PVM

Be PVM: **270.99€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 24 Gigabit Ethernet (10/100/1000) RJ-45 ports
- ✓ 4x10G SFP+ uplinks
- ✓ Managed Layer 3 switch, rack mounting
- ✓ Switching capacity 128 Gbit/s, forwarding rate 95.23 Mpps
- ✓ VLAN support with up to 255 VLANs, QoS, IGMP snooping
- ✓ AC input 100 - 240 V, 50 - 60 Hz

Aprašymas

The Cisco Catalyst 1200 (C1200-24T-4X) is a managed Layer 3 switch designed for rack mounting. It provides 24 Gigabit Ethernet (10/100/1000) RJ-45 ports and 4x10G SFP+ uplinks.

Key technical data:

- Switching capacity: 128 Gbit/s
- Forwarding rate: 95.23 Mpps
- MAC address table: 8000 entries
- Packet buffer memory: 1.5 MB
- Jumbo frames support, up to 9000

Management and network features include VLAN support with up to 255 VLANs, link aggregation, spanning tree protocol, broadcast storm control, port mirroring, IGMP snooping and Quality of Service (QoS) support.

The switch is powered from an AC source with an input voltage of 100 - 240 V and an input frequency of 50 - 60 Hz.

Techninė specifikacija

Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Management features	
Switch type	Managed
Switch layer	L3
Quality of Service (QoS) support	Yes
Design	
Rack mounting	Yes
Data transmission	
MAC address table	8000 entries
Jumbo frames	9000
Jumbo frames support	Yes
Switching capacity	128 Gbit/s
Forwarding rate	95.23 Mpps
Packet buffer memory	1.5 MB
Network	
VLAN support	Yes
Number of VLANs	255
Link aggregation	Yes
Spanning tree protocol	Yes
Broadcast storm control	Yes
Port mirroring	Yes
Security	
IGMP snooping	Yes
Power	
AC input voltage	100 - 240V
AC input frequency	50 - 60 Hz
Power source	AC
Matmenys ir svoris	
Matmenys (I × P × A)	59.00cm × 52.00cm × 40.00cm
Svoris	5.13kg

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.