EIZO FlexScan EV3240X-BK computer monitor 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD LCD Black

Gamintojas: **EIZO** · Modelis: **EV3240X-BK** · EAN: **4995047065296** · Prekės kodas: **104130**

1 289,90 €

Kaina su PVM

Be PVM: **1 066,03 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 31.5" 4K monitor with large-screen display and fine 140 ppi resolution
- ✓ Docking function for tablets, notebooks and smartphones thanks to USB-C port with DisplayPort signal channel, LAN and power supply up to 94 watts
- ✓ Choice of black or white housing color
- ✓ Extremely slim case frame: super-compact and ultra-chic design
- ✓ Contrast 2000:1, brightness 350 cd/m2, 178° viewing angle
- ✓ Auto EcoView and EcoView Optimizer for maximum energy savings and optimal ergonomics
- ✓ Signal inputs: USB-C (DisplayPort Alt Mode), DisplayPort, 2 x HDMI
- ✓ Picture-by-Picture and Picture-in-Picture for 2 signal sources and KVM switch function
- ✓ Produced in an environmentally and socially responsible manner

Aprašymas

Thanks to quadruple Full HD resolution, the EV3240X is ideally suited for professional applications. With 3840 x 2160 pixels, it offers a pixel density of 140 dpi on a 31.5" diagonal. Graphics and texts are therefore displayed razor-sharp. Its USB-C port guarantees state-of-the-art connectivity and charges end devices like tablets or notebooks. Thus, it convinces as a fully functional docking, including LAN connection and 94 watts of power delivery for the computer. Fewer cables offer more freedom on the desk. It also shines with its almost frameless design. Highest picture quality and ergonomics inspire and qualify it for highest demands in the office and at home. The case is available in black or white; even the cables are color-

coordinated. The monitor is equipped with two HDMI ports as well as one DisplayPort and USB-C port each. With its two USB upstream ports, the EV3240X can be used as a keyboard/mouse switcher. For example, if both a home PC and a company computer are connected to the monitor in the home office, both computers can be operated with a single keyboard and mouse. When using its Picture-by-Picture function, it even displays two signal sources simultaneously.

Techninė specifikacija

Specifications	
Sandėlio grupė	Displays > Lcd Monitor [+331][-416]
Display	
Display diagonal	80 cm (31.5")
Display resolution	3840 x 2160 pixels
Native aspect ratio	16:9
Display technology	LCD
Touchscreen	No
HD type	4K Ultra HD
Panel type	IPS
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	2000:1
Maximum refresh rate	60 Hz
Display number of colours	16.7 million colours
LED backlight	Yes
Backlight type	W-LED
Display brightness (typical)	350 cd/m²
Anti-glare screen	Yes
Supported graphics resolutions	720 x 400, 1280 x 1024 (SXGA), 3840 x 2160, 800 x 600 (SVGA), 2560 x 1440, 1600 x 1200 (UXGA), 1024 x 768 (XGA), 1680 x 1050 (WSXGA+), 640 x 480 (VGA), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.182 x 0.182 mm
Pixel density	140 ppi
Viewable size, horizontal	69.7 cm
Viewable size, vertical	39.2 cm
Digital horizontal frequency	31 - 135 kHz
Digital vertical frequency	29 - 61 Hz
Display diagonal (metric)	80 cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Colour gamut standard	sRGB
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	4 W
Design	
Market positioning	Office
Product colour	Black
Feet colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B, USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	3
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	94 W
HDMI ports quantity	2
DisplayPorts quantity	1
Headphone outputs	2
Headphone connectivity	3.5 mm
Built-in KVM switch	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

HDCP	Yes
HDCP version	1.4/2.3
Network	
Ethernet LAN	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington
Adjustable height (max)	19.5 cm
Pivot	Yes
Pivot angle	0 - 90°
Swivelling	Yes
Swivel angle range	-90 - 90°
Tilt adjustment	Yes
Tilt angle range	-5 - 35°
Picture-in-Picture	Yes
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Swedish
Power	
Energy efficiency class (SDR)	D
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	21 kWh
Power consumption (typical)	18 W
Power consumption (standby)	0.35 W
Power consumption (max)	196 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width (with stand)	712 mm
Depth (with stand)	242 mm
Height (with stand)	622 mm
Weight (with stand)	9.4 kg
Width (without stand)	712 mm
Depth (without stand)	59 mm
Height (without stand)	415 mm
Weight (without stand)	6.7 kg
Packaging content	
Stand included	Yes
Cables included	AC, USB Type-C to USB Type-C
Quick start guide	Yes
Sustainability	
Sustainability certificates	ENERGY STAR, EPEAT Climate +, EPEAT Gold, TCO
Sustainability compliance	Yes
Other features	
Picture-by-Picture (PbP)	Yes
Automatic brightness control	Yes
Warranty period	5 year(s)
Look-up table (LUT) bit depth	14
Compliance certificates	CB, CCC, CE, China RoHS, Federal Communications Commission (FCC), GS mark, ICES, PSE, RCM, RoHS, cTUVus, UKCA, VCCI, WEEE
Ethernet LAN data rates	10,100,1000 Mbit/s
Ethernet LAN (RJ-45) ports	1
Certification	CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 10, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Matmenys (I × P × A)	81,00cm × 56,00cm × 34,00cm
Svoris	14,44kg