



**Monitorius DELL
UltraSharp
U2724DE 27"
QHD
(2560x1440) IPS
120Hz Hub
Monitorius su
Thunderbolt 4
(90W PD)**

Modelis: DELL-U2724DE

Gamintojas: DELL EMC

EAN: 5397184821480

Prekės kodas: 104407

592.98€

**DELL UltraSharp U2724DE: 27 colių QHD stebėjimo stotis
maksimaliam produktyvumui**

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

DELL UltraSharp U2724DE sukurtas užtikrinti aukščiausią našumą ir vizualinį komfortą. Šis 27 colių Quad HD monitorius veikia kaip galinga produktyvumo stotis, pasižyminti pažangiomis jungtimis, įskaitant „Thunderbolt 4“. Sertifikuotas TÜV 5 žvaigždučių akių komforto sertifikatu, jis sumažina akių nuovargį dėl „Flicker-Free“ (nemirgančios) ir „Low Blue Light“ (mažos mėlynosios šviesos) technologijų, todėl ilgos darbo valandos tampa žymiai patogesnės.

Išskirtinis vaizdo aiškumas ir sklandumas

Patirkite stulbinančias detales ir sklandų judesį, puikiai tinkančius reikloms užduotims, tokioms kaip turinio kūrimas ar analizė. IPS matrica užtikrina plačius 178° žiūrėjimo kampus ir nuoseklų spalvų atkūrimą, o 120 Hz atnaujinimo dažnis suteikia daug sklandesnį judėjimą, lyginant su standartiniais 60 Hz ekranais.

- **Ekrano raiška:** QHD (2560 x 1440) suteikia išskirtinę darbo vietą ir aiškumą.
- **IPS matrica:** Puikus spalvų tikslumas (100% sRGB, 98% DCI-P3) ir platūs 178° žiūrėjimo kampai.
- **Didelis atnaujinimo dažnis:** 120 Hz maksimalus atnaujinimo dažnis užtikrina sklandesnius vaizdus ir geresnį reagavimą.
- **Didelis kontrastas:** 2000:1 tipinis kontrasto santykis užtikrina gilesnę juodą ir ryškesnę baltą spalvą.
- **Akių komfortas:** TÜV 5 žvaigždučių sertifikatas, skirtas mažinti akių nuovargį, su „Low Blue Light“ ir „Flicker-Free“ technologijomis.

Integruota jungčių stotis su Thunderbolt 4 ir 90W galia

Paverskite savo stalą supaprastinta darbo vieta. U2724DE veikia kaip visavertė prijungimo stotelė, leidžianti prijungti ir krauti nešiojamąjį kompiuterį, tuo pačiu supaprastinant laidų valdymą. „Thunderbolt 4“ jungtis užtikrina didelės spartos duomenų perdavimą, tinklo prieigą ir vaizdo išvestį per vieną kabelį.

- **Thunderbolt 4 stotis:** Dvi „Thunderbolt 4“ jungtys itin greitam duomenų ir ekrano prijungimui.
- **Maitinimo tiekimas (PD):** USB-C įkrovimo jungtis tiekia iki 90 W galios, akimirksniu įkraunant prijungtą nešiojamąjį kompiuterį.

- **Platus I/O:** Turi integruotą Ethernet (RJ-45), 1x HDMI 2.1, 2x DisplayPort 1.4 ir 4 USB Type-A išvesties jungtis.

Ergonomiškas dizainas individualiam komfortui

„UltraSharp“ serija teikia pirmenybę vartotojo savijautai, siūlydama visą reguliavimo spektrą.

Lengvai pritaikykite ekrano padėtį savo poreikiams, kad išlaikytumėte optimalią laikyseną visą dieną.

- Reguliuojamas aukštis (iki 150 mm)
- Pasukimo (Swivel), pakreipimo (Tilt) ir pilnos apsukos (Pivot 90 laipsnių) funkcijos
- Integruota kabelių valdymo sistema ir VESA tvirtinimo suderinamumas

DELL yra visame pasaulyje pripažintas technologijų lyderis, skirtas tiekti novatoriškus, patikimus ir didelio našumo kompiuterinius sprendimus profesionaliai ir verslo aplinkai. Šis monitorius, pagamintas laikantis tvarumo sertifikatų, tokių kaip ENERGY STAR ir TCO, atspindi DELL įsipareigojimą kokybei ir aplinkosauginei atsakomybei.

Užsisakykite šiandien iš ++SHOP++, nes siūlome geriausias kainas ir garantuotą klientų aptarnavimą aukščiausios klasės verslo monitoriams.

Experience a new level of visual comfort and productivity with this hub monitor certified by TÜV for 5-star eye comfort. Designed with extensive connectivity and the power of Thunderbolt 4.

Experience a new level of visual comfort and productivity with this hub monitor certified by TÜV for 5-star eye comfort. Designed with extensive connectivity and the power of Thunderbolt 4.

- 68.6cm (27") Quad HD 2560 x 1440 Edge LED IPS
- 8ms, 16:9, 350cd/m², 2000:1
- USB, HDMI, DisplayPort

Actual configuration might differ from illustration

Product Carbon Footprint (PCF):

1. Dell generally uses the PAIA (Product Attribute to Impact

Algorithm)(<http://msl.mit.edu/projects/paia/main.html>) tool for product carbon footprint calculations.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

2. Docking station related PCFs are extracted from corresponding LCAs and as such do not follow the PAIA methodology used for calculating other PCFs in this report.
3. PAIA method is developed by the Massachusetts Institute of Technology's Materials Systems Laboratory and partners.
4. All estimates of carbon footprint are uncertain. Dell Technologies reports the 5th and 95th percentile of the carbon footprint estimate to reflect this uncertainty wherever possible.
(<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>)
5. Please note the emission estimate in this report is calculated using the mean value along with the standard deviation for that product model.
6. Use of default inputs (i.e. not primary data) and assumptions on location of use and other fields can introduce a standard deviation which must be taken into account while completing the calculations.
7. Please note, PAIA uses the ecoinvent Database (<https://ecoinvent.org/the-ecoinvent-database/>) whenever primary data is not made available for calculations.
8. For client and commercial end user computing products, minimum configurations were assumed for calculations. For Server and Storage products, typical configurations or ENERGY STAR (<https://www.energystar.gov/products>) configurations were used for calculations.
9. Use Phase emissions were calculated based on the location of use as "Europe" i.e. the Use Phase emissions are not specific to a single country / location.
10. The report does provide an option for a total emissions number for manufacturing, transport and end of life while leaving the use phase emissions out, in case the customer uses their own calculation methodology for use phase emissions.
11. The lifetime usage assumption at the product family level is as follows: Desktop, Notebook - 4 years, Display - 5 years and Servers - 4 years.
12. For detailed assumptions please refer to the product datasheets in the Dell Technologies reports (<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>).
13. The results from the PAIA tool are liable to change over time as the methodology is improved and datasets are updated. The PAIA version used to calculate emissions has been indicated with each record in the report.
14. Metrics used: The units for global warming potential are in kgCO₂-equivalent or MT (metric ton) CO₂-equivalent (CO₂e).

15. Beginning in June 2024, the data dashboard now incorporates PCF values computed using the Dell PCF calculator. It's important to note that the default location utilized for these calculations shown on the data dashboard is Europe. To access PCF values calculated for the USA and China locales, please refer to the Product PCF PDF document on Dell.com.

Summary: DELL UltraSharp U2724DE. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black, Silver | Vendor Homepage: <https://www.dell.com/en-uk/shop/> | Anti-glare screen: Yes | Backlight type: Edge LED | Colour depth: 8 | Colour gamut: 98 | Colour gamut standard: DCI-P3 | Contrast ratio (typical): 2000:1 | Digital horizontal frequency: 30 - 178 | Digital vertical frequency: 48 - 120 | Display brightness (typical): 350 | Display diagonal: 27 | Display diagonal (metric): 68.47 | Display number of colours: 1.07 billion colours | Display resolution: 2560 x 1440 | Display technology: LCD | HD type: Quad HD | High Dynamic Range (HDR) supported: No | Maximum refresh rate: 120 | Native aspect ratio: 16:9 | Panel type: IPS | Pixel density: 108.97 | Pixel pitch: 0.2331 x 0.2331 | Response time: 8 | Response time (fast): 5 | Screen shape: Flat | sRGB coverage (typical): 100 | Supported graphics resolutions: 1024 x 768 (XGA)/1152 x 864 (XGA+)/1280 x 1024 (SXGA)/1280 x 720 (HD 720)/1600 x 1200 (UXGA)/1600 x 900/1920 x 1080 (HD 1080)/2048 x 1080/2560 x 1440/640 x 480 (VGA)/720 x 400/800 x 600 (SVGA) | Supported video modes: 1080i/1080p/480p/576p/720p | Surface hardness: 3H | Touchscreen: No | Viewable size, horizontal: 596.74 | Viewable size, vertical: 335.66 | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | AMD FreeSync: No | Flicker-free technology: Yes | Low Blue Light technology: Yes | NVIDIA G-SYNC: No | Built-in camera: No | Built-in speaker(s): No | Feet colour: Silver | Front bezel colour: Black | Market positioning: Business | Product colour: Black,Silver | AC (power) in: Yes | Built-in USB hub: Yes | DisplayPort version: 1.4 | DisplayPorts quantity: 2 | HDCP: Yes | HDCP version: 1.4 | HDMI: Yes | HDMI ports quantity: 1 | HDMI version: 2.1 | Headphone out: Yes | Microphone in: No | Number of upstream ports: 1 | Number of USB Type-C upstream ports quantity: 1 | PC Audio in: No | Thunderbolt 4 ports quantity: 2 | USB Power Delivery (USB PD): Yes | USB Power Delivery up to: 90 | USB Type-A downstream ports quantity: 4 | USB Type-C DisplayPort Alternate Mode: Yes | USB Type-C downstream ports quantity: 1 | USB upstream port type: USB Type-C | Ethernet LAN: Yes | Wi-Fi: No | Adjustable height (max): 150 | Cable lock slot: Yes | Cable lock slot type: Kensington | Cable management: Yes | Height adjustment: Yes | On Screen Display (OSD): Yes | Panel mounting interface: 100 x 100 | Pivot: Yes | Pivot angle: -90 - 90 | Plug and Play: Yes | Swivel angle range: -45 - 45 | Swivelling: Yes | Tilt adjustment: Yes | Tilt angle range: -5 - 21 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

VESA mounting: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Energy consumption (SDR) per 1000 hours: 24 | Energy efficiency class (HDR): Not available | Energy efficiency class (SDR): F | European Product Registry for Energy Labelling (EPREL) code: 1591641 | Input current: 2.65 | Power consumption (max): 225 | Power consumption (off): 0.3 | Power consumption (standby): 0.5 | Power consumption (typical): 24.4 | Power supply type: Internal | Non-operating altitude: 5000 - 12192 | Operating altitude: 0 - 5000 | Operating relative humidity (H-H): 10 - 80 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -20 - 60 | Bezel width (bottom): 9.1 | Bezel width (side): 7.75 | Bezel width (top): 7.75 | Depth (with stand): 192.28 | Depth (without stand): 50.12 | Height (with stand): 535.58 | Height (without stand): 352.51 | Weight (with stand): 6980 | Weight (without stand): 5230 | Width (with stand): 612.24 | Width (without stand): 612.24 | Package weight: 10210 | Cables included: AC/DisplayPort/Thunderbolt/USB Type-A to USB Type-C | Power adapter included: Yes | Quick start guide: Yes | Remote control included: No | Stand included: Yes | Stylus included: No | Doesn't contain: PVC/BFR | Sustainability certificates: ENERGY STAR/TCO | Sustainability compliance: Yes | Carbon emissions, end-of-life (kg of CO2e): 5.74 | Carbon emissions, energy usage (kg of CO2e): 181.7 | Carbon emissions, logistics (kg of CO2e): 48.98 | Carbon emissions, manufacturing (kg of CO2e): 412.27 | PAIA version: 1.3.2, 2022 | Total carbon emissions, standard deviation (kg of CO2e): 152 | Total carbon footprint (kg of CO2e): 649 | Compliance certificates: RoHS | RJ-45 ports quantity: 1 | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/1591641/fiches?language=EN> | Energy efficiency class: F | EPREL Registration Number: 1591641 | EPREL Version Number: 2 | Model: U2724DE | Included Accessories: Monitor, Stand Riser, Stand Base, Quick setup guide, Safety, Environmental and Regulatory Information, Factory calibration report; 1 x Power cable 1 x DisplayPort 1.4 cable - 1.8 m 1 x USB Type-A to USB Type-C Gen 2 cable - 1 m 1 x Thunderbolt™ 4 cable - 1 m | Unit Calculated Volume: 0.05535 | Product Net Weight: 7.37 | Unit Calculated Weight: 10.2