iiyama ProLite T2755QSC-B1 kompiuterio monitorius 68,6 cm (27") 2560 x 1440 pikseliai Quad HD LCD Lietimui jautrus ekranas Juoda

Gamintojas: **IIYAMA CONSIGNMENT** · Modelis: **T2755QSC-B1** · EAN: **4948570122981** · Prekės kodas: **104857**



493,90 €

Kaina su PVM

Be PVM: **408,18 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 68,6 cm (27") Juoda
- ✓ Įmontuoti garsiakalbiai
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekrano forma: Plokščias
- ✓ Maksimalus atnaujinimo dažnis: 75 Hz Reakcijos laikas: 5 ms Atsako trukmės matavimo tipas: GTG (Gray to Gray)
- ✓ 2560 x 1440 pikseliai Quad HD Skydo tipas: IPS
- ✓ Energijos vartojimo efektyvumo klasė (SDR): D ErP REACH, RoHS, WEEE










Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903






Aprašymas

The ProLite T2755QSC with its WQHD (2560x1440) resolution and IPS panel technology offers exceptional colors and wide viewing angles. The Optical Bonded Projective Capacitive (PCAP) 10-point touch technology ensures a seamless and accurate touch response and a lower light reflection, in addition, the display is protected against humidity and potential moisture development. A special anti-fingerprint coating ensures a smoother touch and less resistance in the swipe. It makes the screen less static and susceptible to dirt, dust and fingerprints. The monitor supports MPP2.0 (Microsoft Pen Protocol) technology, which is used in digital pens and styluses for use with compatible devices. The pen or stylus can interact with the ProLite T2755QSC, allowing users to write, draw, and navigate on the screen. It is very precise and supports tilt functionality, meaning the users can adjust the thickness and angle of their lines by tilting the pen, providing a more natural and intuitive writing and drawing experience. Its flexible stand can be positioned at several angles creating a comfortable and ergonomic user experience. A perfect choice for a vast array of creative applications.

Techninė specifikacija

Display	
Display diagonal	68.6 cm (27")
Display resolution	2560 x 1440 pixels
Native aspect ratio	16:9
Display technology	LCD
Touchscreen	Yes
HD type	Quad HD
Panel type	IPS
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	75 Hz
Display number of colours	16.7 million colours
Touchscreen technology	Projected capacitive system
Number of simultaneous touchpoints	10
Display brightness (peak)	400 cd/m²
Display brightness (typical)	400 cd/m²
Display brightness	360 cd/m²
Response time measurement type	GTG (Gray to Gray)
Viewing angle, horizontal	178°

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Viewing angle, vertical	178°
Pixel pitch	0.233 x 0.233 mm
Horizontal scan range	30 - 100 kHz
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.4 cm
Surface hardness	7H
Colour depth	8 bit
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Flicker-free technology	Yes
Low Blue Light technology	Yes
Palm rejection	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	2 W
Design	
Market positioning	Business
Product colour	Black
Front bezel colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of downstream ports	2
USB Type-A downstream ports quantity	2
USB Power Delivery (USB PD)	Yes
USB Touch port	Yes
HDMI ports quantity	1
DisplayPorts quantity	1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.


www.shopro.lt · info@shopro.lt · +370 693 39903

HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	15 - 70°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Portuguese, Russian
Number of OSD languages	10
Plug and Play	Yes
Power	
Energy efficiency class (SDR)	D
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	17.2 kWh
Power consumption (typical)	35 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	614 mm
Depth (with stand)	49 mm
Height (with stand)	364.5 mm
Weight (with stand)	5.8 kg
Packaging data	
Package width	710 mm
Package depth	130 mm
Package height	460 mm
Package weight	7.3 kg
Packaging content	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Cables included	AC, USB, HDMI
Quick start guide	Yes
Sustainability	
Sustainability certificates	ErP
Other features	
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Positional accuracy	2 mm
Brightness	360 cd/m²
Packaging content	spiral tube
Active display area (W x H)	597 x 336 mm
USB ports quantity	2
Weight	5.8 kg
Height	364.5 mm
Width	614 mm
Depth	49 mm
Compliance certificates	REACH, RoHS, WEEE
Mean time between failures (MTBF)	50000 h
Certification	CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH, UKCA
User controls	Picture adjust (brightness, contrast, i-Style Colour, adv. contrast, ECO, OverDrive, X-Res technology), colour settings (gamma, RGB range, color temp.), image settings (video mode adjust, blue light reducer, sharp and soft), OSD (horizontal pos., vertical pos., OSD time, OSD background, language, display information), extra (reset, DDC/CI, signal select, volume, mute, opening logo, led, touch switch)
Touch method	stylus, finger, glove (latex)
Control panel	Press/enter, right/volume, left/eco/exit, up/signal select, down, power
Technical details	
Native refresh rate	75 Hz
Matmenys ir svoris	
Matmenys (I × P × A)	71,00cm × 46,00cm × 13,00cm
Svoris	7,40kg

Energijos efektyvumas ir ekologinis projektavimas



Energijos efektyvumo klasė **D** A–G

- Energijos etiketė
- Gaminio informacijos lapas
- EPREL duomenų bazė

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International
Wijkermeerstraat 8, 2131 HA Hoofddorp, NL
iiyama.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt