

iiyama LH6560UHS-B2AG Signage Display Digital A-board 163.8 cm (64.5") LED Wi-Fi 500 cd/m² 4K Ultra HD Black Built-in processor Android 11 24/7

Gamintojas: **IIYAMA CONSIGNMENT** · Modelis: **LH6560UHS-B2AG** · EAN: **4948570124459** · Prekės kodas: **105394**



1 306,90 €

Kaina su PVM

Be PVM: **1 080,08 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Indoor Digital A-board Black
- ✓ Ethernet LAN Wi-Fi
- ✓ 163.8 cm (64.5") 3840 x 2160 pixels LED 500 cd/m²
- ✓ Built-in speaker(s) 20 W
- ✓ 60 Hz 6.5 ms



Aprašymas

Elevate your visual communication with the LH6560UHS-B2AG and unlock the new possibilities for your business. This 500cd/m² high brightness display is a powerful business tool that takes your marketing and communication efforts to the next level. With its Android 11 OS, iiSignage2 (Content Management Software), Signal FailOver and EShare features, this display offers a straightforward user experience, making content creation, management, and sharing a breeze. This ELED VA display consumes significantly less power compared to DLED IPS while maintaining the same level of brightness. Its versatile orientation, sleek design, and 24/7 reliability ensure it seamlessly integrates into any business environment. Whether it's used in retail, corporate, hospitality, or educational settings, the LH6560UHS -B2AG will undoubtedly captivate your audience and leave a lasting impression.

Techninė specifikacija

Specifications	
Sandėlio grupė	Displays > Lcd Large Format [+88][-90]
Display	
Display diagonal	163.8 cm (64.5")
Display technology	LED
Display resolution	3840 x 2160 pixels
Display brightness	500 cd/m²
HD type	4K Ultra HD
Touchscreen	No
Panel type	VA
Native aspect ratio	16:9
Response time	6.5 ms
Contrast ratio (typical)	5000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Pixel pitch	0.372 x 0.372 mm
Active display area (W x H)	1428.5 x 803.5 mm
Display diagonal (metric)	164 cm
Horizontal scan range	28 - 160 kHz
Native refresh rate	60 Hz
Haze rate	25%
Surface hardness	3H
Ports & interfaces	
HDMI ports quantity	3
DVI port	No
DisplayPorts quantity	0
USB port	Yes
HDMI version	2
USB ports quantity	2
USB version	2
Ethernet LAN (RJ-45) ports	1
Audio (L/R) in	1

Audio (L/R) out	1
RS-232C	Yes
Remote (IR) input	1
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital A-board
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal/Vertical
Panel mounting interface	400 x 400 mm
Bezel width (bottom)	1.6 cm
Bezel width (side)	1.4 cm
Bezel width (top)	1.4 cm
Bezel colour	Black
Anti-glare screen	Yes
Performance	
Purpose	Universal
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, Czech, Danish, German, English, Spanish, Finnish, French, Italian, Japanese, Norwegian, Dutch, Polish, Russian, Swedish
Operating hours (hours/days)	24/7
HDCP	Yes
HDCP version	1.4/2.2
Mean time between failures (MTBF)	50000 h
Power	
Power consumption (typical)	59 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
Energy efficiency class (SDR)	C
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	58.9 kWh

AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Computer system	
Computer system	No
Built-in processor	Yes
Processor manufacturer	ARM
Processor family	ARM Cortex
Processor model	A53
Processor architecture	ARM Cortex-A53
Processor cores	4
Internal memory	2 GB
On-board graphics card model	ARM Mali-G52
Internal storage capacity	16 GB
Operating system installed	Android 11
Weight & dimensions	
Display width	1459.2 mm
Display depth	38.9 mm
Display height	837.1 mm
Display weight	25.3 kg
Width	1459.2 mm
Depth	38.9 mm
Height	837.1 mm
Weight	25.3 kg
Packaging data	
Package width	1640 mm
Package depth	164 mm
Package height	990 mm
Package weight	36.4 kg
Packaging content	
Remote control included	Yes
Batteries included	Yes
Cables included	AC, HDMI, RS-232
Mounting kit	Yes
Operational conditions	

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Certificates	
Certification	CB, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH, UKCA
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Wi-Fi standards	Wi-Fi 5 (802.11ac)
Technical details	
Sustainability certificates	ErP
Compliance certificates	CB, CE, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE
Playback media	Y
User controls	picture (brightness, contrast, sharpness, black level, tint, colour, noise reduction, gamma selection, colour temperature, colour control, over scan, picture reset), screen (zoom mode, custom zoom, screen reset), Audio (balance, treble, bass, volume, audio out, maximum volume, minimum volume, mute, audio out sync, speaker setting, audio reset), configuration 1 (switch on state, panel saving, RS232-routing, boot on source, WOL, configuration 1 reset, factory reset), Configuration 2 (OSD timeout, OSD H-Position, OSD V-position, system rotation, information OSD, logo and animation logo setting, animation setting, monitor ID, monitor information, HDMI version, configuration 2 reset), advanced option (IR control, off timer, schedule, HDMI with one wire, HDMI with one wire power off, FailOver, language, OSD transparency, power saving, advanced option reset), Android settings (network & internet, apps & notifications, display, signage display, security, language & input, date & time, about device)
Other features	
Quick start guide	Yes
Power supply type	Internal
Matmenys ir svoris	
Matmenys (I × P × A)	165,00cm × 100,00cm × 17,00cm
Svoris	38,00kg