



**Power Supply BE
QUIET POWER
ZONE 2 750
Watts Peak
Power 820
Watts Efficiency
80 PLUS
PLATINIUM
MTBF 100000
hours BP006EU**

Modelis: BP006EU

Gamintojas: BE QUIET

EAN: 4260052191361

Prekės kodas: 14024

143.99€

Exceptional efficiency for Gamers

Power Zone 2 750W is a power supply with 80 PLUS® Platinum certification and semi-passive zero-RPM cooling for both efficient and quiet gaming sessions.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

PLATINUM CERTIFIED

Highly efficient operation

Power Zone 2 750W is certified with 80 PLUS Platinum and Cybenetics Platinum, resulting in an energy efficiency rating of up to 94.2%. This results in lower power consumption, overall cooler and quieter operation, and many other benefits for your high-end system.

SEMI-PASSIVE ZERO-RPM COOLING

Enjoy the silence

A large Pure Wings 3 140mm fan is keeping Power Zone 2 750W cool. While under low load, the fan turns off completely until its services are needed again for more demanding operations. This post-ventilation requires a short cooldown period of 2-5 minutes to avoid frequent and annoying starts and stops of the fan. Combined with the large fan for active cooling, this power supply is exceptionally silent in all load scenarios.

PURE WINGS 3 FAN

Specially designed for Power Zone 2

No Power Supply is like the other. Hence, we have altered aspects of our renowned Pure Wings 3 140mm fan to make it the perfect match for Power Zone 2 750W. The fan offers outstanding reliability and makes for a long-lasting companion. Due to its large diameter, the fan cools the interior of the PSU efficiently and quietly.

FUTURE-PROOF YOUR SYSTEM

With 90° angled 12V-2x6 connector in scope of delivery

Power Zone 2 750W is an ATX 3.1 PSU and comes with both native integration of the 12V-2x6 connector for next-generation PCIe 5.1 graphics cards, and 3 PCIe 6+2-pin connectors for support of current-gen GPUs. A 90° angled 12V-2x6 connector in the scope of delivery leaves no doubt that this PSU is here to stay. All of this makes Power Zone 2 750W extremely versatile and the perfect choice for powerful systems of today and the ones to come.

THE NEW STANDARD OF POWER

For massive transient loads

Power Zone 2 offers 750W of continuous power with one massive 12V rail. Even if the graphics card demands excessive power for a short time: Power Zone 2 750W handles power excursions up to

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

double its rated power with ease. This ensures reliable operation with the next generation of processors and graphics cards.

HIGH-CLASS TECHNOLOGIES

All packed in a stunning design

With its LLC topology, the Power Zone 2 750W offers best-in-class voltage regulation and efficiency. This makes it perfect for building very quiet systems or upgrading gaming and media creation PCs. The inner values are what everyone cares about most in a power supply but looks cannot be completely ignored. That is why the Power Zone 2 750W has a distinctive look with a newly designed mesh front. In addition, all cable designations are printed directly on the PSU's case for a long-lasting impression and an unparalleled look and feel.

- 80 PLUS® Platinum and Cybenetics Platinum efficiency rating (up to 94.2%)
- Semi-passive zero-RPM cooling
- Fan runs on for 2-5 minutes to avoid frequent starting noise
- Pure Wings 3 140mm fan for quiet and efficient cooling
- 90° angled 12V-2x6 connector and PCIe 5.1/ATX 3.1 compatibility
- Advanced voltage regulation and stability thanks to LLC technology
- Unique look with an unmistakable mesh design
- One massive high-performance 12V-rail

Summary: be quiet! POWER ZONE 2 750W. Total power: 750 W, AC input voltage: 100 - 240 V, Peak power: 820 W. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 550,700,850,1000 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Platinum. Product colour: Black, Cooling type: Active, Fan diameter: 14 cm. Compliance certificates: BSMI, CB, CCC, CE, Federal Communications Commission (FCC), RCM, RoHS, TÜV mark, UKCA, WEEE | Vendor Homepage:

<https://www.bequiet.com/en/powersupply/5585> | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Combined power (+12V): 750 | Combined power (+3.3V): 120 | Combined power (+5V): 120 | Combined power (+5Vsb): 15 | Combined power (-12V): 3.6 | Efficiency: 92.5 | Hold time: 24.5 | Max output current (+12V): 62.5 | Max output current (+3.3V): 20 | Max output current (+5V): 20 | Max output current (+5Vsb): 3 | Max output current (-12V): 0.3 | Maximum input current (@110V): 10 | Maximum input current (@220V): 5 | Number of +12V rail(s): 1 | Peak power: 820 | Power factor: 0.98 | Power protection features: Over current/Over power/Over voltage/Overheating/Short

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

circuit/Surge & inrush/Under voltage | Total power: 750 | Cabling type: Fully-Modular | CPU P4 connector (4-pin): 1 | CPU power cable length: 700 | CPU power connector (4+4 pin): Yes | EPS power connector (8-pin): Yes | Motherboard power cable length: 600 | Motherboard power connector: 20+4 pin ATX | Number of SATA power connectors: 6 | PCI Express power cable length: 600 | PCI Express power connectors (16-pin): 1 | PCI Express power connectors (6+2 pin): 3 | Peripheral (Molex) power cable length: 850 | Peripheral (Molex) power connectors (4-pin): 1 | SATA power cable length: 1000/550/700/850 | 80 PLUS certification: 80 PLUS Platinum | ATX version: 3.1 | Bearing technology: Rifle | EPS version: 2.92 | Mean time between failures (MTBF): 100000 | Noise level: 15.8 | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 140 | Number of fans: 1 | On/off switch: Yes | Product colour: Black | Operating relative humidity (H-H): 0 - 85 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 0 - 95 | Storage temperature (T-T): -40 - 70 | Compliance certificates: BSMI/CB/CCC/CE/Federal Communications Commission (FCC)/RCM/RoHS/TÜV mark/UKCA/WEEE | Waste Electrical and Electronic Equipment (WEEE) compliance: Yes | Depth: 160 | Height: 86 | Width: 150 | Manual: Yes | Manual languages: English/French/German/Polish/Russian/Spanish/Ukrainian | Package depth: 328 | Package height: 102 | Package type: Box | Package weight: 3210 | Package width: 248 | Sustainability certificates: ENERGY STAR/ErP/Triman | Products per shipping (inner) case: 6 | Shipping (inner) case gross weight: 19260 | Shipping (inner) case height: 346 | Shipping (inner) case length: 651 | Shipping (inner) case width: 282 | Cable ties included: Yes | Screws included: Yes | Model name: POWER ZONE 2 | Units per Pallet: 0 | Units per Shipping Box: 6 | Unit Calculated Volume: 0.01201 | Unit Calculated Weight: 3.51

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903