



**Mainboard MSI
Intel B760
Express
LGA1700
Memory DDR5
Memory slots 4
5xPCI-Express
5.0 16x 2xM.2
1xHDMI
1xDisplayPort
2xUSB 2.0
2xUSB 3.2
1xUSB-C
1xOptical S/PDIF
1xRJ45 5xAudio
port PROB760-
PII**

Modelis: PROB760-PII

Gamintojas: MSI

EAN: 4711377193887

Prekės kodas: 14040

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

134.99€

Extended Heatsink

Extended Heatsink enlarges the surface of heat dissipation and maintain the performance at heavy loads.

M.2 Shield Frozr

Strengthened M.2 thermal solution helps keep M.2 SSD safe and ensures incredible performance.

Heavy Plated VRM Heatsink

The VRM heatsink covers the upper MOS and helps dissipate the heat.

7W/mK Thermal Pad & Additional Choke Pad

High-quality 7W/mK MOSFET thermal pads and additional choke thermal pads ensure stable performance when all cores are runnging at high speed.

Chipset Heatsink

The chipset heatsink is designed to reduce dust and noise and capable of maintaining high efficiency of heat dissipation.

OPTIMIZED FOR WATER COOLING

Designed to support the most popular All-In-One & customized water cooling solutions on the market. A dedicated water pump PIN header supports up to 3 amp, giving you full control of the water pump speed. A clearly marked 'keep-out-zone' allows for easy and safe installation and a perfect fit.

LIGHTNING GEN 4 PCI-E

Doubling over the previous generation, the bandwidth of a x16 interface can reach 64GB/s.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

REINFORCED,

HEAVY SOLDERED CONNECTIONS

Secure to the motherboard with extra solder points and support the weight of heavy graphics cards.

FAST AND FUTURE-READY STORAGE

MSI PRO series motherboards support all the latest storage standards, which allows users to connect any ultra-fast storage device. Start games faster, load levels faster and have a real advantage over your enemies.

THE ISOLATED ANALOGY STRUCTURE FOR AUDIO CONNECTORS

To provide clear voice, MSI develops a unique structure – Isolated Analogy Structure. The external metal framework of the audio connectors is separated from the internal layout, which ensures the sound quality crisp.

- Support Intel® Core™ 14th/ 13th/ 12th Gen Processors, Intel® Pentium® Gold and Celeron® Processors for LGA 1700 socket
- Supports DDR5 Memory, Dual Channel DDR5 7000+MHz (OC)
- Enhanced Power Design: 12+1 Duet Rail Power System with P-PAK, 8-pin + 4-pin CPU power connectors, Core Boost, Memory Boost
- Premium Thermal Solution: Extended Heatsink, MOSFET thermal pads rated for 7W/mK, additional choke thermal pads and M.2 Shield Frozr are built for high performance system and non-stop gaming experience
- High Quality PCB: 6-layer PCB made by 2oz thickened copper and server grade level material
- Lightning Fast Game experience: PCIe 4.0 slot, Lightning Gen 4 x4 M.2
- Intel Turbo USB 10Gbps: Powered by Intel USB 10Gbps controller, Turbo USB ensures an uninterrupted connection with more stability and fastest USB speeds
- 2.5G LAN: Upgraded network solution for professional and multimedia use. Delivers a secure, stable and fast network connection
- AUDIO BOOST: Reward your ears with studio grade sound quality for the most immersive gaming experience

Summary: MSI PRO B760-P II. Processor manufacturer: Intel, Processor socket: LGA 1700, Compatible processor series: Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Pentium® Gold. Supported memory types: DDR5-SDRAM, Maximum internal memory: 256 GB,

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Memory slots type: DIMM. Supported storage drive interfaces: PCI Express 4.0, SATA III, RAID levels: 0, 1, 5, 10. Ethernet interface type: 2.5 Gigabit Ethernet, LAN controller: Realtek RTL8125-BG. Component for: PC, Motherboard form factor: ATX, Motherboard chipset family: Intel | Vendor Homepage: <https://www.msi.com/Motherboard/PRO-B760-P-II/Overview> | Audio chip: Realtek ALC897 | Audio output channels: 7.1 | Component for: PC | Motherboard chipset: Intel B760 | Motherboard chipset family: Intel | Motherboard form factor: ATX | Windows operating systems supported: Windows 10 x64/Windows 11 x64 | Compatible processor series: Intel® Celeron®/Intel® Core™ i3/Intel® Core™ i5/Intel® Core™ i7/Intel® Pentium® Gold | Maximum internal memory supported by processor: 256 | Processor manufacturer: Intel | Processor socket: LGA 1700 | ECC compatibility: Non-ECC | Maximum internal memory: 256 | Memory channels: Dual-channel | Memory slots type: DIMM | Number of memory slots: 4 | Supported memory clock speed (max): 7000 | Supported memory clock speeds: 4800/5000/5200/5400/5600/5800/6000/6200/6400/6600/6800/7000 | Supported memory types: DDR5-SDRAM | Unbuffered memory: Yes | Number of HDDs supported: 4 | Number of storage drives supported: 6 | RAID levels: 0/1/10/5 | RAID support: Yes | Supported storage drive interfaces: PCI Express 4.0,SATA III | 12V power connector: Yes | ATX Power connector (24-pin): Yes | Chassis intrusion connector: Yes | CPU fan connector: Yes | Front panel audio connector: Yes | Front panel connector: Yes | Number of SATA III connectors: 4 | Power fan connector: Yes | S/PDIF out connector: Yes | USB 2.0 connectors: 4 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 4 | USB 3.2 Gen 2 (3.1 Gen 2) connectors: 1 | DisplayPort version: 1.4 | DisplayPorts quantity: 1 | Ethernet LAN (RJ-45) ports: 1 | HDMI ports quantity: 1 | HDMI version: 2.1 | USB 2.0 ports quantity: 4 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity: 1 | Ethernet interface type: 2.5 Gigabit Ethernet | Ethernet LAN: Yes | LAN controller: Realtek RTL8125-BG | Wi-Fi: No | Number of M.2 (M) slots: 2 | PCI Express x1 (Gen 3.x) slots: 1 | PCI Express x1 (Gen 4.x) slots: 2 | PCI Express x16 (Gen 4.x) slots: 1 | PCI Express x4 (Gen 4.x) slots: 1 | ACPI version: 6.4 | BIOS memory size: 256 | BIOS type: UEFI AMI | Clear CMOS button: Yes | Clear CMOS jumper: Yes | System Management BIOS (SMBIOS) version: 3.5 | Depth: 304.8 | Width: 243.84 | Cables included: SATA | Drivers included: Yes | Model: PRO B760-P II | Units per Shipping Box: 10 | Unit Calculated Volume: 0.007252 | Unit Calculated Weight: 1.51

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903