



# Power Supply MSI MAG A750GL PCIE5 II 750 Watts Efficiency 80 PLUS GOLD PFC Active MAGA750GLPCIE5II

Modelis: MAG A750GL PCIE5 II

Gamintojas: MSI

EAN: 4711377246705

Prekės kodas: 14205

## 108.98€

### ATX 3.1 Ready

It has an output port that is compliant with PCIe 5.1 and Intel PSDG(Power Supply Design Guide) ATX 3.1, also the power supply can hold up to 2x total power excursion and 3x GPU power excursion.

### ENERGY EFFICIENCY CERTIFICATION

The efficiency of your power supply directly influences your system's performance and your power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

consumption. The 80 PLUS Gold certification promises lower energy consumption and higher efficiency.

### **COMPACT SIZING**

Smaller than typical PSUs on the market, this power supply unit that can save space and make it easier to organize cables in the computer case by freeing up more room inside.

### **ONLY WHAT YOU NEED**

The connectors that required by the build need to be used, significantly reducing cable clutter and simplifying the system's overall build. Additionally, the included cable pack provides a storage solution for any unused cables.

### **ALL THE MORE ORGANIZED**

Organizing cables is often the most bothersome part of building a PC. The flat cables make cable management easier and less of a headache! Thanks to the flat cables, the entire system can be more organized and has more room for unobstructed airflow.

### **FLUID DYNAMIC BEARING**

The power supply's fan sports a fluid dynamic bearing that perfectly balances cooling performance and noise level.

### **DC to DC & Full bridge**

DC to DC and Full bridge be combined to achieve higher conversion efficiency, stable output voltage, and quick voltage adjustment for different usage scenarios, thus providing a stable power supply design.

### **THE POWER YOU HAVE**

The single rail supply of power can properly deliver the power you need. For high-performance graphics cards and CPUs, this power supply's CPU & PCIe connectors are more than plenty.

### **PROTECTION MECHANISMS**

To make sure the entire system can operate safely and stably at all times, the power supply comes with a number of protection mechanisms to give you the best peace of mind.

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

- ATX 3.1 ready, native PCIe 5.1 connector
- Supports NVIDIA® GeForce RTX™ 40 Series graphics cards
- Full modular design, Flat cables
- 80 Plus Gold certified for high efficiency with Active PFC design
- Industrial level protection with OVP, OCP, OPP, OTP, SCP, UVP
- 120 mm Fluid Dynamic Bearing Fan
- LLC Full Bridge Topology with DC-DC module design

Summary: MSI MAG A750GL PCIE5 II. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 150,500 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 140 mm, Height: 86 mm | Vendor Homepage: <https://www.msi.com/Power-Supply/MAG-A750GL-PCIE5-II/Overview> | AC input frequency: 47 - 63 | AC input voltage: 100 - 240 | Combined power (+12V): 744 | Combined power (+3.3V): 110 | Combined power (+5V): 110 | Combined power (+5Vsb): 12.5 | Combined power (-12V): 3.6 | Efficiency: 90 | Max output current (+12V): 62 | Max output current (+3.3V): 20 | Max output current (+5V): 20 | Max output current (+5Vsb): 2.5 | Max output current (-12V): 0.3 | Number of +12V rail(s): 1 | Power Factor Correction (PFC) type: Active | Power protection features: Over current/Over power/Over voltage/Overheating/Short circuit/Under voltage | Total power: 750 | Cabling type: Fully-Modular | CPU power connector (4+4 pin): Yes | EPS power connector (4+4 pin): Yes | Motherboard power cable length: 600 | Motherboard power connector: 20+4 pin ATX | Number of SATA power connectors: 8 | PCI Express power connectors (16-pin): 1 | PCI Express power connectors (6+2 pin): 3 | Peripheral (Molex) power cable length: 500 | Peripheral (Molex) power connectors (4-pin): 4 | SATA power cable length: 150/500 | 80 PLUS certification: 80 PLUS Gold | ATX version: 3.1 | Bearing technology: FDB | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | Number of fans: 1 | On/off switch: Yes | Product colour: Black | Depth: 140 | Height: 86 | Width: 150 | Package type: Box | Model name: MAG A750GL PCIE5 II | Units per Shipping Box: 6 | Unit Calculated Volume: 0.01012 | Unit Calculated Weight: 1.92

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903