



Power Supply
GIGABYTE 550
Watts Efficiency
80 PLUS SILVER
PFC Active MTBF
100000 hours
GP-P550SS

Modelis: GP-P550SS

Gamintojas: GIGABYTE

EAN: 4719331554187

Prekės kodas: 14644

46.98€

Ensure reliable and efficient power delivery with GIGABYTE power supplies. Designed for peak performance and durability, our PSUs offer stable and consistent energy to power your high-performance systems. With advanced protections and high-quality components, GIGABYTE power supplies provide the confidence you need for seamless, uninterrupted computing experiences.

- 80 PLUS Silver certified (230V EU)
- Support Intel ATX 3.0 standard (compatible with ATX 3.1)
- 120mm Fluid Dynamic Bearing (FDB) Fan

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Flat cable design
- Powerful single +12V rail
- OVP/OPP/SCP/UVP/OCP/OTP protection

Summary: GIGABYTE P550SS Power Supply - PCIe 5.0, 80 PLUS Silver, 120mm Fan, ATX 3.0 compatible, EU Plug. Total power: 550 W, AC input voltage: 155-240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Silver. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 140 mm, Depth: 150 mm, Height: 86 mm | Vendor Homepage: <https://www.gigabyte.com/> | AC input frequency: 50/60 | AC input voltage: 155-240 | Combined power (+12V): 549.6 | Combined power (+3.3V): 100 | Combined power (+5V): 100 | Combined power (+5Vsb): 15 | Combined power (-12V): 3.6 | Efficiency: 90 | Hold time: 16 | Input current: 6.3 | Max output current (+12V): 45.8 | Max output current (+3.3V): 20 | Max output current (+5V): 20 | Max output current (+5Vsb): 3 | Max output current (-12V): 0.3 | Power Factor Correction (PFC) type: Active | Power Good signal delay range: 100 - 150 | Power protection features: Over current/Over power/Over voltage/Overheating/Short circuit/Under voltage | Total power: 550 | ATX power connector (20+4 pin): Yes | Cabling type: Non-Modular | CPU power connector (4+4 pin): Yes | Floppy disk drive connector: Yes | Floppy drive power connector: 2 | Motherboard power cable length: 600 | Motherboard power connector: 20+4 pin ATX | Number of SATA power connectors: 5 | PCI Express connector: Yes | PCI Express power connectors (6+2 pin): 2 | Peripheral (Molex) power connectors (4-pin): 4 | 80 PLUS certification: 80 PLUS Silver | ATX version: 3.1 | Bearing technology: Ball bearing | Mean time between failures (MTBF): 100000 | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | Fan location: Top | Number of fans: 1 | On/off switch: Yes | Product colour: Black | Depth: 150 | Height: 86 | Weight: 1860 | Width: 140 | Package depth: 206 | Package height: 117 | Package type: Box | Package weight: 2316 | Package width: 254 | Warranty period: 3 | Units per Shipping Box: 5 | Unit Calculated Volume: 0.007577 | Unit Calculated Weight: 2.2

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903