

Epson C31C412682 label printer Direct thermal 203 x 203 DPI 90 mm/sec Wired

Gamintojas: **EPSON** · Modelis: **C31C412682** · EAN: **8715946680163** · Prekės kodas: **235019**



437,90 €

Kaina su PVM

Be PVM: **361,90 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Built-in taken sensor: Automatic next label printing
- ✓ Media flexibility: 1.5-inch, 2-inch or 3-inch media widths
- ✓ Speed: Print speeds of up to 170mm/sec
- ✓ Paper-saving: Improved paper reduction function
- ✓ Easy installation: Three mounting positions

Aprašymas

Fast liner-free label printing for hospitality and retail

This thermal label printer has been developed for fast-food retail chains, restaurants, food delivery services, and logistics. The TM-L90LF liner-free thermal label printer benefits users by providing cost-effective, fast and reliable technology. It's also compatible with liner-free adhesive media.

Cost efficient

As the TM-L90LF prints both liner-free labels and receipts in order to improve the user's operational efficiency and total cost of ownership (TCO). As the printer works with adhesive-backed media, users are able to accurately label food and drink orders - thereby increasing customer satisfaction and user accuracy.

Order processing speed

With print speeds of up to 170mm/sec, the potential benefits to the user are clear: fast order (and checkout) processing, faster drive-through services and improved customer satisfaction.

Built-in taken sensor

The next label prints automatically as the printed one is taken.

Flexible installation

Users can position the printer in the most convenient spot, thanks to a choice of vertical, horizontal or wall-mounted (using optional bracket) installation.

Saves paper

The TM-L90LF features improved paper reduction functionality that includes back feed capability, line feed adjustment and a smaller sized font. It can be set up to cut through adhesive areas, which saves paper. To further reduce paper consumption, the automatic top margin reduction function prints the top of the next receipt before cutting the current one when printing continues after auto cutting. It supports 1.5-inch, 2-inch or 3-inch media widths.

Techninė specifikacija

Specifications	
Sandėlio grupė	POS > Receipt Printer [+0][-0]
Printing	
Print technology	Direct thermal
Maximum resolution	203 x 203 DPI
Print speed	90 mm/sec
Printing characters	Text, Graphic
Paper handling	
Half-cutter	Yes
Maximum roll diameter	10.2 cm
Supported paper width	80 mm
Autocutter durability	1 million cuts
Ports & interfaces	
Connectivity technology	Wired
USB port	Yes
Performance	
Mean time between failures (MTBF)	360000 h
Mean cycles between failures (MCBF)	35000000
Cutter	Yes
Certification	VCCI-Class A, CE
Design	
Product colour	Grey
Power	
AC input voltage	24 V
Power consumption	1800 mA

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	5 - 45 °C
Storage temperature (T-T)	-10 - 50 °C

Weight & dimensions

Width	140 mm
Depth	148 mm
Height	203 mm
Weight	1.9 kg

Packaging data

Quantity per pack	1 pc(s)
Package width	195 mm
Package depth	255 mm
Package height	240 mm
Package weight	2.76 kg

Packaging content

Manual	Yes
--------	-----

Logistics data

Products per pallet (UK)	168 pc(s)
Pallet weight (UK)	0 g
Harmonized System (HS) code	84433210
Pallet gross weight	0 g
Products per pallet	112 pc(s)

Other features

Safety	TÜV
Buffer size	4 KB
Character sets	ANK
Country of origin	China

Matmenys ir svoris

Matmenys (l × p × A)	25,00cm × 24,00cm × 20,00cm
Svoris	2,62kg