

Brother TD-4420TN label printer Direct thermal / Thermal transfer 203 x 203 DPI 152 mm/sec Wired Ethernet LAN

 Gamintojas: **BROTHER** · Modelis: **TD4420TNZ1** · EAN: **4977766798556** · Prekės kodas: **237204**


424,90 €

Kaina su PVM

 Be PVM: **351,16 €**

Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 203dpi printing for crisp text and barcodes
- ✓ Up to 152mm/second (6 ips) print speed
- ✓ USB, wired ethernet and serial ports as standard
- ✓ Supports popular printer languages including ZPL/ZPL2, EPL and DPL
- ✓ Free label design software available via download



Aprašymas

The TD-4420TN uses innovative thermal transfer technology to create durable labels that stand up to the toughest of tests. SAP and BarTender compatibility* ensure it fits perfectly into your workflows, and there's the added bonus of customisation options like label peelers, cutters and external roll holders. Plus, you can also use the in-built direct thermal technology to print high-volume, low-cost labels for everyday usage.

Techninė specifikacija

Specifications

Sandėlio grupė

POS > Label Printers [+0][I-0]

Printing

Print technology	Direct thermal / Thermal transfer
Colour	No
Maximum resolution	203 x 203 DPI
Print speed	152 mm/sec
Print speed	6 lpm
Maximum print height	10.8 cm
Maximum print length	25.4 m
Paper handling	
Maximum label width	11.2 cm
Maximum roll diameter	12.7 cm
Core diameter	2.54 cm
Ports & interfaces	
Connectivity technology	Wired
Ethernet LAN	Yes
Wi-Fi	No
USB port	Yes
Bluetooth	No
USB 2.0 ports quantity	2
RS-232 ports	1
Performance	
Page description languages	DPL, EPL, ZPL, ZPL II
Internal memory	64 MB
Flash memory	128 MB
Built-in barcodes	GS1 DataMatrix, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, EAN128, EAN13, EAN8, GS1 DataBar, ITF-14, Interleaved 2/5, LOGMARS, MSI, MaxiCode, MicroPDF417, PDF417, PLESSEY, POSTNET, QR Code, UPC-A, UPC-E
Number of fonts	8
Design	
Product colour	Black
Display	No
Built-in display	No
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz

AC adapter output current	2 A
---------------------------	-----

System requirements

Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave
Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Linux operating systems supported	Yes

Operational conditions

Operating relative humidity (H-H)	5 - 40%
Storage relative humidity (H-H)	25 - 85%
Operating temperature (T-T)	10 - 90 °C
Storage temperature (T-T)	-40 - 60 °C

Weight & dimensions

Width	275 mm
Depth	405 mm
Height	245 mm
Weight	3.15 kg

Packaging data

Quantity per pack	1 pc(s)
Package weight	3.93 kg

Packaging content

Cables included	AC, USB
Quick start guide	Yes
Warranty card	Yes
AC adapter included	Yes
Software development kit (SDK)	Yes
Starter roll included	Yes

Logistics data

Harmonized System (HS) code	84433210
Pallet gross height	16.2 cm
Pallet gross weight	211.9 kg
Master (outer) cases per pallet	48 pc(s)
Master (outer) cases per pallet layer	8 pc(s)
Layers per pallet	6 pc(s)

Products per pallet	48 pc(s)
---------------------	----------

Technical details

Pallet type	800 x 1200 mm
-------------	---------------

Other features

LED indicators	Yes
----------------	-----

Country of origin	China
-------------------	-------

Languages support	Danish, German, Dutch, English, Spanish, Finnish, French, Italian, Norwegian, Portuguese, Swedish
-------------------	---

Number of languages	11
---------------------	----

Spare part retention	5 year(s)
----------------------	-----------

Matmenys ir svoris

Matmenys (I x P x A)	41,00cm x 28,00cm x 25,00cm
----------------------	-----------------------------

Svoris	4,02kg
--------	--------