NETGEAR GS728TPP Valdomas L2/L3/L4 Gigabit Ethernet (10/100/1000) Maitinimas per Eternetą (PoE) Pilka

Gamintojas: **NETGEAR** · Modelis: **GS728TPP-300EUS** · EAN: **606449162356** · Prekės kodas: **242513**



477,90 €

Kaina su PVM

Be PVM: **394,96 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Valdomas L2/L3/L4
- ✓ Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 24
- ✓ Adreso lentelės dydis: 16000 įrašai Perjungimo pajėgumas: 56 Gbit/s
- ✓ Prieigos kontrolės sąrašas (ACL)
- ✓ Stovo montavimas
- ✓ AC Maitinimas per Eternetą (PoE)







Aprašymas

All ports PoE+ with up to 760W PoE budget and Remote/Cloud Management option - Select your new network engine!

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

As a leading provider of network equipment for SMBs, NETGEAR® understands the importance of providing a great choice of PoE port counts and power budgets that can adapt to your business' needs, whether in the hospitality, catering, education or retail domains. The GS728TP, GS728TPP, GS752TP and GS752TPP Gigabit Ethernet Switches with PoE+ and 4 SFP Ports join the NETGEAR standalone Smart switches family, adding full 24 and 48 port PoE+ support for deployment of modern high-power PoE devices. Cautious spender organizations can now deploy denser PoE+ devices connected to a cost-effective switch, with a reasonable PoE power budget of 190W over 24-port, or 380W over 48-port. Organizations who buy infrastructure for the long term and want future proofing for the unforeseeable can now select a switch with a PoE power budget of 380W over 24-port, or 760W over 48-port providing more headroom. Temperature- and load-based fan-speed control combines accurate monitoring with minimized system acoustic noise: the GS728TP supports quiet rack mounting operation with a maximum of 26.80dBA even at full PoE power with traffic on all ports and 25°C (77°F) ambient. Following the same measurements, the GS728TPP is rated at 33.30dBA, the GS752TP at 36.60dB and the GS752TPP at 39.30dBA.

Highlights

The NETGEAR PoE+ Gigabit Smart switches with Remote/Cloud Management provides a great value, with configurable L2 network features like VLANs and PoE operation scheduling, allowing SMB customers to deploy PoEbased VoIP phones, IP cameras, videoover-IP endpoints and Wireless access points simply and securely. Advanced features such as IPv4/IPv6 Layer 3 static routing, LACP link aggregation, DiffServ QoS, Private VLANs, Multicast VLAN Registration and Spanning Tree will satisfy even the most advanced small business networks.

Key features include:
- Quiet rack mounting operation with 26.80 to 39.30dBA at 25°C (77°F) ambient
- Layer 3 static routing with 32 routes (IPv4 and IPv6) for interVLAN local routing
- Advanced VLAN and Private VLAN support for better network segmentation
- L2/L3/L4 access control lists (ACLs) for granular network access control including 802.1x port authentication
- Advanced per port PoE controls for remote power management of PoE connected devices including operation scheduling (e.g. Wireless APs, IP security cameras, LED lighting, secure access door locks, IoT devices…)
- Advanced QoS (Quality of Service) for traffic prioritization including port-based, 802.1p and L2/L3/L4 DSCP-based
- Auto "denial-of-service" (DoS) prevention
- IGMP Snooping and Querier for multicast optimization
- Multicast VLAN Registration (MVR) for larger L2 multicast networks and AV over IP deployment
- Dynamic ARP for increased security targeting a class of Man in the Middle attack
- Rate limiting and priority queuing for better bandwidth allocation
- Port mirroring for network monitoring
- Energy Efficient Ethernet (IEEE 802.3az) for maximum power savings
- Cable test to troubleshoot connection issues
- SNMP v1, v2c, v3 and RMON remote monitoring

Build a future-proof network with NETGEAR:
- Solid performance with non-blocking architecture, 16K MAC addresses, 256 VLANs, 100 shared (ingress) ACLs and 512 Multicast groups
- Comprehensive IPv6 supporting management, QoS, ACL and routing, ensuring investment protection and a smooth migration to IPv6-based network
- PoE+ support on all models and on all ports
- 4 Dedicated SFPs, not only providing fiber uplinks, but also uplink redundancy and failover, improving reliability and availability for the network

Fully-integrated cloud-manageable devices

- Remote/Cloud Management capability with NETGEAR Insight. Instantly activate NETGEAR Insight Cloud management from the web GUI, for simpler configuration and deployment from anywhere using the NETGEAR Insight app on mobile devices or the Insight Cloud portal through a web browser

Smart IT, not Big IT
- Easy-to-use Web browser-based management GUI
- Network Management System (NMS300), allowing all NETGEAR business products to be deployed and managed through this single interface
- Dual firmware images improve reliability and uptime to your network
- Text-based Lite Command-line Interface (CLI)

NETGEAR quality and reliability

- Worry-free NETGEAR Limited Lifetime Warranty*, online technical chat support and Next Business Day (NBD) replacement
- 90-days Free 24x7 Advanced Technical Phone Support**

Techninė specifikacija

Valdymo funkcijos	
Perjungimo tipas	Valdomas
Perjungimo sluoksnis	L2/L3/L4
ARP kontrolė	Taip
Ryšys	
Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius	24
Pagrindinių perjungimo RJ-45 eterneto prievadų tipas	Gigabit Ethernet (10/100/1000)
Įdiegtų SFP modulių kiekis	4
USB „Type-A“ lizdų kiekis	1
Tinklas	
Tinklo standartai	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x
IPv4 maršrutai	32
IPv6 maršrutai	32
VLAN palaikymas	Taip
VLANs skaičius	256
Duomenų perdavimas	
Adreso lentelės dydis	16000 įrašai
Perjungimo pajėgumas	56 Gbit/s
Vėlavimas (10–100 Mb/s)	8,871 µs
Vėlavimas (1 Gb/s)	4,701 µs
Paketo buferio atmintis	1,5 MB
Saugumas	
DHCP funkcijos	DHCP snooping, DHCPv6 client
Prieigos kontrolės sąrašas (ACL)	Taip
Prieigos kontrolės sąrašo (ACL) IPv4 įrašai	100
Transliavimo grupiniu adresu ypatybės	
Multicast palaikymas	Taip
Išfiltruotų daugiaadresinio perdavimo grupių skaičius	512
Konstrukcija	

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Stovo montavimas	Taip
Produkto spalva	Pilka
Rezervinių ventiliatorių palaikymas	Taip
Ventiliatorių skaičius	2 ventiliatorius(iai / ių)

Veikimo charakteristikos

Integruotas procesorius	Taip
Procesoriaus gamintojas	ARM
Procesoriaus modelis	ARM Cortex-A55
Procesoriaus dažnis	800 MHz
Vidinė atmintis	512 MB
Flash atmintis	64 MB
Garso lygis	33,3 dB
Vidutinis laikas tarp trikčių (MTBF)	1252990 h

Energijos valdymas

Maitinimo šaltinis	AC
Energijos suvartojimas	26 W
Galios suvartojimas (maks.)	427 W

„Power over Ethernet“ (PoE)

Maitinimas per Eternetą (PoE)	Taip
Maitinimo per Eternetą plius (PoE+) prievadų skaičius	24
Maitinimo per Eternetą (PoE) galia prievadui	380 W

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 50 °C
Sandėliavimo temperatūros norma (T-T)	-20 - 70 °C
Darbo santykinės drėgmės diapazonas	0 - 90%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%

Svoris ir matmenys

Plotis	440 mm
Ilgis	257 mm
Aukštis	432 mm
Svoris	4,11 kg

Sertifikatai

Sertifikavimas	CE, FCC Class A, RCM, ICES Class A, VCCI, KC, BSMI, UKCA

Matmenys ir svoris

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Matmenys (I × P × A)	52,00cm × 35,00cm × 11,00cm
Svoris	5,01kg

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

NETGEAR

ATSAKINGAS ASMUO ES

NETGEAR Deutschland GmbH
Konrad-Zuse-Platz 1, 81829 München, DE
netgear.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt