

Allied Telesis AT-GS910/8E-50 Unmanaged Gigabit Ethernet (10/100/1000) Grey

Gamintojas: **ALLIED TELESIS** · Modelis: **AT-GS910/8E-50** · EAN: **767035207445** · Prekės kodas: **321928**



123,90 €

Kaina su PVM

Be PVM: **102,40 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Unmanaged
- ✓ Basic switching RJ-45 Ethernet ports quantity: 8
- ✓ MAC address table: 4000 entries Switching capacity: 16 Gbit/s

Aprašymas

The Allied Telesis GS910 Series offers unmanaged Gigabit switching solutions for the desktop, and small networks. The series has internal and external power supply versions, and also features network loop guard technology, which automatically detects any unexpected network loops, and prevents network devices from broadcast packet storms.

With minimal to no set-up, GS910 Series switches provide simple and seamless connectivity to existing network infrastructure. Each unmanaged switch is backed with a lifetime limited warranty.

Techninė specifikacija

Management features

Switch type Unmanaged

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0

Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	8
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support	No
Flow control support	Yes
Broadcast storm control	Yes
Cable length detection	Yes
Data transmission	
MAC address table	4000 entries
Switching capacity	16 Gbit/s
Throughput	11.9 Mpps
Jumbo frames support	Yes
Packet forwarding rate (1 Gbps)	1488000 pps
Packet forwarding rate (100 Mbps)	148800 pps
Packet forwarding rate (10 Mbps)	14880 pps
Security	
Loop protection	Yes
BPDU filtering/protection	Yes
Design	
Rack mounting	No
Product colour	Grey
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	5 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Weight & dimensions	
Width	210 mm
Depth	121 mm

Height	38 mm
Weight	720 g
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Matmenys (l × p × A)	29,00cm × 26,00cm × 9,00cm
Svoris	1,20kg