



Switch TP-LINK Omada SG2428P Type L2+ 384 Watts ES228GMP



Modelis: ES228GMP

Gamintojas: TP-LINK

EAN: 1210002600989

Prekės kodas: 322584

327.99€

Omada Cloud Essentials — A Free and Easy Cloud-Based Network Management

Omada Cloud Essentials is a free, easy-to-use version of the Omada Cloud-based Controller. It provides cloud-based centralized management and monitoring for the Omada networking system, covering access points, switches, and gateways, ideal for surveillance networks and small businesses.

- 26× 10/100/1000Mbps RJ45 ports (24× 802.3af/at-compliant PoE+)
- 2× Gigabit SFP port
- 384W Power Budget, with up to 30W for each PoE port
- Easy to Use: Supports plug-and-play for instant connectivity and simple configuration for additional features

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Centralized Cloud Management via the web or the Omada app
- Up to 250m PoE, QoS Δ , PoE Auto Recovery, and Port Isolation for reliable surveillance networking
- Automatic Loop Prevention, VLAN, and IGMP Snooping
- Durable metal casing and rack-mountable design

Summary: TP-Link Omada ES228GMP. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 26. MAC address table: 8000 entries, Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i,.... Power over Ethernet (PoE). Rack mounting | Vendor Homepage:

<https://www.omadanetworks.com/en/business-networking/omada-switch-agile/es228gmp/> | Cloud-managed: Yes | Quality of Service (QoS) support: Yes | Switch layer: L2 | Switch type: Managed | Unified static configuration: Yes | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 26 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 26 | SFP module slots quantity: 2 | 10G support: No | Auto MDI/MDI-X: Yes | Broadcast storm control: Yes | Copper ethernet cabling technology: 1000BASE-T/1000BASE-X/100BASE-X/10BASE-T | Ethernet LAN data rates: 10,100,1000 | Fast leave: Yes | Flow control support: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1ab/IEEE 802.1p/IEEE 802.1Q/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x/IEEE 802.3z | Number of VLANs: 32 | Port mirroring: Yes | Virtual LAN features: MTU VLAN/Port-based VLAN/Tagged VLAN | VLAN support: Yes | Forwarding rate: 41.66 | Jumbo frames: 15000 | Jumbo frames support: Yes | MAC address table: 8000 | Packet buffer memory: 4 | Store-and-forward: Yes | Switching capacity: 56 | DHCP features: DHCP client | IGMP snooping: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Multicast support: Yes | Housing material: Metal | LED indicators: Yes | Number of fans: 2 | Product colour: Black | Rack mounting: Yes | Fanless: No | Firmware upgradeable: Yes | Flash memory: 64 | Mean time between failures (MTBF): 224143 | Noise level: 46.2 | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Power consumption (max): 454.8 | Power source: AC | Power supply included: Yes | Surge protection: Yes | Surge protection voltage: 6 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet (PoE) type supported: PoE+ | Power over Ethernet plus (PoE+) ports quantity: 24 | Total Power over Ethernet (PoE) budget: 384 | Heat dissipation: 1546.15 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 45 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 330 | Height: 44 | Width: 440 | Cables included: AC | Manual: Yes | Quick start

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

guide: Yes | Rack mount kit: Yes | Certification: FCC, CE, RoHS | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Series: Omada | Model name: SG2428P | Units per Shipping Box: 1 | Unit Calculated Volume: 0.02491 | Unit Calculated Weight: 6.125

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903