

Epson TM-L90-i label printer Direct thermal 180 x 180 DPI 150 mm/sec Wired

Gamintojas: **EPSON** · Modelis: **C31C412412** · EAN: **8715946533568** · Prekės kodas: **338739**



542,90 €

Kaina su PVM

Be PVM: **448,68 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Direct thermal
- ✓ 180 x 180 DPI
- ✓ Printing colours: Black
- ✓ Maximum printing width: 1.41 mm Print speed: 150 mm/sec
- ✓ Connectivity technology: Wired
- ✓ USB port
- ✓ 1.6 kg

Aprašymas

Intelligent label printer

Print thermal labels directly from devices running popular web browsers - no drivers needed.

Epson TM-L90-i Series

This gives you huge flexibility, as you can use the TM-L90-i with virtually any device and operating system. And as the TM-L90-i can control other Epson printers, it will enable you to add driverless printing capabilities to your existing printers.

The TM-L90-i simplifies servicing and maintenance and reduces your costs. It can be configured directly from web applications and, as it doesn't need a permanent connection to a PC or server, you need fewer pieces of equipment, cutting your energy bills and environmental impact.

Key Features

- Driverless;
- Print directly from web browsers;
- Flexible;
- Works with most devices and OS;
- Printers Hub;

- Controls additional printers;
- Easy maintenance;
- Configure from web applications;
- Saves money;
- Cuts bills and environmental impact.

Techninė specifikacija

Specifications	
Sandėlio grupė	POS > Receipt Printer [+0][-0]
Printing	
Print technology	Direct thermal
Colour	No
Maximum resolution	180 x 180 DPI
Print speed	150 mm/sec
Maximum printing width	1.41 mm
Printing colours	Black
Maximum print height	3.39 mm
Paper handling	
Autocutter	Yes
Maximum roll diameter	9 cm
Autocutter durability	2000000 million cuts
Ports & interfaces	
Connectivity technology	Wired
Wi-Fi	No
USB port	Yes
USB 2.0 ports quantity	1
RS-232 ports	1
Performance	
Print head life	150000000 million characters
Certification	TÜV, CE
Design	
Product colour	Grey
Operational conditions	
Operating relative humidity (H-H)	5 - 45%
Storage relative humidity (H-H)	-10 - 50%

Operating temperature (T-T)	10 - 90 °C
-----------------------------	------------

Storage temperature (T-T)	10 - 90 °C
---------------------------	------------

Weight & dimensions

Width	145 mm
-------	--------

Depth	195 mm
-------	--------

Height	148 mm
--------	--------

Weight	1.6 kg
--------	--------

Packaging data

Quantity per pack	1 pc(s)
-------------------	---------

Package width	190 mm
---------------	--------

Package depth	250 mm
---------------	--------

Package height	240 mm
----------------	--------

Package weight	2.8 kg
----------------	--------

Packaging content

AC adapter included	Yes
---------------------	-----

Logistics data

Products per pallet layer	16 pc(s)
---------------------------	----------

Products per pallet layer (UK)	24 pc(s)
--------------------------------	----------

Products per pallet (UK)	168 pc(s)
--------------------------	-----------

Pallet length (UK)	120 cm
--------------------	--------

Pallet width (UK)	100 cm
-------------------	--------

Pallet height (UK)	179.5 cm
--------------------	----------

Harmonized System (HS) code	84433210
-----------------------------	----------

Pallet gross width	80 cm
--------------------	-------

Pallet gross length	120 cm
---------------------	--------

Pallet gross height	179.5 cm
---------------------	----------

Products per pallet	112 pc(s)
---------------------	-----------

Other features

Buffer size	4 KB
-------------	------

Country of origin	China
-------------------	-------

Cabling technology	10/100Base-T(X)
--------------------	-----------------

Matmenys ir svoris

Matmenys (I × P × A)	26,00cm × 24,00cm × 20,00cm
----------------------	-----------------------------

Svoris	2,77kg
--------	--------