

AOC 24B3HA2 computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LED Black

Gamintojas: **AOC** · Modelis: **24B3HA2** · EAN: **4038986151481** · Prekės kodas: **340904**



102,90 €

Kaina su PVM

Be PVM: **85,04 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 60.5 cm (23.8") LED IPS
- ✓ Full HD 1920 x 1080 pixels 16:9
- ✓ 120 Hz 4 ms 250 cd/m² 1500:1
- ✓ Flicker-free technology
- ✓ E 18 kWh 20 W



Aprašymas

High-performance clarity with 23.8" FHD monitor featuring 120Hz refresh rate and HDMI

Dive into the extraordinary world of crystal-clear visuals and vibrant colors with our solid 24-inch FHD IPS Monitor. Elevate your viewing experience to new heights as every detail comes alive on the compact screen, making your content truly immersive. Experience smooth 120Hz refresh rate, ensuring each frame is a visual delight. No more lag or motion blur – just pure and clear for eye pleasure. The 1ms MPRT takes your working experience to the next level, making fast-paced scenes sharper and more exhilarating. 24B3HA2 isn't just about visuals; it's a feast for your ears too. Enjoy rich sound with built-in 2W speakers, turning every movie night or watching multimedia session into action which can fulfil basic audio needs without the need for additional audio equipment. Sleek and stylish narrow borders provide you with more screen real estate, featuring a 9.5mm ultra-narrow chin that is almost half as thin as standard monitors. Lastly, the low blue light feature ensures your eyes stay fresh during extended use. This is a statement piece for your setup.

Techninė specifikacija

Specifications	
Sandėlio grupė	Displays > Led Small Format [+0][-0]
Display	
Display diagonal	60.5 cm (23.8")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	No
HD type	Full HD
Panel type	IPS
Response time	4 ms
Screen shape	Flat
Contrast ratio (typical)	1500:1
Maximum refresh rate	120 Hz
Display number of colours	16.7 million colours
LED backlight	Yes
Backlight type	W-LED
Display brightness (typical)	250 cd/m²
Response time measurement type	GTG (Gray to Gray)
Response time (MPRT)	1 ms
Anti-glare screen	Yes
Aspect ratio	16:9
Contrast ratio (dynamic)	20000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Response time (fast)	1 ms
Pixel pitch	0.2745 x 0.2745 mm
Pixel density	93 ppi
Vertical scan range	48 - 100 Hz
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm
Digital horizontal frequency	30 - 115 kHz
Digital vertical frequency	48 - 100 Hz

Display diagonal (metric)	60.5 cm
High Dynamic Range (HDR) supported	Yes
Haze rate	25%
Surface hardness	3H
sRGB coverage (typical)	95.2%
NTSC coverage (typical)	83%
Adobe RGB coverage	81.6%
DCI-P3 coverage	73.8%
Performance	
VESA Adaptive Sync support	Yes
Flicker-free technology	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	4 W
Design	
Market positioning	Home
Product colour	Black
Frameless design	Yes
Front bezel colour	Black
Detachable stand	Yes
Ports & interfaces	
Built-in USB hub	No
HDMI	Yes
VGA (D-Sub) ports quantity	1
DVI port	No
HDMI ports quantity	1
HDMI version	1.4
Audio output	Yes
HDCP	Yes
HDCP version	1.4
AC (power) in	Yes
Network	

Ethernet LAN	No
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	-5 - 25°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, Dutch, English, Finnish, French, German, Italian, Japanese, Korean, Croatian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Ukrainian
Plug and Play	Yes
LED indicators	Status
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	E
Energy consumption (SDR) per 1000 hours	18 kWh
Power consumption (typical)	20 W
Power consumption (standby)	0.5 W
Power consumption (max)	32 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-25 - 55 °C
Operating relative humidity (H-H)	10 - 85%
Storage relative humidity (H-H)	5 - 93%
Operating altitude	0 - 5000 m
Non-operating altitude	0 - 12192 m
Weight & dimensions	
Width (with stand)	542.4 mm
Depth (with stand)	202.3 mm

Height (with stand)	412.1 mm
Weight (with stand)	2.97 kg
Width (without stand)	542.4 mm
Depth (without stand)	44.6 mm
Height (without stand)	316.2 mm
Weight (without stand)	2.65 kg
Packaging data	
Package width	614 mm
Package depth	126 mm
Package height	394 mm
Package weight	4.65 kg
Package type	Box
Packaging content	
Cables included	AC, HDMI
HDMI cable length	1.5 m
Sustainability	
Doesn't contain	Mercury, PVC/BFR
Other features	
Low input lag	No
Local dimming	Yes
Warranty period	3 year(s)
Compliance certificates	CE
Mean time between failures (MTBF)	50000 h
Certification	WEEE, REACH compliant, RoHS compliant, CB, TUV-Bauart-Mark, ISO 9241-307, EAC, FCC
Matmenys ir svoris	
Matmenys (I × P × A)	62,00cm × 40,00cm × 13,00cm
Svoris	4,54kg