

LG 75XS4G ženklų ekranas Skaitmeninis informacinis plokščias ekranas 190,5 cm (75") IPS 4000 cd/m² 4K Ultra HD Juoda

Gamintojas: **LG** · Modelis: **75XS4G-B.AEU** · EAN: **8806091087324** · Prekės kodas: **343511**



10 013,90 €

Kaina su PVM

Be PVM: **8 275,95 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vidaus Skaitmeninis informacinis plokščias ekranas Juoda
- ✓ Ethernet LAN jungtis
- ✓ 190,5 cm (75") 3840 x 2160 pikseliai IPS 4000 cd/m²
- ✓ Įmontuoti garsiakalbiai 10 W



Aprašymas

Make Your Content Stand Out beyond Window with the Outstanding Visibility

Deliver Your Message with High Visibility Even Under the Strong Sunlight With a great brightness of 4,000 nits** and UHD picture quality, 75XS4G clearly deliver contents and attract public attention, which is the ultimate display for outdoor visibility.

High Energy Efficiency

The 75XS4G is *energy efficient, allowing for an efficient total cost management while showing content in UHD resolution even with 4,000 nits of high brightness.

Space Blending Slim Design

Given that window-facing displays are usually installed indoors close to the window, 75XS4G's slim design is useful as it can blend naturally inside the store.

Double-sided Usage with Dedicated Bracket

Due to the 75XS4G flat-back design and dedicated bracket*, store owner can attach LG's UHD display** to the back for the purpose of displaying a variety of content for both external and internal customers.

Wide Operating

Temperature Range

75XS4G can operate at various temperatures of 0-40°C.

Conformal Coating

*Conformal Coating improves reliability of the circuit board, power board by protecting it against dust, iron powder, humidity, etc.

High Performance with webOS

Quad Core SoC* can execute several tasks at the same time without a separate media player.

In addition, webOS 4.1 platform enhances user convenience with intuitive UI and simple app development tools.

Multiple Display Control with a Remote Control

Multiple device controls are available through the RJ45 & RS-232C ports.

It means that even double-sided displays can be easily controlled simultaneously with a remote control.

Easy Content Distribution

& SW Update

75XS4G features embedded Wi-Fi, Bluetooth, Beacon making it easy to distribute content wirelessly and update Firmware. In particular, using Beacon and BLE (Bluetooth Low Energy),

Shop manager can do various promotional activities, such as providing promotional coupons or product information to visitor in real time.

Web Monitoring (Control Manager)

This web-based monitoring solution is user-friendly and allows the user to be at ease. It enables the user to have full access anywhere at anytime from their mobile phone while having access to both current and past data. It allows the user to monitor the unit, make adjustments, and control the unit remotely in real time.

Precise Installation Using Leveler Tool The 75XS4G is equipped with a "Leveler Tool" which shows users how the device is tilt, so the display can be precisely installed.

Alert for Right Direction

The 75XS4G is equipped with a "horizontal sensor", so the display can be installed accurately.

Techninė specifikacija

Ekranas

Ekranas įstrižainė

190,5 cm (75")

Ekrano technologija	IPS
Ekrano rezoliucija	3840 x 2160 pikseliai
Ekrano ryškumas	4000 cd/m²
HD tipas	4K Ultra HD
Natūralus kraštinių santykis	16:9
Ryšys	
HDMI portų kiekis	2
„DisplayPort“ kiekis	1
RS-232 sąsaja	Taip
RS-232C	Taip
Garsas	
Įmontuoti garsiakalbiai	Taip
Įmontuotų garsakalbių skaičius	2
RMS galingumas	10 W
Konstrukcija	
Gaminio konstrukcija	Skaitmeninis informacinis plokščias ekranas
Produkto spalva	Juoda
Talpinimas palaikomas	Vidaus
VESA tvirtinimo pagrindas	Taip
Orientacija	Horizontalus
Suderinama su VESA sienos tvirtinimo sistema	600 x 400 mm
Veikimo charakteristikos	
Paskirtis	Komercinis
HDCP	Taip
HDCP versija	2.2
Energijos valdymas	
Energijos suvartojimas	750 W
Svoris ir matmenys	
Plotis	1679,2 mm
Ilgis	104 mm
Aukštis	957,6 mm
Pakuotės duomenys	
Paketo svoris	50 kg
Logistikos duomenys	

Darniosios sistemos (DS) kodas	85285210
--------------------------------	----------

Tinklas

Ethernet LAN jungtis	Taip
----------------------	------

Kitos savybės

Energijos vartojimo efektyvumo klasė (sena)	A
---	---

Matmenys ir svoris

Matmenys (I × P × A)	181,00cm × 29,00cm × 110,00cm
----------------------	-------------------------------

Svoris	57,20kg
--------	---------