



**Canon EOS R100
Mirrorless
Camera + RF-S
18-45mm F4.5-
6.3 IS STM Lens
6052C013
Megapixel 24.1
MP ISO
sensitivity (max)
12800 Display
diagonal 3.0 Wi-
Fi Automatic,
manual CMOS
Black**

Modelis: 6052C013

Gamintojas: CANON

EAN: 4549292214598

Prekės kodas: 344318

618.99€ ~~759.99€~~

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Gross depth (mm): 88.00 | Gross height (mm): 108.00 | Gross weight: 0.44 | Gross width (mm): 146.30 | Net weight: 0.36 | Packing quantity: 1.00 | Paper/Pasteboard: 50.00 | Plastic (No PET): 30.00 | Tare weight (kg): 0.08 | TI weight (kg): 0.02 | Volume (m3): 0.00 | Classification of battery: CL126:NE:2016-12-09 | Composition of battery: CL127:KT:2016-12-09 | Type of battery: Accumulator | Embeeded battery: Yes | WEEE tax: Yes | WEE classification: CL109:5:2017-04-01 | Palette Qty: 1243 | ISO sensitivity (max): 12800 | Image sensor size (W x H): 2.23x1.49 | Producer product name: 6052C013 | Megapixel: 24.1 | Fastest camera shutter speed: 1/4000 to 30 | Maximum video resolution: 3840 x 2160 | Sensor type: CMOS | Self-timer: 2 | Operating relative humidity (H-H): 0 to 85 | Viewfinder type: 0.39-type OLED electronic viewfinder | White balance: AWB (ambience priority/white priority), Daylight, Shadow, Cloudy, Tungsten, Fluorescent, Flash, Custom, Color temperature setting | HDMI: 1x HDMI (Micro-Type-D connector) | Display aspect ratio: 3:2 | Viewfinder: Yes | Dimensions (WxDxH): 116.3 x 68.8 x 85.5 | Flash exposure compensation: +/- 2 EV in 1/3 step increments | Wi-Fi: Yes | Video formats supported: MPEG-4 AVC/H.264 | USB version: USB 2.0 | Image formats supported: JPEG, RAW | Operating temperature (T-T): 0 to 40 | Flash sync-speed: 1/250 | Video resolutions: 3840 x 2160, 1920 x 1080, 1280 x 720 | ISO sensitivity: 100-12800 | Battery type: Rechargeable lithium-ion battery LP-E17 | Auto focusing (AF) modes: AF+MF available (manual focus adjustment after One Shot AF) Enhance image available under MF (3-10x, in 0.1x increment) | Flash modes: Auto fire from E-TTL II flash measurement (Face Priority/Evaluative/Average) | Display: LCD (TFT) | Battery technology: LP-E17 | Lens mount interface: RF-S | Full HD: Yes | Display diagonal: 3.0 | Focus: Automatic, manual | Shooting modes: Stills: Scene Intelligent Auto Hybrid Auto SCN Special Scene Modes (x10) - Portrait - Landscape - Sports - Panning- Close Shots - Food - Night Portrait - Handheld Night Scene - HDR Backlight Control | Colour of product: Black | Touchscreen: No | Producer product family: EOS R100 Mirrorless Camera + RF-S 18-45mm F4.5-6.3 IS STM Lens | Producer: Canon | Warranty: 12